

# Delock M.2 Docking Station for 2 x M.2 NVMe PCIe SSD with Clone function

## Description

This M.2 docking station by Delock enables the installation of **two M.2 PCIe NVMe SSDs** and it can be connected via USB to the PC or laptop. The included USB cable allows the connection to a free USB-C™ port.

### M.2 PCIe SSD clone function

The clone function enables to **copy the content of one SSD to another** without using a PC.

### Good cooling

A **fan in the bottom area** of the docking station ensures sufficient cooling of the SSDs used, so that the operation also works without problems with closed lid.

### Suitable as transport box

Due to the elegant design and the specially designed lid, the docking station is also suitable as a **transport box for two M.2 memories**.



## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 2 x 67 pin M.2 key M slot
  - 1 x DC jack
- Chipset: Asmedia ASM2362
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVMe Express (NVMe)
- Data transfer rate up to 10 Gbps
- Supports UASP
- LED indicator for power, access and copy status
- Function key:
  - 1 x Clone button
  - 1 x On / Off switch
- Dimensions (LxWxH): ca. 132 x 93 x 93 mm
- Hot Plug, Plug & Play

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.5 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 10 mm

## System requirements

- Android 9.0 or above
- Chrome OS 83.0 or above
- iPad Pro (2018)
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

## Package content

## Item no. 63331

EAN: 4043619633319

Country of origin: China

Package: • Retail Box

- M.2 docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- External power supply 12 V / 2 A
- User manual

### Images



General	
Function:	Clone Function
Supported operating system:	Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit iPad Pro (2018) Android 9.0 or above Chrome OS 83.0 or above Linux Kernel 5.4 or above Mac OS 10.15.6 or above
Slot:	PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
Connector 2:	2 x 67 pin M.2 key M slot
connector 3:	1 x DC jack
Technical characteristics	
Data transfer rate:	10 Gbps
Physical characteristics	
Length:	132 mm
Width:	93 mm
Height:	93 mm
Colour:	white