

BenQ EW600 dataprojektori Vakioprojektori 3600 ANSI lumenia DLP WXGA (1280x800) 3D Valkoinen

Tuotemerkki : BenQ Tuotekoodi: 9H.JLT77.1HE

Tuotteen nimi: EW600

BenQ EW600. Projektorin kirkkaus: 3600 ANSI lumenia, Projektioteknologia: DLP, Projektorin oletusresoluutio: WXGA (1280x800). Valonlähteen tyyppi: Lamppu, Valonlähteen käyttöikä: 5000 h, Valonlähteen käyttöikä (säästötila): 10000 h. Tarkennus: Ohje, Polttovälialue: 22 - 24.1 mm, Zoomaussuhde: 1.1:1. Analogisen signaalin järjestelmä: NTSC, PAL, SECAM, Tuetut 3D-formaatit: Peräkkäiset kuvat, Kuvan pakkaus, Vierekkäin, Ylhäällä ja alhaalla, Tuetut grafiikan erottelutarkkuudet: 640 x 480 (VGA), 1920 x 1200 (WUXGA). Sarjaliitännän tyyppi: RS-232, HDMI/liitäntätyyppi: Täysikokoinen, HDMI-versio: 1.4a





Projector		Ports & interfaces	
Supported aspect ratios	4:3, 16:10, 16:9	HDMI ports quantity *	1
Smart projector *	✓	DVI port *	×
Screen size compatibility *	762 - 7620 mm (30 - 300") 3600 ANSI lumens DLP WXGA (1280x800) 20000:1	Network	
Projector brightness * Projection technology *		Smart TV *	×
Projector native resolution * Contrast ratio (typical) *		Ethernet LAN * Wi-Fi *	× •
Native aspect ratio * Number of colours	16:10 1.07 billion colours	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Horizontal scan range	15 - 102 kHz	Bluetooth	✓
Vertical scan range	23 - 120 Hz	Bluetooth version	4.0
Keystone correction, vertical	-40 - 40°	Storage	
Matrix size	1.65 cm (0.65")	Card reader integrated *	×
Matrix type	DMD	Features	
Light source		Interactive *	
Light source type *	Lamp		X
Service life of light source *	5000 h	Noise level (economic mode)	29 dB
Service life of light source (economic mode)	10000 h	HDCP On Screen Display (OSD)	✓ ✓
Lamp power	200 W	Number of OSD languages	30
Lamps quantity	1 lamp(s)	Noise level *	33 dB
Lens system		AirPlay	✓
Focus *	Manual	Multimedia	
Focal length range	22 - 24.1 mm	Built-in speaker(s) *	√
Zoom capability	1	- 1 op 01 (0)	2 W
Zoom ratio	1.1:1		
Throw ratio	1.55~1.7:1		±
Offset	100%		

Wide		D. ciam	
Video		Design	
Analog signal format system *	NTSC, PAL, SECAM	Market positioning *	Business
Full HD *	×	Product type *	Standard throw projector
3D *	✓	Product colour *	White
Supported 3D formats	Frame Sequential, Frame packing, Side by side, Top and bottom 640 x 480 (VGA), 1920 x 1200 (WUXGA)	Power	
Supported graphics resolutions		Power source *	AC
		Power consumption (typical) *	270 W
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i,	Power consumption (standby) *	0.5 W
Supported video modes	1080p	Power consumption (max)	320 W
Video colour modes	Presentation, sRGB	Power consumption (economy mode)	235 W
Ports & interfaces		Operational conditions	
HDMI connector type	Full-size	Operating temperature (T-T)	0 - 40 °C
HDMI version	1.4a		0 - 40 C
USB 2.0 ports quantity	3	Weight & dimensions	
Mini-USB 2.0 ports quantity	1	Width	296 mm
Headphone outputs	1	Depth	232 mm
Serial interface type *	RS-232	Height	120 mm
PC Audio in	✓	Weight *	2.5 kg
VGA (D-Sub) ports quantity *	2	Packaging content	
		Remote control included *	✓
		Remote control type	IR
		Batteries included	✓
		Cables included	AC, VGA
		Logistics data	
		Harmonized System (HS) code	85286200

