

VC70 Technical Accessory Guide



NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any third-party products, accessories, or hardware. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Communication Cables and Accessories Part Number Picture Description Notes Required Items USB to ActiveSync PC/Host 25-124330-01R ►Micro USB connection on VC70 end cable ►USB cable locks onto VC70 using two screws Coiled cable is 12 ft long when extended and is about 5 ft. long when un-extended. CBA-UF7-C12ZAR VC70N0 to 36xx Cable (USB) ▶Rated to -30°C for freezer environment use. ►When connected to STB3678/FLB3678, will charge a fully depleted battery in about 10 hours (provides 500 maH current to cradle). ►USB cable locks onto VC70 using two ►Coiled cable is 9 ft long when extended (even though SKU indicates VC70 to 36xx Scanner Cable CBA-UF2-C12ZAR 12 ft.) and is about 5 ft. long when un-(USB) extended. Use CBA-UF7-C12ZAR for a true 12 ft. length cable. ►Rated to -30°C for freezer environment use. ▶Improved performance in freezer environments vs. 25-159548-01. The conductor insulation material was changed to a stiffer material so the copper does not flex at as sharp an VC70 to 34xx/35xx Scanner 25-159548-02 angle, resulting in a longer bend life. Cable (USB) ►USB cable locks onto VC70 using two screws ► Provides enough power for DS3508-ER ▶ 12 ft long when extended Discontinued 4/2016, now use 25-159548-02 - PMB 2712 ►USB cable locks onto VC70 using two VC70 to 34xx/35xx Scanner 25-159548-01 Cable (USB) ► Provides enough power for DS3508-ER ▶ 12 ft long when extended

CBA-RF3-C09ZAR	VC70 to 36xx Scanner Cable (Serial)	➤VC70 provides power to scanner on pin 9 (COM1 or COM2 using 25-159547-01 Adapter Cable). ➤Provides enough power for DS3608-ER in default power mode. ➤VC70 Control Panel applet must be configured to power the COM port. ➤Scanner can be used in native SSI mode for additional scanner control. ➤Rated to -30°C for freezer environment use. ➤Cable provides TTL to RS232 signal conversion for improved performance with VC70.	
CBA-R49-C09ZAR	VC70 to 34xx/35xx Scanner Cable - (Serial)	*VC70 provides power to scanner on pin 9 (COM1 or COM2 using 25-159547-01 Adapter Cable). *Provides enough power for DS3508-ER. *VC70 Control Panel applet must be configured to power the COM port. *Scanner can be used in native SSI mode for additional scanner control. *9 ft. coiled cable *Cable and strain relief are rated for freezer environment use (-30°C) and will provide better performance in nonfreezer environments also. *Cable provides TTL to RS232 signal conversion for improved performance with VC70.	
CBA-R37-C09ZBR	VC70 to 34xx/35xx Scanner Cable (Serial)	➤ Recommend using CBA-R49-C09ZAR instead ➤ VC70 provides power to scanner on pin 9 (COM1 or COM2 using 25-159547-01 Adapter Cable). ➤ Provides enough power for DS3508-ER. ➤ VC70 Control Panel applet must be configured to power the COM port. ➤ Scanner can be used in native SSI mode for additional scanner control. ➤ 9 ft. coiled cable ► Includes improved TTL current limit protection vs. CBA-R37-C09ZAR.	
CBA-R37-C09ZAR	VC70 to 34xx/35xx Scanner Cable (Serial)	➤Recommend using CBA-R49- C09ZAR instead ➤VC70 provides power to scanner on pin 9 (COM1 or COM2 using 25- 159547-01 Adapter Cable). ➤Provides enough power for DS3508- ER. ➤VC70 Control Panel applet must be configured to power the COM port. ➤Scanner can be used in native SSI mode for additional scanner control. ➤9 ft. coiled cable ➤Includes improved strain relief design over CBA-R36-C09ZAR	
CBA-R36-C09ZAR	VC70 to 34xx/35xx Scanner Cable (Serial)	*Discontinued 3/2013, now use CBA-R37-C09ZAR *VC70 provides power to scanner on pin 9 (COM1 or COM2 using 25-159547-01 Adapter Cable). *Provides enough power for DS3508-ER. *VC70 Control Panel applet must be configured to power the COM port. *Scanner can be used in native SSI mode for additional scanner control. *9 ft. coiled cable	

	T		,
25-159547-01	DB15 to DB9 Converter Cable for COM2 Port	➤ Connects to the DB15 COM2+CAN- Bus port on VC70 and converts to a standard DB9 male connector. ➤ Can be used to connect equipment with RS232 interface when CAN-bus interface is not needed. ➤ 6" long cable	
P1031365-053	QLn/ZQ6 Series Printer Serial Cable	➤Connects to serial port on VC70 ➤6 ft. straight cable	
P1031365-055	QLn/ZQ6 Series Printer USB Cable	➤Connects to USB port on VC70 ➤6 ft. straight cable	
KT-SPKR-01R	External Speaker kit	➤Includes External Speaker (HSN4040A) and Speaker Adapter Cable (25-159552-01). ➤VC70 internal speaker will be disabled when adapter cable is attached.	
HSN4040A	External Speaker	►Motorola HSN4040A ►13 Watt water-resistant loudspeaker	Speaker Adapter Cable (25- 159552-01)
25-159552-01	Speaker Adapter cable	➤Connects VC70 (Speaker port) to external speaker ➤VC70 internal speaker will be disabled when cable is attached.	External Speaker (HSN4040A)
KT-MIC-01R	External Push-To-Talk (PTT) Microphone Kit	Discontinued 12/2011 External side-mount PTT microphone GCAI (water resistant) Includes Side Mount Bracket (KT-ACCMNT-VC70-R) Includes clip for attaching mic to the Side Mount Bracket (KT-ACCMNT-VC70-R) Includes screws for mounting the microphone clip to the bracket	
HMN1089B (3rd party)* Can be ordered through Motorola partner BearCom: +1-214-765-7116 http://www.bearcom.com/	Motorola External Push-To- Talk (PTT) Microphone	►External side-mount PTT microphone ►GCAI (water resistant) ►Includes clip for attaching mic to the Side Mount Bracket (KT-ACCMNT- VC70-R)	Side Mount Bracket (KT-ACCMNT-VC70-R) for mounting mic on the side of the VC70

KT-SCANMNT-VC70-R		Scanner Mount	►Used to mount an external Scanner (i.e. LS/DS 34xx/35xx) on the side of the VC70. ►Eliminates the need for a scanner Tool Balancer/Pulley ►LI36xx/DS36xx will not fit properly in this mount unless it is bent a little to make the bracket/mount wider.	Side Mount Bracket (KT-ACCMNT-VC70-R) for mounting scanner mount on the side of the VC70
KT-ACCMNT-VC70-R		Accessory Side Mount Bracket	►Used to mount the External PTT Microphone or barcode scanner on the side of the VC70. ►Includes screws for mounting the accessory (Mic or Scanner) to the bracket	
Misc				
Part Number	Picture	Description	Notes	Required Items
KT-U-MOUNT-VC70-R		U Mount Bracket w/ hardware	►Attaches to VC70 shock mount plate. ►Includes mounting hardware ►Includes screws allowing the DC Power Supply (PWRS-9-60VDC-01R) to be mounted to the back of the VC70 on the shock plate. ►Bracket uses the same vehicle mounting holes as the VC5090 bracket for easy migration. ►NOTE: Existing VC5090 U-Mount bracket can't be used with the VC70.	
KT-VC50ARM3-VC70-R	5 1	VC70 to VC5090 Mounting Bracket Adapter Kit (Short)	►Allows existing VC5090 U Mount bracket to be used with VC70 ►Short bracket (3.5") ►Includes mounting bolts	
KT-VC50ARM7-VC70-R		VC70 to VC5090 Mounting Bracket Adapter Kit (Long)	►Allows existing VC5090 U Mount bracket to be used with VC70 ►Long bracket (7") ►Includes mounting bolts	
RAM-D-2461U-MOTO7		RAM Mount with Bridge	Attaches to VC70 shock mount plate. Includes D-size ball attachment with VESA 75 interface Includes screws allowing the DC Power Supply (PWRS-9-60VDC-01R) to be mounted to the back of the VC70 on the shock plate. Uses RAM Mount P/N RAM-D-2461U and includes hardware to attach to VC70.	Typicallly used along with the following: 1. RAM Double Socket Arm 2. RAM Clamp Base, Rail Base or Round Plate Base. Refer to Common Mounting Systems TAG for details.

EMC Product Line - VC70 TAG

RAM-D-2461U-MOTO7B		RAM Mount without Bridge	*Connects directly to VC70 shock plate. *Includes D-size ball attachment with VESA 75 interface and screws for mounting Ball Plate to the VC70's shock mount plate. *Power Supply (PWRS-9-60VDC-01R) CAN'T be mounted to the shock mount plate. It must be mounted remotely *Uses RAM Mount P/N RAM-D-2461U and includes hardware to attach to VC70.	▶Power Supply Extension Cable (25-159549-01) for remotely mounting Power Supply. ▶Typicallly used along with the following: 1. RAM Double Socket Arm 2. RAM Clamp Base, Rail Base or Round Plate Base. Refer to Common Mounting Systems TAG for details.
(3rd party) * http://www.ram-mount.com	PRODUCT NUMBER: NAME 1-201U PRODUCT NUMBER: NAME 1-2470-4 PRODUCT NUMBER: NAME 0-24611-MOTTO'S	RAM mounting arms	Refer to RAM Mounts web site for the required arm and base and search for VC70	
KT-STYLUS01-10R		Stylus (pack of 10)		
KT-SPRTCT-VC70-05R		Spare/Replacement Screen Protector (pack of 5)		
SG-VC70-VISR1-01	00000	Sun Visor	Mountable with cut out wing on right side of VC70 Includes drop-down screen cover Attaches to VC70 using screws	
AD1931DW (3rd party) *		Sun Visor / Hood	▶Reduce screen glare without adding bulk. ▶Attaches around screen with heavyduty adhesive hook and loop. ▶Removable and reattachable.	
BTRY-VC70IAB00	THE SECOND	Spare/Replacement Uninterruptable Power Supply (UPS)	*Provides for host session persistence during vehicle battery replacement *30+ minutes typical. VC70 display will remain on (dim), WLAN radio remains on. Keyboard and other USB accessories (scanner) will be disabled while on UPS power. *Once UPS 30+ minute backup is depleted, VC70 will go into suspend mode and RAM will be protected for up to 72 hours.	

8508851K46	WAS PAID If the control of the cont	External antenna for indoor/outdoor use	*Discontinued 2/2019 - see PMB 10057. *Used when the VC70 is used in indoor/outdoor areas where an externally mounted antenna is needed for better coverage. *2.4GHZ Min/5.9GHZ Max, 0 DBI *Requires a ground plane which can be fabricated using the instructions in the VC70 Integrator's Guide.	
WTS2450-RPSMA (3rd party) *		External antenna for Indoor use	*Used when the VC70 is used in indoor areas where an externally mounted antenna is needed for better coverage. *4.5 - 5.5 DBI GAIN ANTENNA	RPSMA-RTRPSMA antenna adapter
RPSMA-RTRPSMA-05R (5 pack) RPSMA-RTRPSMA-10R (10 pack)	a sale	External Antenna adapter	*Adapter allows standard external antennas to be attached to VC70 external antenna connector *RP-SMA to RTRP-SMA	
8508851K46 (3rd party) *		External antenna for indoor use	*Used when the VC70 is used in indoor areas where an externally mounted antenna is needed for better coverage. *2.4 & 5 GHZ 802.11 a/b/g/n WI-FI. *Includes 4.5 - 5.5 DBI GAIN ANTENNA + MAGNETIC MOUNT WITH 12 FT CABLE & RT/RP-SMA MALE	
KT-DSCNT-VC70-05R		Replacement Desiccant packs - Package of 5	*Once desiccant pack is used in each VC70. *VC70 Control Panel applet can be enabled to monitor the device's internal humidity level and will alert user when desiccant pack needs to be replaced.	
3rd party * http://www.lindy-usa.com/us	b-port-blocker-pack-of-4-color-code-white-4	Locking USB port cover/insert	*Prevents unauthorized access/use of USB ports on bottom of VC70 *Requires "key" to install and remove the USB insert *Covers/inserts can be ordered in different colors, each color having a unique "key"	
B350-XT (3rd party) * http://www.blueparrott.com		BlueParrott Bluetooth Headset for voice directed applications	*Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 24 hours talk time. *Works with StoneStreet Bluetooth stack. Will not function with Microsoft BT stack or voice applications that depend on the Microsoft BT stack. *Allows the use of other BT devices (i.e. RS507 scanner or mobile printer)	►May require Bluetooth Wideband Speech CAB file from support site to enable StoneStreet BT stack wideband (16 Khz) audio support.

3PTY-VXI-B350XT (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications	*Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 24 hours talk time. *Works with StoneStreet Bluetooth stack. Will not function with Microsoft BT stack or voice applications that depend on the Microsoft BT stack. *Allows the use of other BT devices (i.e. RS507 scanner or mobile printer) *Zebra Compatible certification for VDP application use with MC32.	May require Bluetooth Wideband Speech CAB file from support site to enable StoneStreet BT stack wideband (16 Khz) audio support.
3PTY-VXI-B250XTP (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications ZEBRA Compatible	*Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 20 hours talk time. *Works with StoneStreet Bluetooth stack. Will not function with Microsoft BT stack or voice applications that depend on the Microsoft BT stack. *Allows the use of other BT devices (i.e. RS507 scanner or mobile printer)	►May require Bluetooth Wideband Speech CAB file from support site to enable StoneStreet BT stack wideband (16 Khz) audio support.
3PTY-VXI-EXPWAYII (Zebra orderable SkU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications	*Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls *Works with StoneStreet Bluetooth stack. Will not function with Microsoft BT stack or voice applications that depend on the Microsoft BT stack. *Provides 8 hours talk time. *Allows the use of other BT devices (i.e. RS507 scanner or mobile printer) *Zebra Compatible certification for VDP application use with MC92, VC70, WT41 and MC32.	➤ May require Bluetooth Wideband Speech CAB file from support site to enable StoneStreet BT stack wideband (16 Khz) audio support.
Power Cords				
Part Number	Picture	Description	Notes	Required Items
PWRS-9-60VDC-01R		DC Power Supply	▶9-60VDC, 12VDC, Up to 10A ▶Can be used with electric or gas fork lifts. ▶Can be mounted to the back of the VC70 when the U Mount Bracket (KT-U-MOUNT-VC70-R) is used.	DC Power Cable (25-159551- 01)

Document Update date: 9/16/19

25-159551-01	DC Power Cable (9-60 VDC)	Cable connect vehicle battery to DC Power Supply Works with gas and electric vehicles (9-60VDC) Includes vehicle ignition sense wire. Wire must be connected to positive terminal of vehicle battery if not connected to ignition. 10 ft. long cable Includes fuse.	DC Power Supply (PWRS-9- 60VDC-01R)
25-159551-02	DC Power Cable (36-96 VDC)	➤Cable connect vehicle battery to DC Power Supply ➤Works with electric vehicles (36-96 VDC) ➤Includes vehicle ignition sense wire. Wire must be connected to positive terminal of vehicle battery if not connected to ignition. ➤10 ft. long cable ➤Includes fuse.	DC Power Supply (PWRS-9- 60VDC-01R)
25-159553-01	VC5090 DC Power Cable Adapter	➤ Allows a vehicle wired for the VC5090 to use the VC70. ➤ Connects the VC5090 Forklift Power cable to the VC70 DC Power Supply ➤ 2 ft. long cable ➤ Includes fuse. The fuse must be used to replace the existing fuse in the VC5090 Forklift Power cable.	*DC Power Supply (PWRS-9-60VDC-01R) *VC5090 Forklift Power cable (25-71919-01R, 25-71919-02R, 25-71919-04R)
25-159549-01	Power Supply Cable Extender	➤ Allows the DC Power Supply (PWRS-9-60VDC-01R) to be mounted further from the VC70 (i.e. when not mounted to the back of the VC70) ➤ 6.5 ft. long cable	DC Power Supply (PWRS-9- 60VDC-01R)
CBL-DC-389A1-01	AC Brick Power Cable	►Used with Power Supply PWR-BGA12V108W0WW to connect VC to AC power supply ►Cable is 6.5 ft long	
25-159550-01	AC Brick Power Cable	➤Used with Power Supply PWRS- 14000-241R to connect VC to AC power supply. ➤Cable is 6.5 ft long ➤Discontinued 2/2017, now use CBL- DC-389A1-01 - PMB 2851 and 2933	
PWR-BGA12V108W0WW	Power Supply	➤Used to power VC70 via AC wall outet (for staging, training, demos, etc. ➤100-240 VAC, 12V, 9A, 108W ➤Provides US DOE Level VI compliance for power efficiency. ➤Replaces PWRS-14000-241R	CBL-DC-389A1-01 and 23844- 00-00R
PWRS-14000-241R	Power Supply	▶Replaces 50-14000-241R ▶Used to power VC70 via AC wall outet (for staging, training, demos, etc.) ▶100-240VAC,12VDC,9A ▶Energy Star Compliant ▶Discontinued 2/2017, now use PWR-BGA12V108W0WW - PMB 2851 and 2933	25-159550-01 and 23844-00- 00R

50-14001-004R	Power Supply		25-159550-01 and 23844-00- 00R
50-14000-241R	Power Supply	▶Replaces 50-14001-004 ▶Used to power VC5090 via AC wall outet (for staging, training, demos, etc.) ▶Discontinued 12/2010 - now use PWRS-14000-241R	25-159550-01 and 23844-00- 00R
23844-00-00R	AC Line Cord		

Keyboards
See External Keyboards Technical Accessory Guide (TAG) for additional keyboard options.

	iKey keyboards					
Part Number	Picture	Description	Notes	Required Items		
various		iKey keyboards	See External Keyboards Technical Accessory Guide (TAG) for iKey options.	Keyboard Tray for iKey keyboards (KT-KYBDTRAY- VC70-3)		
KT-KYBDTRAY-VC70-3		Keyboard Tray for iKey or VH10 style keyboards	►Allows iKey or VH10 style keyboards to be mounted under the VC70. ►Includes mounting tray, arms, knobs and screws			
KT-TRAY-VC70-SPRHW		Replacement Hardware Kit for Keyboard Tray	►Includes arms, knobs, screws that are normally included in KT-KYBDTRAY- VC70-3			
RAM-246U	FINANCE CO.	RAM Mount base for iKey or VH10 style Keyboards	▶Provides alternate solution to Keyboard Tray ▶1.5" rubber ball (RAM C size), connected to a 4.75" square plate with 4x100mm holes and 4x75mm holes in each corner. ▶Base attaches to forklift ▶Uses RAM Mount P/N RAM-246U	►RAM Ball Mount for iKey Keyboards (RAM-202U) ►RAM Mount arm for iKey Keyboards (RAM-201U)		

	T	1		1
RAM-201U	A Alba	RAM Mount 3" arm for iKey or VH10 style Keyboards	Provides alternate solution to Keyboard Tray Double socket arm, has a socket at both ends that accommodates 1.5" ball bases (RAM C size). 3 inch length A single spring inside the arm opens the end sockets, allowing you to pivot the ball and socket connection. Connects RAM Mount base for iKey Keyboards (RAM-246U) to RAM Ball Mount for iKey Keyboards (RAM-202U) Uses RAM Mount P/N RAM-201U	•RAM Mount base for iKey Keyboards (RAM-246U) •RAM Ball Mount for iKey Keyboards (RAM-202U)
RAM-202U	AAN CONTRACTOR OF THE PARTY OF	RAM Ball Mount for iKey or VH10 style Keyboards	Provides alternate solution to Keyboard Tray 1.5" diameter rubber ball (RAM C size) connected to a flat 2.5" diameter base. Mount has pre-drilled holes, including the universal AMPS hole pattern. ↑Attaches to mounting holes on iKey or VH10 style keyboards Uses RAM Mount P/N RAM-202U	►RAM Mount base for iKey Keyboards (RAM-246U) ►RAM Mount arm for iKey Keyboards (RAM-201U)
	VH10 styl	e QWERTY/AZERTY	keyboards	
	If F13 and higher keys are require			
Part Number	Picture	Description	Notes	Required Items
			▶Based on the VH10 keyboard design ▶12 direct Function keys with an additional 12 via shift function. ▶Dimmable backlit keys. ▶IP66, -30 to +50 C, condensing - for use in Freezer Applications (when used with freezer use keyboard cables) ▶Build-in heaters and drainage system for error free operations even in heavy condensing environments	

Document Update date: 9/16/19

KYBD-QW-VC70-S-1 (short cable 18 cm/7 in) KYBD-QW-VC70-L-1 (long cable 300 cm/~10 ft)	QWERTY Keyboard Kit (non-freezer use)	▶Based on the VH10 keyboard design ▶12 direct Function keys with an additional 12 via shift function. ▶Dimmable backlift keys. ▶IP66, -30 to +50 C, condensing - for use in Freezer Applications (when used with freezer use keyboard cables) ▶Build-in heaters and drainage system for error free operations even in heavy condensing environments ▶Industrial keyboard controller with temperature compensation ▶Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards ▶Two available cable lengths allowing the installation close the by VC or away from it. ▶Keyboard elastomer and cable are both field replaceable. ▶Can be mounted on Keyboard Tray (KT-KYBDTRAY-VC70-3) or via RAM mount. NOTE: Keyboard will fit on Keyboard Tray KT-KYBDTRAY-VC70-R	
		but additional holes will need to be drilled into this tray to align with screw holes on the keyboard. *Kit includes QWERTY Keyboard (KYBD-QW-VC-01) and Keyboard Cable (CBL-VC70-KBUS1-01 - short OR CBL-VC70-KBUS2-01 - long) *Based on the VH10 keyboard design	
KYBD-QW-VC70F-S-1 (short cable 37 cm/14.5 in) KYBD-QW-VC70F-L-1 (long cable 300 cm/~10 ft)	QWERTY Keyboard Kit (freezer use)	*based on the VHTO keyboard design *12 direct Function keys with an additional 12 via shift function. *Dimmable backlit keys. *IP66, -30 to +50 C, condensing - for use in Freezer Applications (when used with freezer use keyboard cables) *Build-in heaters and drainage system for error free operations even in heavy condensing environments *Industrial keyboard controller with temperature compensation *Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards *Two available cable lengths allowing the installation close the by VC or away from it. *Keyboard elastomer and cable are both field replaceable. *Can be mounted on Keyboard Tray (KT-KYBDTRAY-VC70-3) or via RAM mount. NOTE: Keyboard will fit on Keyboard Tray KT-KYBDTRAY-VC70-R but additional holes will need to be drilled into this tray to align with screw holes on the keyboard. *Kit includes QWERTY Keyboard (KYBD-QW-VC-01) and Keyboard Cable (CBL-VC70-KBUS4-01 - short OR CBL-VC70-KBUS3-01 - long)	

KYBD-AZ-VC-01	DEBERTAL SERVICE DE LA COMPANSION DE LA	AZERTY Keyboard	*Based on the VH10 keyboard design *12 direct Function keys with an additional 12 via shift function. *Dimmable backlit keys. *IP66, -30 to +50 C, condensing - for use in Freezer Applications (when used with freezer use keyboard cables) *Build-in heaters and drainage system for error free operations even in heavy condensing environments *Industrial keyboard controller with temperature compensation *Meets shock/vibrations standards: EN60721-5M3, MIL810F, and Zebra internal testing standards *Two available cable lengths allowing the installation close the by VC or away from it. *Keyboard elastomer and cable are both field replaceable. *Can be mounted on Keyboard Tray (KT-KYBDTRAY-VC70-3) or via RAM mount. NOTE: Keyboard will fit on Keyboard Tray KT-KYBDTRAY-VC70-R but additional holes will need to be drilled into this tray to align with screw holes on the keyboard.	Keyboard Cable (CBL-VC70- KBUS1-01, CBL-VC70-KBUS2- 01, CBL-VC70-KBUS3-01, or CBL-VC70-KBUS4-01)
CBL-VC70-KBUS1-01		VC70 Short Keyboard Cable (non-freezer use)	➤Short Cable length (18 cm / 7 in) ➤Typically used when keyboard is mounted directly near the VC (i.e. on Keyboard Tray) ➤For non-freezer environments - will not provide power for the keyboard's internal heater.	
CBL-VC70-KBUS2-01		VC70 Long Keyboard Cable (non-freezer use)	➤Long Cable length (300 cm / approx. 10 ft) ➤Typically used when keyboard is mounted away from the VC. ➤For non-freezer environments - will not provide power for the keyboard's internal heater.	
CBL-VC70-KBUS4-01		VC70 Short Keyboard Cable (freezer use)	*Short Cable length (37 cm / 14.5 in) *Typically used when keyboard is mounted directly near the VC (i.e. on Keyboard Tray) *For freezer environments - additional RS232 connector on cable will provide power for the keyboard's internal heater. *RS232 connection provides power on pin 9 via VC70's COM1 or COM2 (using 25-159547-01 Adapter Cable). *VC70 Control Panel applet must be configured to power the COM port.	
CBL-VC70-KBUS3-01		VC70 Long Keyboard Cable (freezer use)	Long Cable length (300 cm / approx. 10 ft) Typically used when keyboard is mounted away from the VC. For freezer environments - additional RS232 connector on cable will provide power for the keyboard's internal heater. RS232 connection provides power on pin 9 via VC70's COM1 or COM2 (using 25-159547-01 Adapter Cable). VC70 Control Panel applet must be configured to power the COM port.	

	. .			
KT-KYBDTRAY-VC70-3		Keyboard Tray for iKey or VH10 style keyboards	►Allows iKey or VH10 style keyboards to be mounted under the VC70. ►Includes mounting tray, arms, knobs and screws	
KT-TRAY-VC70-SPRHW		Replacement Hardware Kit for Keyboard Tray	►Includes arms, knobs, screws that are normally included in KT-KYBDTRAY-VC70-3	
RAM-246U	FRANK C	RAM Mount base for iKey or VH10 style Keyboards	Provides alternate solution to Keyboard Tray ▶1.5" rubber ball (RAM C size), connected to a 4.75" square plate with 4x100mm holes and 4x75mm holes in each corner. ▶Base attaches to forklift	►RAM Ball Mount for iKey Keyboards (RAM-202U) ►RAM Mount arm for iKey Keyboards (RAM-201U)
RAM-201U	S.A.M.	RAM Mount 3" arm for iKey or VH10 style Keyboards	*Provides alternate solution to Keyboard Tray *Double socket arm, has a socket at both ends that accommodates 1.5" ball bases (RAM C size). *3 inch length *A single spring inside the arm opens the end sockets, allowing you to pivot the ball and socket connection. *Connects RAM Mount base for iKey Keyboards (RAM-246U) to RAM Ball Mount for iKey Keyboards (RAM-202U)	*RAM Mount base for iKey Keyboards (RAM-246U) *RAM Ball Mount for iKey Keyboards (RAM-202U)
RAM-202U	AAN O	RAM Ball Mount for iKey or VH10 style Keyboards	Provides alternate solution to Keyboard Tray 1.5" diameter rubber ball (RAM C size) connected to a flat 2.5" diameter base. Mount has pre-drilled holes, including the universal AMPS hole pattern. Attaches to mounting holes on iKey or VH10 style keyboards	Keyboards (RAM-246U) ▶RAM Mount arm for iKey Keyboards (RAM-201U)
KYBD-QW-SP-01		Replacement QWERTY Keypad for VH10 style keyboard	*Wear Item Replacement for KYBD-QW- VC-01 (includes Elastomer with hard caps)	
KYBD-AZ-SP-01		Replacement AZERTY Keypad for VH10 style keyboard	►Wear Item Replacement for KYBD-AZ- VC-01 (includes Elastomer with hard caps)	
VC70 style QWERTY/AZERTY keyboards				
Part Number	Picture	Description	Notes	Required Items

KYBD-QW-VC70-03R		65-Key QWERTY Keyboard	*Discontinued 4/2018, now use one of the following VH10 style keyboards: KYBD-QW-VC70F-L-1, KYBD-QW-VC70F-S-1, KYBD-QW-VC70-L-1, or KYBD-QW-VC70-S-1 - PMB 3062 *Connects to USB port on VC70 using a secure locking USB connector. *65 Backlit keys *IP66 sealed *Includes Keyboard Protection Grill (KT-KYBDGRL1-VC70-R)	Mounting Tray (KT- KYBDTRAY -VC70-R)
KYBD-QW-VC70-01R	E 1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	65-Key QWERTY Keyboard	➤Discontinued 9/2013, now use KYBD-QW-VC70-03R ➤Connects to USB port on VC70 using a secure locking USB connector. ➤65 Backlit keys ➤1P66 sealed	Mounting Tray (KT- KYBDTRAY -VC70-R)
KYBD-AZ-VC70-03R		65-Key AZERTY Keyboard	*Discontinued 4/2018, now use the VH10 style keyboard: KYBD-AZ-VC-01 and a keyboard to VC70 keyboard cable (see VH10 style keyboard section above) - PMB 3062 *Connects to USB port on VC70 using a secure locking USB connector. *65 Backlit keys *IP66 sealed *Includes Keyboard Protection Grill (KT-KYBDGRL1-VC70-R)	Mounting Tray (KT- KYBDTRAY -VC70-R)
KYBD-AZ-VC70-01R		65-Key AZERTY Keyboard		Mounting Tray (KT- KYBDTRAY -VC70-R)
KT-KYBDQW-VC70-04R		65-Key QWERTY Keyboard with Mounting Tray	*Discontinued 4/2018, now use the VH10 style keyboard - PMB 3062 *Connects to USB port on VC70 using a secure locking USB connector. *65 Backlit keys *IP66 sealed *Includes Keyboard Protection Grill (KT-KYBDGRL1-VC70-R) and Keyboard Mounting Tray (KT-KYBDTRAY -VC70-R), arms, knobs and screws	
KT-KYBDQW-VC70-02R		65-Key QWERTY Keyboard with Mounting Tray	➤Discontinued 9/2013, now use KYBD-OW-VC70-04R ➤Connects to USB port on VC70 using a secure locking USB connector. ➤65 Backlit keys ➤IP66 sealed ➤Includes Keyboard Mounting Tray (KT-KYBDTRAY -VC70-R), arms, knobs and screws	

KT-KYBDAZ-VC70-04R		65-Key AZERTY Keyboard with Mounting Tray	➤Discontinued 4/2018, now use the VH10 style keyboard - PMB 3062 ➤Connects to USB port on VC70 using a secure locking USB connector. ➤65 Backlit keys ➤IP66 sealed ➤Includes Keyboard Protection Grill (KT-KYBDGRL1-VC70-R) and Keyboard Mounting Tray (KT-KYBDTRAY -VC70-R), arms, knobs and screws		
KT-KYBDAZ-VC70-02R		65-Key AZERTY Keyboard with Mounting Tray	*Discontinued 9/2013, now use KYBDAZ-VC70-04R *Connects to USB port on VC70 using a secure locking USB connector. *65 Backlit keys *IP66 sealed *Includes Keyboard Mounting Tray (KT- KYBDTRAY -VC70-R), arms, knobs and screws		
KT-KYBDTRAY-VC70-R		Keyboard Tray for VC70 Style QWERTY or AZERTY keyboard	Discontinued 4/2018, now use the VH10 style keyboard - PMB 3062 Allows QWERTY or AZERTY keyboard to be mounted under the VC70. Includes mounting tray, arms, knobs and screws NOTE: VH10 Style keyboard will fit on tray, but mounting holes will not line up. Additional holes will need to be drilled into tray to use with this keyboard.		
KT-TRAY-VC70-SPRHW		Replacement Hardware Kit for Keyboard Tray	►Includes arms, knobs, screws that are normally included in KT-KYBDTRAY- VC70-R		
KT-KYBDGRL1-VC70-R		Keyboard Protection Grill for QWERTY or AZERTY keyboard	►Adds extra protection to keys by minimizing the keys' exposure.		
VC5090 style keyboards					
Part Number	Picture	Description	Notes	Required Items	
VC5090KYBD-02R	الم يحد إلى	VC5090 Style External Keyboard (QWERTY style)	➤Uses rugged USB port connector found on VC5090 unit. ➤64 Backlit keys ➤IP66 sealed ➤Heated	Mounting Tray (KT- KYBDTRAY -VC70-R) and VC5090 Keyboard to VC70 Adapter Kit (KT-VC50KYBD- ADPT-R)	

VC5090KYBD-03R		VC5090 Style External Keyboard (AZERTY style)	►Uses rugged USB port connector found on VC5090 unit. ►64 Backlit keys ►IP66 sealed ►Heated	Mounting Tray (KT- KYBDTRAY -VC70-R) and VC5090 Keyboard to VC70 Adapter Kit (KT-VC50KYBD- ADPT-R)	
KT-VC50KYBD-ADPT-R	Left Hand VC70 Spacer Ton Head Screws VC70 Screws Looking Knob with Flat and VC5080 Keyboard Look Walking	VC5090 Keyboard to VC70 Adapter Kit	➤Uses spacers allowing VC5090 keyboard and associated brackets to be attached to VC70. →Also includes adapter cable to connect VC5090 keyboard to USB port on VC70 (P/N 25-163518-01). →Includes adapter cable, 2 spacers and 4 screws.		
VC70 style Numeric keyboard					
Part Number	Picture	Description	Notes	Required Items	
KYBD-NU-VC70-03R		21-Key Numeric Keyboard	*Connects to USB port on VC70 using a secure locking USB connector. *21 Backlit keys *IP66 sealed *Mounts on side of VC70	Keypad Mounting Bracket (KT- KYBDMNT-VC70-R)	
			►Includes Keyboard Protection Grill (KT- KYBDGRL2-VC70-R)		

KT-KYBDNU-VC70-04R		21-Key Numeric Keyboard with Side Mount Bracket	►Connects to USB port on VC70 using a secure locking USB connector. ►21 Backlit keys ►1P66 sealed ►Mounts on side of VC70 ►Includes Keyboard Protection Grill (KT-KYBDGRL2-VC70-R) and Keypad Mounting Bracket (KT-KYBDMNT-VC70-R) with screws	
KT-KYBDNU-VC70-02R		21-Key Numeric Keyboard with Side Mount Bracket	*Discontinued 9/2013, now use KYBD-NU-VC70-04R *Connects to USB port on VC70 using a secure locking USB connector. *21 Backlit keys *IP66 sealed *Mounts on side of VC70 *Includes Keypad Mounting Bracket (KT-KYBDMNT-VC70-R) and screws	
KT-KYBDMNT-VC70-R	3600	Numeric Keyboard Side Mount Bracket	►Allows 21-Key Numeric Keyboard to be mounted to left or right side of the VC70 ►Includes screws	
KT-KYBDGRL2-VC70-R		Keyboard Protection Grill for Numeric keyboard	►Adds extra protection to keys by minimizing the keys' exposure.	