StarTech.com HB31C2A1CGS keskitin USB 3.2 Gen 2 (3.1 Gen 2) Type-C 10000 Mbit/s musta, Harmaa

Tuotemerkki : StarTech.com

Tuotekoodi: HB31C2A1CGS

Tuotteen nimi : HB31C2A1CGS

StarTech.com HB31C2A1CGS. Isäntäkoneen käyttöliittymä: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, Liittimiä: RJ-45, USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Tiedonsiirtonopeus: 10000 Mbit/s, Tuotteen väri: musta, Harmaa, Kotelon materiaali: Alumiini, Muovi. Ethernet-liitännän tyyppi: Nopea Ethernet, Gigabitti Ethernet. Virtalähteen tyyppi: AC, Virrankulutus: 24 W, Tulojännite: 110 - 240 V. Windows-käyttöjärjestelmätuki: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Mac-käyttöjärjestelmätuki: Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High..., Tuetut palvelinkäyttöjärjestelmät: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 x64

Ports & interfaces	
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Hub interfaces *	RJ-45, USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
Ports quantity *	4
Ethernet LAN (RJ-45) ports	1
DC-in jack	✔

Features	
Data transfer rate *	10000 Mbit/s
Product colour	Black, Grey
Housing material	Aluminium, Plastic
LED indicators	Link, Power
Cable length	1 m
Plug and Play	✔
Certification	CE, FCC, RoHS, REACH

Network	
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Full duplex	✔
Auto MDI/MDI-X	✔
UASP support	✔

Power	
Power supply type	AC
Power consumption (typical)	24 W
Input voltage	110 - 240 V

System requirements	
Linux operating systems supported	✔
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 x64
Other operating systems supported	Android

Weight & dimensions	
Width	60 mm
Depth	100 mm
Height	25 mm
Weight	87 g

Packaging data	
Quantity per pack	1 pc(s)
Package width	150 mm
Package depth	210 mm
Package height	51 mm
Package weight	500 g

Packaging content	
AC adapter included	✔
Included power plug types	ANZ, EU, JP, NA, UK
Cables included	USB Type-C

Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%

Logistics data	
Master (outer) case width	450 mm
Master (outer) case length	320 mm

Power

Input current	0.8 A
Output voltage	12 V
Output current	2 A
Power plug type	Type M

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura

Logistics data

Master (outer) case height	570 mm
Products per master (outer) case	40 pc(s)
Harmonized System (HS) code	84719000

Other features

Chipset	Realtek - RTL5428, Realtek - RTL8153B

0065030877916

065030877916