


## Chieftec BDK-650FC virtalähdeyksikkö 650 W 20+4 pin ATX ATX musta

**Tuotemerkki :** Chieftec

**Tuotekoodi:** BDK-650FC

**Tuotteen nimi :** BDK-650FC

Chieftec BDK-650FC. Kokonaisteho: 650 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 47 - 63 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 65 cm, SATA-virtakaapelin pituus: 150,500 mm. Tarkoitus: PC/palvelin, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Bronze. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 12 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 140 mm, Tuotteen korkeus: 86 mm



Power		Ports & interfaces	
Total power *	650 W	EPS power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	PCI Express power connectors (6+2 pin)	4
AC input frequency	47 - 63 Hz	Floppy drive power connector	1
Input current	10 A	Cabling type	Fully-Modular
Power factor	0.9	Performance	
Power Factor Correction (PFC) type	Active	80 PLUS certification *	80 PLUS Bronze
Combined power (+3.3V)	110 W	Purpose *	PC/Server
Combined power (+12V)	648 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5V)	110 W	ATX version	2.3
Combined power (-12V)	3.6 W	Bearing technology	FDB
Combined power (+5Vsb)	12.5 W	Certification	CB EAC FCC
Max output current (+3.3V)	20 A	Design	
Max output current (+12V)	54 A	Product colour	Black
Max output current (+5V)	20 A	Cooling type	Active
Max output current (-12V)	0.3 A	Fan diameter	12 cm
Max output current (+5Vsb)	2.5 A	Number of fans	1 fan(s)
Power protection features	Over current, Over voltage, Overheating, Overload, Short circuit, Under voltage	Weight & dimensions	
Ports & interfaces		Width	150 mm
Motherboard power connector *	20+4 pin ATX	Depth	140 mm
Motherboard power cable length	65 cm	Height	86 mm
Number of SATA power connectors	6	Weight	1.65 kg
SATA power cable length	150,500 mm	Packaging data	
Peripheral (Molex) power connectors (4-pin) *	3	Package weight	2.2 kg
Peripheral (Molex) power cable length	500 mm	Technical details	
		Sustainability compliance	✓

**Technical details**

Sustainability certificates	ErP
Compliance certificates	CE, RoHS

**Logistics data**

Harmonized System (HS) code	84733020
-----------------------------	----------



0753263077424



753263077424

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.