ATEN

ATEN CN9950-AT-G KVM-kytkin musta

Tuotemerkki : ATEN Tuotekoodi: CN9950-AT-G

Tuotteen nimi: CN9950-AT-G

ATEN CN9950-AT-G. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 4K Ultra HD, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Videokaistanleveys: 30 Hz. Tuotteen väri: musta, Kotelon materiaali: Metalli. Voimanlähde: DC, Tulojännite: 5 V, Virrankulutus: 9,76 W. Tuotteen leveys: 149,3 mm, Tuotteen syvyys: 200 mm, Tuotteen korkeus: 28,5 mm





| Ports & interfaces | | Power | |
|-------------------------------|---|---|--|
| Keyboard port type * | USB | Input voltage | 5 V |
| Mouse port type * | USB | Power consumption (typical) | 9.76 W |
| Video port type * | DisplayPort | Operational conditions | |
| DisplayPorts quantity | 2 | Operating temperature (T-T) | 0 - 50 °C |
| USB 2.0 Type-B ports quantity | 1 | Storage temperature (T-T) | -20 - 60 °C |
| Console ports * | 3.5mm headphone, 3.5mm mic, DisplayPort, USB A | Operating relative humidity (H-H) | 0 - 80% |
| Console USB ports quantity | 2 | Weight & dimensions | |
| USB connector type | Mini-USB B | Width | 149.3 mm |
| PS/2 ports quantity | 1 | Depth | 200 mm |
| Serial port type | RJ-45 | Height | 28.5 mm |
| Serial ports quantity | 2 | Weight | 1.25 kg |
| Audio connections | • | Packaging data | |
| Headphone outputs | 2 | Package width | 98 mm |
| Number of microphone inputs | 2 | Package depth | 325 mm |
| DC-in jack | • | Package height | 210 mm |
| Network | | Package weight | 1.67 kg |
| Ethernet LAN | ✓ | Packaging content | |
| Ethernet LAN (RJ-45) ports | 2 | Cables included | DisplayPort, USB, USB Type-A to USB Type-B |
| Performance | | Manual | ✓ |
| HD type * | 4K Ultra HD | AC adapter included | · |
| Maximum resolution * | 4096 x 2160 pixels | · | • |
| Video bandwidth | 30 Hz | Logistics data | |
| Design | | Master (outer) case net weight | 6.25 kg |
| Product colour * | Black | Harmonized System (HS) code | 85176200 |
| Housing material | Metal | Master (outer) case width | 342 mm |
| LED indicators | 1 | Master (outer) case length | 512 mm |
| Display | | Master (outer) case height Master (outer) case gross weight | 232 mm 8.98 kg |
| Built-in display * | × | Products per master (outer) case | 5 pc(s) |
| Power | | | |
| Power source | DC | | |



4710469340666

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.