



TP-Link Omada EAP615-WALL WLAN-tukiasema 1774 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link

Tuoteperhe: Omada

Tuotekoodi: EAP615-WALL

Tuotteen nimi : EAP615-WALL

TP-Link Omada EAP615-WALL. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1774 Mbit/s. Tietoturva-algoritmit: WPA, WPA2, WPA3. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Management features	
2.4 GHz *	✓	Syslog	✓
5 GHz *	✓	Firmware upgradeable	✓
6 GHz *	✗	Ports & interfaces	
Maximum data transfer rate *	1774 Mbit/s	Ethernet LAN (RJ-45) ports *	4
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Power	
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Design	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Placement *	Wall
Cabling technology	10/100/1000Base-T(X)	Product colour *	White
Automatic channel selection	✓	On/off switch	✓
Automatic channel scanning	✓	Reset button	✓
MIMO	✓	LED indicators	Power
MIMO type	Multi User MIMO	Antenna	
VLAN support	✓	Antenna type *	Internal
Rate limiting	✓	Antennas quantity	4
Wireless isolation	✓	Antenna gain level (max)	4 dBi
Band steering	✓	Certificates	
Airtime Fairness (ATF)	✓	Certification	CE, FCC, RoHS
Quality of Service (QoS) support	✓	Weight & dimensions	
BeamForming	✓	Width	143 mm
Transmitting power (CE)	20 dBm	Depth	86 mm
Transmitting power (FCC)	21 dBm	Height	20 mm
Security		Packaging data	
Security algorithms *	WPA, WPA2, WPA3	Package width	385 mm
		Package depth	495 mm

Security		Packaging data	
Service Set Identifier (SSID) features	Multiple SSIDs	Package height	210 mm
Number of SSID supported	16	Package weight	330 g
Remote Authentication Dial-In User Service (RADIUS)	✓	Operational conditions	
Access Control List (ACL)	✓	Operating relative humidity (H-H)	10 - 90%
Protocols		Operating temperature (T-T)	0 - 40 °C
STelnet using SSH v2	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%
		Logistics data	
		Harmonized System (HS) code	85176990



4897098683606



4897098682128



0840030703607



840030703607

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.