



## Lenovo 4XB7A17096 internal solid state drive 240 GB 3.5" Serial ATA III 3D TLC NAND



**Brand :** Lenovo

**Product code:** 4XB7A17096

**Product name :** 4XB7A17096

ThinkSystem 3.5" 5300 240GB Mainstream SATA 6Gb Hot Swap SSD

[Lenovo 4XB7A17096 internal solid state drive 240 GB 3.5" Serial ATA III 3D TLC NAND:](#)

The ThinkSystem 5300 Mainstream SATA 6Gb solid-state drives (SSDs) use Micron 96-layer 3D NAND flash memory technology with a 6Gbps SATA interface. They provide an affordable solution for mixed read/write applications such as cache in transactional applications and high-speed storage for enterprise databases.

Lenovo 4XB7A17096. SSD capacity: 240 GB, SSD form factor: 3.5", Read speed: 540 MB/s, Write speed: 380 MB/s, Data transfer rate: 6 Gbit/s, Component for: Server/workstation

Features		Features	
Security algorithms	256-bit AES	Certification	Micron Green Standard Built with sulfur resistant resistors CE (Europe): EN 55032 Class B, RoHS FCC: CFR Title 47, Part 15 Class B UL: UL-60950-1, 2nd Edition BSMI (Taiwan): approval to CNS 13438 RCM (Australia, New Zealand): AS/NZS CISPR32 Class B KCC RRL (Korea): approval to KN 32 Class B, KN 35 Class B W.E.E.E.: Compliance with EU WEEE directive 2002/96/EC. TUV (Germany): approval to IEC60950/EN60950 VCCI (Japan): 2015-04 Class B IC (Canada): CISPR32 Class B: Canadian ICES-003:2016
SSD capacity *	240 GB		
SSD form factor *	3.5"		
Interface *	Serial ATA III		
Memory type *	3D TLC NAND		
Component for *	Server/workstation		
Hardware encryption *	✓		
Data transfer rate	6 Gbit/s		
Read speed	540 MB/s		
Write speed	380 MB/s		
Random read (4KB)	82000 IOPS		
Random write (4KB)	60000 IOPS		
Read latency	175 µs		
Write latency	300 µs		
S.M.A.R.T. support	✓		
Hot-swap	✓		
Mean time between failures (MTBF)	3000000 h		
		Power	
		Power consumption (read)	2.5 W
		Power consumption (write)	3 W
		Weight & dimensions	
		Width	257 mm
		Depth	193 mm
		Height	95 mm
		Weight	484 g
		Operational conditions	
		Operating temperature (T-T)	0 - 70 °C
		Storage temperature (T-T)	-40 - 85 °C
		Operating relative humidity (H-H)	5 - 95%
		Non-operating shock	1.5 G
		Logistics data	
		Harmonized System (HS) code	84717070



0889488510818



889488510818

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date