



## Seagate Barracuda 1TB 2.5" internal hard drive 5400 RPM 128 MB 2.5" Serial ATA III

**Brand :** Seagate

**Product family:** Barracuda

**Product code:** ST1000LMA48

**Product name :** 1TB 2.5"

Barracuda 1TB, 2.5", SATA III (6 Gbit/s), 5400 RPM, 5V DC, 90 g

[Seagate Barracuda 1TB 2.5" internal hard drive 5400 RPM 128 MB 2.5" Serial ATA III:](#)

### Versatile. Fast. Dependable.

Barracuda leads the industry with the highest capacities for desktops and mobile computers. With drives available up to 12 TB, the BarraCuda portfolio is a great option for upgrades at any price point.

### Laptop and Mobile Storage

Experience the highest capacity, and the thinnest 2.5-inch hard drive you've ever seen. Choose from 500 GB to 2 TB of massive storage for all of your application and data needs along with a slim 7 mm form factor drive that makes system upgrades very easy.

### Multi-Tier Caching Technology

All hard drives in the BarraCuda family come equipped with Multi-Tier Caching Technology (MTC). MTC takes your PC to new performance levels, so you can load applications and files faster than ever before. By applying intelligent layers of NAND Flash, DRAM and media cache technologies, BarraCuda delivers improved read and write performance by optimising data flow.



Features		Operational conditions	
HDD capacity *	1 TB	Storage temperature (T-T)	-40 - 70 °C
HDD speed *	5400 RPM	Operating shock	400 G
Storage drive buffer size *	128 MB	Non-operating shock	1000 G
HDD size *	2.5"	<b>Technical details</b>	
Interface *	Serial ATA III	Doesn't contain	Halogen
Type *	HDD	<b>Packaging content</b>	
Component for *	Laptop	Storage drive adapter included	✗
HDD interface transfer rate	6 Gbit/s	<b>Weight &amp; dimensions</b>	
Bytes per sector	4096	Width	69.8 mm
Start/stop cycles	600000	Height	7 mm
<b>Power</b>		Depth	100.3 mm
Power consumption (read)	1.6 W	Weight	90 g
Power consumption (write)	1.7 W	<b>Packaging data</b>	
Power consumption (idle)	0.45 W	Quantity per pack	1 pc(s)
Operating voltage	5 V	<b>Logistics data</b>	
Start-up current	1 A	Harmonized System (HS) code	84717050
<b>Operational conditions</b>		<b>Other features</b>	
Operating temperature (T-T)	0 - 60 °C	Compliance certificates	RoHS



8719706002288

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-NOV-2024. Prints or copies of Information are only valid on the printed Publication date