



L10 Series Technical Accessory Guide



NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles and Charging



Cradles/Docking Stations (for Indoor use)

Part Number	Picture	Description	Notes	Required Items
300154		Office Docking Station	<ul style="list-style-type: none"> ►Transforms the L10 into a full desktop configuration. ►Has tablet alignment features designed for easy, one handed insertion into the dock, and the dock can be securely mounted to the desk. ►Compatible with all L10 Platform models. ►Includes the following ports and features: Connectivity: - 2 USB 3.0 Dock Powered - 2 USB 2.0 Tablet Powered Video: Dual monitor Support HDMI Type A - Full HD VGA - Full HD - Headphone Out - 3.5 mm - Mic In - 3.5 mm - RJ45 Gigabit Ethernet - DB9 Serial - Optional Battery Charging Bay (450166) for charging spare standard or extended battery. - Kensington® Lock Slot - Secure Installation Option: 4 threaded inserts on bottom of dock (M3 screw type) 	<ul style="list-style-type: none"> ►Power Supply (450165) ►AC Line Cord (450043)



<p><u>Dock without Spare Battery Charger</u></p>			<ul style="list-style-type: none"> •Kit contains the following: <ul style="list-style-type: none"> - Office Dock (300154) - Power Supply (450165) - Country specific AC Line Cord - Spare Battery Charger (450166) if ordered with option. 	
<p>300147 (with North America power supply)</p>			<ul style="list-style-type: none"> •Transforms the L10 into a full desktop configuration. 	
<p>300159 (with Australia/New Zealand power supply)</p>			<ul style="list-style-type: none"> •Includes 90 watt AC adapter to ensure both the tablet battery and the optional spare battery charge simultaneously. 	
<p>300160 (with EU power supply)</p>			<ul style="list-style-type: none"> •Has tablet alignment features designed for easy, one handed insertion into the dock, and the dock can be securely mounted to the desk. 	
<p>300161 (with UK power supply)</p>		<p>Office Docking Station KIT</p>	<ul style="list-style-type: none"> •Compatible with all L10 Platform models. 	
<p><u>Dock with Spare Battery Charger</u></p>			<ul style="list-style-type: none"> •Includes the following ports and features: 	
<p>300148 (with North America power supply)</p>			<p>Connectivity:</p> <ul style="list-style-type: none"> - 2 USB 3.0 Dock Powered - 2 USB 2.0 Tablet Powered 	
<p>300162 (with Australia/New Zealand power supply)</p>			<p>Video:</p> <ul style="list-style-type: none"> Dual monitor Support HDMI Type A - Full HD VGA - Full HD 	
<p>300163 (with EU power supply)</p>			<ul style="list-style-type: none"> - Headphone Out - 3.5 mm - Mic In - 3.5 mm - RJ45 Gigabit Ethernet - DB9 Serial 	
<p>300164 (with UK power supply)</p>			<ul style="list-style-type: none"> - Optional Battery Charging Bay for charging spare standard or extended battery. - Kensington® Lock Slot - Secure Installation Option: 4 threaded inserts on bottom of dock (M3 screw type) 	





<p>300149 (with North America power supply)</p> <p>300150 (with Australia/New Zealand power supply)</p> <p>300151 (with EU power supply)</p> <p>300152 (with UK power supply)</p>		<p>Industrial Dock KIT</p>	<ul style="list-style-type: none"> •Kit contains the following: <ul style="list-style-type: none"> - Vehicle Cradle (300142) - Dock Stand (300051) - Power Supply (450020) - Country specific AC Line Cord •Perfect for fixed use tablet applications in the plant, warehouse, or office. •Barrel-style keylock provides secure vehicle docking. •Easy one-hand release allows for fast "grab and go" transitions between the vehicle, field, and office. •Resistant to water and dust ingress (IP55). •Provides two USB 2.0 ports which are powered from the tablet. External power not required for ports to operate. •A single USB port can provide up to 1.6 A peak current for up to 1 second. Use of DS3508-ER scanner is not recommended. Use of DS3608-ER scanner in default power mode is not recommended. Use DS3608-ER in ER Low Power option instead. •Compatible with all L10 series models. •Dimensions (L x W x H): 9.25 x 11.9 x 14.1 in (23.5 x 30.0 x 35.8 cm) •Weight: 4.8 lb (2.18 kg) •Optional 4K Port Replicator (300146) can be installed to provide four USB 3.0, 2 USB 2.0 ports, DVI, DisplayPort or HDMI, Gigabit Ethernet, microphone in, Stereo speaker out, and security lock slot. 	
<p>300146</p>		<p>4K Dynadock Port Replicator</p>	<ul style="list-style-type: none"> •With just a single USB 3.0 connection, the L10 can output stunning Ultra HD 4K resolution to an external 4K TV or monitor. •Dynadock 4K also boosts everyday productivity by connecting the L10 to peripherals, printers and essential tools like external USB drives, full-size keyboards, mice and headphones. •Features: <ul style="list-style-type: none"> - Built-in video card supports one 4K display via DisplayPort OR HDMI dual display mode resolution is supported via DisplayPort or HDMI and DVI-I used simultaneously. - Stereo sound through HDMI, DisplayPort or 3.5 mm audio out jack. - Six USB 3.0 ports (2 on front of dock and 4 on rear of dock). - RJ-45 Ethernet, 1000Base-T •Horizontal slim design reduces cable clutter on desk space. •Docking and undocking is easy, just plug USB 3.0 cable from the USB-B port on rear of Dynadock to any USB 3.0 or USB 2.0 port on the L10 and your display(s) and accessories will be activated in seconds. To undock, simply unplug the USB cable and go! •Includes Power Supply, USB-B to USB-A cable for connecting L10 to dock and stand for mounting dock vertically. 	<p>Typically used with Industrial Dock (300149)</p>

Battery Charging


Part Number	Picture	Description	Notes	Required Items
450166		Single Slot Battery Charger	<ul style="list-style-type: none"> Charges either Standard 36 WHr or Extended Life 98 WHr battery. Rugged design stands up to the critical demands of industrial use. Can be integrated into the Office Docking Station or used as a stand-alone charger. Standard Battery charge time: 2.75 Hrs Extended Life Battery charge time: 3.25 Hrs LED indicator shows charging status. 	<ul style="list-style-type: none"> Power Supply (450154) AC Line Cord (450040) <p>OR</p> <ul style="list-style-type: none"> Power supply kit that includes AC Line Cord (450159)
450150 (with North America power supply) 450170 (with Australia/New Zealand power supply) 450171 (with EU power supply) 450172 (with UK power supply)		Single Slot Battery Charger KIT	<ul style="list-style-type: none"> Charges either Standard 36 WHr or Extended Life 98 WHr battery. Rugged design stands up to the critical demands of industrial use. Can be integrated into the Office Docking Station or used as a stand-alone charger. Standard Battery charge time: 2.75 Hrs Extended Life Battery charge time: 3.25 Hrs LED indicator shows charging status. Kit includes Single Slot Battery Charger (450166), Power Supply (450154) and country specific AC Line Cord (450040). 	





Direct to Device Charging

Part Number	Picture	Description	Notes	Required Items
450154		Spare AC Power Supply	<ul style="list-style-type: none"> This is a spare power supply. This power supply normally ships with each L10 series tablet. Power supply also used when using the Spare Battery Charger (450166) in stand-alone mode. Uses IEC 320 C5 style AC Line Cord 	AC Line Cord (450040)
450159 (with US AC Line Cord) 450160 (with Australia/New Zealand AC Line Cord) 450161 (with EU AC Line Cord) 450162 (with UK AC Line Cord)		Spare AC Power Supply KIT	<ul style="list-style-type: none"> This is a spare power supply. This power supply normally ships with each L10 series tablet. Power supply also used when using the Spare Battery Charger (450166) in stand-alone mode. Uses IEC 320 C5 style AC Line Cord Kit includes country specific AC Line Cord 	

450140		Lind Cigarette Lighter Adapter (CLA) Kit for 12-16V vehicles	<ul style="list-style-type: none"> Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. Designed for vehicles providing 12-16V power. 20 volt output Includes 36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable (450142) 	
450141		Lind Cigarette Lighter Adapter (CLA) Kit for 12-32V vehicles	<ul style="list-style-type: none"> Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. Designed for vehicles providing 12-32V power. 20 volt output Includes 36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable (450142) 	
450142		Lind Replacement Cigarette Lighter Adapter (CLA) Cable	<ul style="list-style-type: none"> This is a spare/replacement cable. Cable is normally included with Cigarette Lighter Adapter Kits (450140 or 450141) 36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable. 	
XP2035-2396 (3rd party) * http://www.lindelectronics.com		Lind Cigarette Lighter Adapter (CLA) Kit	<ul style="list-style-type: none"> Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. 12-32 VDC input Includes: <ul style="list-style-type: none"> Cigarette Lighter Plug 36" Input Cable 5.5x1.7 36" Output Cable Low Input Voltage Disconnect High Input Voltage Disconnect Output Short Circuit Protection Output Overcurrent Protection Internal Over Temperature Protection 	

Communication Cables




Part Number	Picture	Description	Notes	Required Items
CBA-UF8-C12ZAR		L10 to 36xx Series Scanner Cable (USB)	<ul style="list-style-type: none"> Cable rated for 1.2A current Coiled cable is 12 ft long when extended Rated to -30°C for freezer environment use. When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. 	


CBA-UF6-C12ZAR		L10 to 36xx Series Scanner Cable (USB)	<ul style="list-style-type: none"> ▶Cable rated for 1.2A current ▶Coiled cable is 9 ft long when extended (even though SKU indicates 12 ft.) and is about 5 ft. long when un-extended. Use CBA-UF8-C12ZAR for a true 12 ft. length cable. ▶Rated to -30°C for freezer environment use. ▶When connected to STB3678/FLB3678, will charge a fully depleted battery in about 4.5 hours if host USB port is BC 1.2 compatible or about 10.5 hours for USB 2.0 host ports. 	
CBA-U12-C09ZAR		Generic Cable to Scanners 34xx/35xx Cable (USB)	▶9 ft long when extended	
CBA-U09-C15ZAR		Generic Cable to Scanners 34xx/35xx Cable (USB)	▶15 ft long when extended	
P1031365-055		QLn Series Printer USB Cable	<ul style="list-style-type: none"> ▶Connects to USB port on ET5X ▶6 ft. straight cable 	

Optional Modules



NOTE: Optional Modules must be factory installed. Modules cannot be field installed.





Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------

<p>Order L10 with Smart Card/CAC Reader module option</p>		<p>Smart Card/CAC Reader module</p>	<ul style="list-style-type: none"> ▶FIPS 140-2 compliant – ideal for government, military, and other security-conscious organizations. ▶Supports the following asynchronous and synchronous smart card interfaces: <ul style="list-style-type: none"> - Complies with all sections of ISO7816 (both T=0 and T=1 asynchronous card supported) - EMV2000 (EMV 4.1) compatible - Complies with PC Smart Card industry standard: PC/SC1.0 and PC/SC 2.0 - Supports 2-wire, 3-wire, or I2C Interface synchronous card - Atmel: AT88sc1608, AT88sc153 - Atmel: AT24c128, AT24c256 - ST: M14C16, M14C04 - Siemens 2-wire link protocol: sle4432/42 - Siemens serial 3-wire bus: sle4418/28 - Configurable hardware auto error detection - Supply Voltage for Card: 5V, 3V, 1.8V - Supports Class A/Class B/Class C operating class as defined in ISO/IEC 7816-3:1997 and ISO/IEC 7816-3:1997/Amd 1:2002. ▶Module connects to the Expansion port on the back of the tablet. 	
<p>Order L10 with RFID reader option</p>		<p>UHF RFID Reader module</p>	<ul style="list-style-type: none"> ▶Adds UHF RFID functionality to the Xplore L10 rugged tablet. ▶No external power supply required. ▶APIs available for custom software development. ▶Specifications: <ul style="list-style-type: none"> - Read range up to 3m (Tag Dependent) - Two frequency ranges: <ol style="list-style-type: none"> 1. 866.7MHz (Supports ISO 18000-6B, -6C) 2. 912-925MHz (Supports AEI, EPC Class 1 Gen 1, EPC Class 1 Gen 2, ISO 18000-6B, -6C) - Operating Temperature: -20 °C to 60°C (-4 °F to 140 °F) - Storage Temperature: -30 °C to 70°C (-22 °F to 158 °F) - Device peak power consumption: 4w RF max power: .05w ▶Module connects to the Expansion port on the back of the tablet. 	
<p>Order L10 with Serial port module option</p>		<p>True Serial (RS232) module</p>	<ul style="list-style-type: none"> ▶Adds True Serial capability to connect legacy Serial equipment to the tablet via a DB9 adapter. ▶Module connects to the optional Multi-function/HDMI-in port on the side of the tablet. ▶Installation of Module requires one of the following for proper mounting: (1) Extended Battery Kickstand, (2) KickStrap or (3) Spacer Bracket 	

Order L10 with HDMI port option		HDMI module	►Adds HDMI port.	
---------------------------------	---	-------------	------------------	--


Soft Goods


Part Number	Picture	Description	Notes	Required Items
410055		KickStrap	<ul style="list-style-type: none"> ►Combined Kickstand and Rotating Hand Strap provides working comfort for all Xplore L10 rugged tablet models in the field and at a desk. ►The integrated Kickstand closes tightly when workers are on the move, enabling access to the Rotating Hand Strap, which can be adjusted for hand size as well as unique rotation angle. ►KICKSTAND features: <ul style="list-style-type: none"> - Rigid design provides great ergonomics for reading and touch screen interactions while the tablet is on flat surfaces or while the Companion Keyboard is attached. - Adds 0.9 in (2.3 cm) to thickness - Adds 0.55 lb (0.25 kg) to weight - Display angle is user adjustable ►ROTATING HANDSTRAP features: <ul style="list-style-type: none"> - Easy to use while walking - Adjustable to hand size - Detents help lock desired rotation angle ►Compatible with Companion Keyboard, Top Handle, Option modules (RFID, Smart Card Reader / CAC) ►Not Compatible with Extended Battery option or Kickstand (410056) ►KickStrap is included on XBOOK L10 configurations. 	
410056		Kickstand / Extended Battery Bracket	<ul style="list-style-type: none"> ►Kickstand provides adjustable viewing angle, keeping the tablet upright for easy reading and touch while in the field and when using the Companion Keyboard. ►Kickstand folds away for mobility. ►Integrated battery bracket holds the extended battery. ►Kickstand bracket does not need to be removed when docking in the Vehicle (except antenna pass-through version - 300144), Office or Industrial docks. ►Can also be used in combination with the optional Soft Handle and Stylus pen accessory set. ►Not compatible with KickStrap (410055) or Vehicle Cradle with Antenna Pass-Through (300144). ►Adds .64 lb (.29 kg) weight to tablet and .78 in (.2 cm) to thickness. 	

<p>410052 (includes tether, no Stylus/Pen)</p> <p>410061 (includes Long Active Pen/Stylus with tether)</p> <p>410062 (includes Long Passive ePen/Stylus with tether)</p>		<p>Soft Handle</p>	<ul style="list-style-type: none"> ▶Integrated handle attaches to the top of the XSLATE or XBOOK tablet. ▶Allows users to carry the tablet without the worry of dropping it. ▶Handle is manufactured with smooth durable soft rubber, providing maximum grip without sacrificing comfort. ▶Handle contains a pen storage slot suitable for either of the Long pens/stylus. ▶Optional detachable Shoulder Strap (410057) attaches to the handle for carrying long distances and freeing up hands. ▶Handle can be ordered with or without pen/stylus. Soft Handle kit w/Long Active Pen/Stylus (410061) requires tablet with Active Display (digitizer screen) option. ▶Not compatible with XPAD which includes an integrated handle. ▶Dimensions and Weight: <ul style="list-style-type: none"> - Length: 16 inches (405 mm) - Width: 1.125 inches (28mm) - Weight: 1.4 oz (40 grams) 	
<p>410059</p>		<p>Carrying Case / Operations Case for XPAD</p>	<ul style="list-style-type: none"> ▶Professional-grade carrying case designed specifically for the L10-Series Tablet. ▶Provides easy access to power button, both cameras and ports. ▶Includes two storage locations for stylus/pens. ▶Includes detachable Shoulder Strap for carrying long distances and freeing up hands. ▶Only compatible with XPAD configurations. 	
<p>410058</p>		<p>Carrying Case / Operations Case for XSLATE</p>	<ul style="list-style-type: none"> ▶Professional-grade carrying case designed specifically for the L10-Series Tablet. ▶Integrated handle provides convenient carrying option. ▶Provides easy access to power button, both cameras and ports. ▶Includes two storage locations for stylus/pens. ▶Optional detachable Shoulder Strap (410057) attaches to the case for carrying long distances and freeing up hands. ▶Only compatible with XSLATE configurations. 	
<p>410057</p>		<p>Shoulder Strap</p>	<ul style="list-style-type: none"> ▶Shoulder Strap attaches to the XPAD, Soft Handle or Carrying Case. ▶Ideal for hands-free, long-distance carrying, and it is adjustable for height. ▶Wide strap enhances comfort and can be easily attached and detached via clips. ▶Adjustable to maximum length of 4.1 ft (1.28 m) ▶Strap width 1.5 in (3.8 cm) 	<p>XSLATE or XBOOK requires Soft Handle or Carrying Case (410058)</p>

Vehicle Cradles and Holders


Powered Cradles and Holders (provides device charging and/or communication)

Part Number	Picture	Description	Notes	Required Items
300142		Vehicle Dock - powered with xDIM module	<ul style="list-style-type: none"> • Holds rugged tablet in place under extreme vibration and stress. - Shock and Vibration: Minimum Integrity Vibration: Category 24 Unit is not operating (Tablet with Dock and Vehicle Kit) MIL-STD-810G, Method 514.6, Procedure I - Vehicle Vibration: Unit is operating (Tablet with Dock and Vehicle Kit) MIL-STD-810G, US Highway Truck and Composite Wheel, Method 514.6C-1 and 514.6C-3 - Functional Shock: 40 g operating (peak); 11 ms, saw tooth 6+/- shocks x 3-axis=18 shocks MIL-STD-810G, Method 516.6, Procedure I • Barrel-style keylock provides secure vehicle docking. • Easy one-hand release allows for fast "grab and go" transitions between the vehicle, field, and office. • Resistant to water and dust ingress (IP55). • Provides charging via included Cigarette Lighter adapter - compatible with 12V vehicle systems. • Provides two USB 2.0 ports which are powered from the tablet. External power not required for ports to operate. • A single USB port can provide up to 1.6 A peak current for up to 1 second. Use of DS3508-ER scanner is not recommended. Use of DS3608-ER scanner in default power mode is not recommended. Use DS3608-ER in ER Low Power option instead. • USB cables should be terminated in dry area of the vehicle. • Compatible with all L10 series models. • Can be hard wired to 12V vehicles by removing Cigarette Lighter Adapter and using optional Direct Wire Power Cable Kit (300039). 	


300144		Vehicle Dock - powered with xDIM module and RF Pass Through Antennas	<ul style="list-style-type: none"> ▶ Holds rugged tablet in place under extreme vibration and stress. - Shock and Vibration: Minimum Integrity Vibration: Category 24 Unit is not operating (Tablet with Dock and Vehicle Kit) MIL-STD-810G, Method 514.6, Procedure I - Vehicle Vibration: Unit is operating (Tablet with Dock and Vehicle Kit) MIL-STD-810G, US Highway Truck and Composite Wheel, Method 514.6C-1 and 514.6C-3 - Functional Shock: 40 g operating (peak); 11 ms, saw tooth 6+/- shocks x 3-axis=18 shocks MIL-STD-810G, Method 516.6, Procedure I ▶ Barrel-style keylock provides secure vehicle docking. ▶ Easy one-hand release allows for fast "grab and go" transitions between the vehicle, field, and office. ▶ Resistant to water and dust ingress (IP55). ▶ Provides charging via included Cigarette Lighter adapter - compatible with 12V vehicle systems. ▶ Provides two USB 2.0 ports which are powered from the tablet. External power not required for ports to operate. ▶ A single USB port can provide up to 1.6 A peak current for up to 1 second. Use of DS3508-ER scanner is not recommended. Use of DS3608-ER scanner in default power mode is not recommended. Use DS3608-ER in ER Low Power option instead. ▶ USB cables should be terminated in dry area of the vehicle. ▶ Dock provides MIMO WWAN, MIMO WLAN, and GPS antenna pass-through connections for improved in-vehicle signal strength and throughput (external antennas and cables purchased separately) ▶ Compatible with all L10 series models with antenna pass-through on back of tablet option. ▶ Can be hard wired to 12V vehicles by removing Cigarette Lighter Adapter and using optional Direct Wire Power Cable Kit (300039). 	
--------	---	--	---	--


Un-Powered Cradles and Holders (passive holders, no charging support)

Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------



300139		Vehicle Dock - passive/un-powered	<ul style="list-style-type: none"> •Holds rugged tablet in place under extreme vibration and stress. - Shock and Vibration: Minimum Integrity Vibration: Category 24 I Unit is not operating (Tablet with Dock and Vehicle Kit) I MIL-STD-810G, Method 514.6, Procedure I - Vehicle Vibration: Unit is operating (Tablet with Dock and Vehicle Kit) I MIL-STD-810G, US Highway Truck and Composite Wheel, Method 514.6C-1 and 514.6C-3 - Functional Shock: 40 g operating (peak); 11 ms, saw tooth 6+/- shocks x 3-axis=18 shocks I MIL-STD-810G, Method 516.6, Procedure I •Barrel-style keylock provides secure vehicle docking. •Easy one-hand release allows for fast "grab and go" transitions between the vehicle, field, and office. •Resistant to water and dust ingress (IP55). •Compatible with all L10 series models. •Can be converted to powered cradle w/USB ports (same as 300142) by installing optional xDIM Module G3 with Cigarette Lighter Adapter (300140). 	
--------	---	-----------------------------------	--	--






Vehicle Mounting Hardware and Accessories

Part Number	Picture	Description	Notes	Required Items
300140		xDIM Module G3 with Cigarette Lighter Adapter	<ul style="list-style-type: none"> •Module provides Cigarette Lighter Adapter charging and 2 USB ports to L10 Series Vehicle Dock - passive/un-powered (300139). •Provides charging via included Cigarette Lighter adapter - compatible with 12V vehicle systems. •Provides two USB 2.0 ports which are powered from the tablet. External power not required for ports to operate. •A single USB port can provide up to 1.6 A peak current for up to 1 second. Use of DS3508-ER scanner is not recommended. Use of DS3608-ER scanner in default power mode is not recommended. Use DS3608-ER in ER Low Power option instead. •USB cables should be terminated in dry area of the vehicle. •Can be hard wired to 12V vehicles by removing Cigarette Lighter Adapter and using optional Direct Wire Power Cable Kit (300039). 	Vehicle Dock - passive/un-powered (300139)

<p>241372 (3rd party) *</p> <p>https://www.proclipusa.com</p>		<p>ProClip Keyboard Mount</p>	<ul style="list-style-type: none"> ▶Adjustable keyboard tray with AMPS holes for various keyboards ▶Attaches to rear of L10 series Vehicle Docks or Industrial Dock. ▶Multiple AMPS hole patterns and VESA 75 & 100 for easy mounting 	
--	---	-------------------------------	--	--

Misc




Part Number	Picture	Description	Notes	Required Items
400022		<p>Replacement Screen Protector (pack of 3)</p>	<ul style="list-style-type: none"> ▶Shatter-Resistant Screen Protector Film is an anti-glare, thin protective film with a coating designed to reduce reflections and give a clear, sharp display view even in brightly-lit conditions. ▶Compatible with L10 touch screen and Active Display (digitizer display) to offer additional protection against everyday scratches. ▶This screen protector is included on every L10 tablet model and is available in this 3-pack for replacement of the originally-installed screen protector. 	
440036		<p>Long Active Pen/Stylus with Tether Cord</p>	<ul style="list-style-type: none"> ▶Compact digitizer Pen provides precision and comfort when writing and annotating on the L10 tablet is needed. ▶Allows for a large range of pressure sensitivity, tilt detection and hover capability. ▶Requires Active Display (Digitizer Screen) option in the tablet. ▶Includes attached tether to prevent loss. ▶Pen stores easily in the integrated garage in the XPAD L10 or the Soft Handle (410052) garage of the XSLATE L10 and XBOOK L10. ▶This stylus is included with XPAD units with ViewAnywhere Active displays. 	<p>Soft Handle (410052) required to store Pen in integrated garage when using XSLATE or XBOOK.</p>

440043		Long Passive ePen/Stylus	<ul style="list-style-type: none"> ▶Compact digitizer Pen provides precision and comfort when writing and annotating on the L10 tablet is needed. ▶Features 1.5 mm tip that provides pinpoint accuracy for easy writing and annotating on tablet and enables pressure sensitivity. ▶Features 2 mouse click buttons. ▶Uses one AAAA battery, included. ▶Does not require Digitizer Screen option in the tablet. ▶Pen stores easily in the integrated garage in the XPAD L10 or the Soft Handle (410052) garage of the XSLATE L10 and XBOOK L10. ▶This stylus is included with XPAD units with Standard or ViewAnywhere non-Active displays. ▶Does not include tether cord. 	<ul style="list-style-type: none"> ▶Soft Handle (410052) required to store Pen in integrated garage when using XSLATE or XBOOK. ▶Tether Cord (440017)
440037		Short Active Pen/Stylus with Tether Cord	<ul style="list-style-type: none"> ▶Compact digitizer Pen provides precision and comfort when writing and annotating on the L10 tablet is needed. ▶Allows for a large range of pressure sensitivity, tilt detection and hover capability. ▶Requires Active Display (Digitizer Screen) option in the tablet. ▶Includes attached tether to prevent loss. ▶Pen stores easily in the integrated garage on the side of the XSLATE or XBOOK. ▶This stylus is included with XSLATE and XBOOK units with ViewAnywhere Active displays. 	
440007		440007	<ul style="list-style-type: none"> ▶Provides precision and comfort when writing and annotating on the L10 tablet is needed. ▶Does not require Digitizer Screen option in the tablet. ▶Includes attached tether to prevent loss. ▶Pen stores easily in the integrated garage on the side of the XSLATE or XBOOK. ▶This stylus is included with XSLATE or XBOOK units with Standard or ViewAnywhere non-Active displays. 	
440042		Active Stylus Tip Replacement Kit	<ul style="list-style-type: none"> ▶Replaces the stylus tip on Long or Short Active Stylus (440036 or 440037) 	
440017 (single) 440018 (10 pack)		Replacement Stylus Tether Cord		





400025		Screen Cleaning Cloth	<ul style="list-style-type: none"> Keep the display clean and smudge free with an approved wiping cloth. Cloth is especially designed to remove dirt and skin oils without damaging the display surface. 	
400015		Screen Cleaner	2 oz bottle	

Power Cords/Power Supplies

AC Cords and Power Supplies

Part Number	Picture	Description	Notes	Required Items
450154		Spare AC Power Supply	<ul style="list-style-type: none"> This is a spare power supply. This power supply normally ships with each L10 series tablet. Power supply also used when using the Spare Battery Charger (450166) in stand-alone mode. Uses IEC 320 C5 style AC Line Cord 	AC Line Cord (450040)
450159 (with US AC Line Cord) 450160 (with Australia/New Zealand AC Line Cord) 450161 (with EU AC Line Cord) 450162 (with UK AC Line Cord)		Spare AC Power Supply KIT	<ul style="list-style-type: none"> This is a spare power supply. This power supply normally ships with each L10 series tablet. Power supply also used when using the Spare Battery Charger (450166) in stand-alone mode. Uses IEC 320 C5 style AC Line Cord Kit includes country specific AC Line Cord 	
450165		Power Supply for Office Dock	<ul style="list-style-type: none"> Used with Office Dock (300154 or 300148). 	AC Line Cord (450043)

450168		Power Supply for Office Dock	<ul style="list-style-type: none"> Discontinued, now use 450165 Used with Office Dock (300154 or 300148). 	AC Line Cord (450043)
450020 (no AC Line Cord)		Replacement AC Power Supply for Industrial Dock	<ul style="list-style-type: none"> This is a spare/replacement power supply. This power supply normally ships with each Industrial Dock. 	
450155 (with US AC Line Cord)				
450156 (with Australia/New Zealand AC Line Cord)				
450157 (with EU AC Line Cord)				
450158 (with UK AC Line Cord)				
450040 (for US)		AC Line Cord for Power Supply	<ul style="list-style-type: none"> Included with Spare AC Power Supply KIT (450159) IEC 320 C5 style Cord 	
450047 (for Australia/New Zealand)				
450042 (for EU)				
450041 (for UK)				
450043 (for US)		AC Line Cord	<ul style="list-style-type: none"> Used with Office Dock Power Supply (450165). C13 style cord 	
450046 (for Australia/New Zealand)				
450044 (for EU)				
450045 (for UK)				
In-Vehicle Power Supplies				
Part Number	Picture	Description	Notes	Required Items
300039		Direct Wire Power Cable Kit	<ul style="list-style-type: none"> Used to connect Vehicle Docks (300142, 300144 or 300140) directly to vehicle power. This cable kit replaces the Cigarette Lighter Adapter included on the Vehicle Dock. Kit includes wiring and fuse assembly. 	

450140		Lind Cigarette Lighter Adapter (CLA) Kit for 12-16V vehicles	<ul style="list-style-type: none"> ▶Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. ▶Designed for vehicles providing 12-16V power. ▶20 volt output ▶Includes 36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable (450142) 	
450141		Lind Cigarette Lighter Adapter (CLA) Kit for 12-32V vehicles	<ul style="list-style-type: none"> ▶Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. ▶Designed for vehicles providing 12-32V power. ▶20 volt output ▶Includes 36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable (450142) 	
450142		Lind Replacement Cigarette Lighter Adapter (CLA) Cable	<ul style="list-style-type: none"> ▶This is a spare/replacement cable. Cable is normally included with Cigarette Lighter Adapter Kits (450140 or 450141) ▶36" length, 20 AWG, 1.7 mm x 5.5mm Right Angle tip connector cable. 	
XP2035-2396 (3rd party) * http://www.lindelectronics.com		Lind Cigarette Lighter Adapter (CLA) Kit	<ul style="list-style-type: none"> ▶Typically used when in-vehicle charging via the L10's side power jack is needed. Not used with any docking station. ▶12-32 VDC input ▶Includes: <ul style="list-style-type: none"> - Cigarette Lighter Plug 36" Input Cable - 5.5x1.7 36" Output Cable ▶Low Input Voltage Disconnect ▶High Input Voltage Disconnect ▶Output Short Circuit Protection ▶Output Overcurrent Protection ▶Internal Over Temperature Protection 	

Keyboards

See External Keyboards Technical Accessory Guide (TAG) for additional keyboard options.

Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------

<p>420084 (US English) 420088 (UK English) 420089 (DE German) 420090 (FR French) 420091 (ES Spanish)</p>		<p>Companion Keyboard</p>	<ul style="list-style-type: none"> ▶Keyboard offers a 2-in-1 laptop / tablet experience providing the mobility of a tablet and notebook-style support for data-intensive tasks. ▶Includes full travel tactile feedback keyboard. ▶Integrated touchpad supports two-finger and three-finger gestures. ▶Keyboard can be easily removed from tablet before inserting into one of the docks. ▶No need to charge the keyboard; it is powered by the tablet and communicates via bottom pin connectors on tablet. ▶Spill resistant ▶Keyboard closes to cover tablet display glass for added protection and convenience. Magnets keep closed keyboard in position. ▶Weight: .92 lb (.42 kg) ▶Size: 10.7 x 7.2 x 0.32 in (27.2 x 18.3 x 0.8 cm) 	
<p>various</p>		<p>Other Keyboard options</p>	<p>See External Keyboards Technical Accessory Guide (TAG) for other keyboard options.</p>	

Batteries

Part Number	Picture	Description	Notes	Required Items
<p>450148</p>		<p>Standard Replacement Battery (36 WHr)</p>	<ul style="list-style-type: none"> ▶This is the main battery that attaches to the back of the L10 series. ▶Battery can be charged while in the rugged tablet or while in the battery charging slot provided in the L10-Series Docking Station. ▶Power meter on battery takes the guesswork out of determining available battery life. ▶Hot swappable enables 24x7 usage. ▶36 WHr Lithium-ion battery keeps tablet powered for up to 10 hours (Mobilemark 14). 	
<p>450149</p>		<p>Extended Life Battery (98 WHr)</p>	<ul style="list-style-type: none"> ▶Large 98 WHr Lithium-ion battery keeps tablet powered for up to 27 hours (Mobilemark 14). ▶External LED indicates approximate remaining battery life ▶Hot swappable enables 24x7 usage ▶Battery pack attaches to the tablet using the Extended Battery Bracket kickstand. 	<p>Kickstand Extended Battery Bracket kit (410056)</p>