

Holder and Charging Specifications

Item no 530391, 532391 (Reference doc 311-1165)

Motorola MTP850

Features & Benefits

- Always keep your battery fully charged
- Made of high grade ABS plastic
- Charges Li-Ion or Li-Poly batteries
- Works in 12 and 24 volt vehicles
- Rapid and trickle charges radio
- LED Red to Green charging status indicator
- Custom fit to hold device securely
- Designed and manufactured in Sweden
- Allows one-handed insertion and removal of radio
- You can charge just the battery alone in the holder
- Works with or without belt clip on back of radio
- Charging cable attached to holder providing dock type connection
- Attach to ProClip Vehicle or Pedestal mounts
- Can also be attached directly to any flat surface, dashboard, console wall, or any type of mounting bracket

Holder specifications Item no 530391 – Charging Holder with Cigarette Lighter Plug

Material	Rugged thermal resistant black FT-140 ABS plastic
Dimensions (W x H x D)	58 x 90 x 55 mm
Weight	129 g / 0.28 lbs
Cable Length, un-stretched	51 cm
Attachment	AMPS hole pattern

Holder specifications Item no 532391 – Charging Holder for Hard Wire Installation

Material	Rugged thermal resistant black FT-140 ABS plastic
Dimensions (W x H x D)	58 x 90 x 55 mm
Weight	109 g / 0.24 lbs
Cable Length	142 cm
Attachment	AMPS hole pattern

Charging Specifications

Lithium charging is based on CVCC (Constant Voltage Constant Current). The charging procedure is as follows:

If the battery is empty or has low charge a constant current charges the battery until the cell voltage reaches 8,4V. The LED emits red light. Hereafter the charge continues until the current goes down to 0A. The battery is now full and stays fully charged. A special designed voltage controller is monitoring that the cell voltage is within limit. The LED emits green light.

If the battery is used without disconnecting the charger, current is supplied directly resulting in a fast recovery.

Battery Chemistry	Li-ion or Li-Poly batteries
Input Voltage	11-30 V
Charging Voltage	4.6 V
Max. Charging Time	depending on battery capacity
Rapid Charge	1,6 A +/- 5%
RoHS Compliant	Yes
Input Transient Protected	Withstands +200V & -600V. A 2,5A fuse is mounted on the incoming supply.
Output Short Circuit Protected	The charger will supply a maximum current of 1,0 A which protects both the charger and the connected equipment. The current limit is set to standards of the producer and shall not be higher.

Battery Chemistry	Li-ion and Li-Poly batteries
Compatible batteries	4731
Input Voltage	11-30 V, 1 A
Charging Voltage	8.4 V
Timer for Max. Charging Time	Automatic, stops at 8.4 V
Max. Charging Time	2-3 hours depending on battery capacity
Rapid Charge	1,6 A +/- 5%
Trickle Charge	0 to 50 mA
LED Charging Indicator	LED Red to Green indicator
Temperature Control	Controlled by battery and charger
Operating Temperature	-40° C to + 50° C / -40° F to 122° F (can be restricted by battery chemistry)
EMI/RFI	CE, E, FCC Part 15 Class B, ICES-003 Class B
Environmental	RoHS Compliant
Electrical Testing	ISO 7637 and SAE J1455
Input Transient Protected	Withstands +200V & -600V. A 2,5A fuse is mounted on the incoming supply.
Output Short Circuit Protected	The charger will supply a maximum current of 1,6 A which protects both the charger and the connected equipment. The current limit is set to standards of the producer and shall not be higher.