



## APC SRTG15KXLI UPS-virtalähde Taajuuden kaksoismuunnos (verkossa) 15 kVA 15000 W

**Tuotemerkki :** APC

**Tuotekoodi:** SRTG15KXLI

**Tuotteen nimi :** SRTG15KXLI

APC SRTG15KXLI. UPS topologia: Taajuuden kaksoismuunnos (verkossa), Kokonaislähtöteho (VA): 15 kVA, Lähtöteho: 15000 W. Pistorasian tyypit: Hard Wire 5-wire (3P + N + E), Sarjalitännän tyyppi: RS-232. Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 192 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelot: Telineasennettava/Torni, Tuotteen väri: musta, Telineen kapasiteetti: 7U. Tuotteen leveys: 440 mm, Tuotteen syvyys: 700 mm, Tuotteen korkeus: 306 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery voltage	192 V
Output power capacity *	15 kVA	Battery life (max)	5 year(s)
Output power *	15000 W	Battery recharge time	4 h
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	160 V	<b>Design</b>	
Input operation voltage (max) *	415 V	Form factor *	Rackmount/Tower
Input frequency *	40/70 Hz	Rack capacity	7U
Output operation voltage (max)	230 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Output frequency regulation	0.1 Hz	LED indicators	✓
Maximum current	66 A	International Protection (IP) code	IP20
Number of output phases	3	<b>Operational conditions</b>	
Efficiency	93%	Operating temperature (T-T)	0 - 40 °C
Crest factor	3:1	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Input current Total Harmonic Distortion (THD)	5%	Storage relative humidity (H-H)	0 - 95%
Noise level	58 dB	Operating altitude	0 - 2011.68 m
Surge protection	✓	Non-operating altitude	0 - 15240 m
Audible alarm(s)	✓	<b>Weight &amp; dimensions</b>	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Width	440 mm
Auto-restart	✓	Depth	700 mm
<b>Ports &amp; interfaces</b>		Height	306 mm
AC outlet types	Hard Wire 5-wire (3P + N + E)	Weight	142.5 kg
USB port	✓	Package width	590 mm
Serial interface	✓	Package depth	790 mm
Serial interface type	RS-232	Package height	535 mm
		Package weight	156.7 kg

Ports & interfaces		Packaging data	
SmartSlot	✓	Cables included	RS-232
Battery		Logistics data	
Battery technology	Sealed Lead Acid (VRLA)	Harmonized System (HS) code	85078000



0731304411888



731304411888



8592978462314

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.