

## SilverNet SIL DLC 10M networking cable Black Cat5e F/UTP (FTP)

**Brand :** SilverNet

**Product code:** SIL DLC 10M

**Product name :** SIL DLC 10M

- Installation temperature range: -40 to +85°C
  - Operating temperature range: -40 to +85°C
  - Aluminium Shielded Internal Sheath
  - Aluminium Shielded RJ45 Head
  - Twisted-pair copper wiring
  - Heavy-duty outdoor casing
  - Internal Grounding Wire
- Copper core, Black, 10 m, 2 x RJ-45 Plugs included

[SilverNet SIL DLC 10M networking cable Black Cat5e F/UTP \(FTP\):](#)

The SIL DLC 10M is a 10 Metre Cat5e FTP outdoor cable, designed with 24AWG full copper twisted pairs and is foil shielded to ensure any EMI is kept to a minimum. It also has an internal grounding wire so it can be earthed.

Features a Solid Copper Core, Aluminium Shielding, Twisted Pair Wiring, Outdoor Grade Sheath and includes 2x Shielded RJ45 Plugs.

The SIL DLC 10M is suitable for burying underground, mounting to buildings or installing indoors. The 6mm copper cable is flexible, easy to install and (depending on your network) can deliver speeds of up to 1 gigabit.



Features		Features	
Product colour *	Black	Data transfer rate	1000 Mbit/s
Cable length *	10 m	Frequency	100 MHz
Cable standard *	Cat5e	Plug and Play	✓
Cable shielding *	F/UTP (FTP)	<b>Packaging content</b>	
Connector 1 *	RJ-45	Packaging content	1 x 10 Metre outdoor shielded Ethernet cable with 2 x RJ45 shielded connectors.
Connector 2 *	RJ-45	<b>Weight &amp; dimensions</b>	
Connector contacts plating	Aluminium	Height	10000 mm
Connector shielding	✓	Weight	400 g
Connector shield material	Aluminium	<b>Packaging data</b>	
Jacket material	Polyvinyl chloride (PVC)	Quantity per pack	1 pc(s)
Cable shape	Round	Package width	350 mm
Conductor type	Solid	Package depth	350 mm
Conductor material	Copper	Package height	40 mm
Cable type	Straight-through cable	Package weight	500 g
Cabling technology	10/100/1000Base-T(X)	Package type	Bag
Ethernet interface type	Gigabit Ethernet	<b>Logistics data</b>	
AWG wire size	24	UK Trade Tariff code	85444210



5704174161929



5060693980534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.