## Epson TM-M30II-SL (511) 203 x 203 DPI Wired Direct thermal POS printer

**Brand :** Epson

**Product name :** TM-M30II-SL (511)

**Product code:** C31CH63511

- All-in-one POS solution: Printer and tablet stand
- Discreet design: Stylish, practical design with small footprint and clean lines
- Flexibility: Virtually all tablet devices to be securely fixed in place
- Enhanced connectivity: A rich set of connectivity features and options
- Reliability: Epson's tried and trusted build quality
Themal Line, 250 mm/sec, 203 DPI, Ethernet, Display
Epson TM-M30II-SL (511). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite). Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 2.2 million cuts. Product colour: White

### Printing

| | |
|---|---|
| Maximum resolution | 203 x 203 DPI |
| Print speed | 250 mm/sec |
| Print speed (receipt) | 250 mm/sec |
| Printing characters | Text, Graphic, Barcode |
| Character sets | ANK |
| Print technology * | Direct thermal |
| Type * | POS printer |

### Paper handling

| | |
|---|---|
| Maximum roll diameter | 8.3 cm |
| Supported paper width | 58 mm - 80 mm (Breite) |

### Ports & interfaces

| | |
|---|---|
| USB port * | ✔ |
| USB 2.0 ports quantity | 4 |
| USB connector | USB Type-A / USB Type-B |
| Serial interface * | ✘ |
| Connectivity technology * | Wired |

### Network

| | |
|---|---|
| Ethernet LAN * | ✔ |

### Features

| | |
|---|---|
| Sound pressure level (printing) | 55 dB |
| Mean time between failures (MTBF) | 360000 h |
| Cutter | ✔ |
| Half-cutter | ✔ |
| Autocutter durability | 2.2 million cuts |
| Tablet charge & sync | ✔ |
| Print head life | 150 km |

### Power

| | |
|---|---|
| Power source type * | AC |
| AC adapter model | PS-180 |
| Power plug type | Type C |

### Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 5 - 45 °C |
| Storage temperature (T-T) | -20 - 60 °C |
| Operating relative humidity (H-H) | 10 - 90% |
| Storage relative humidity (H-H) | 10 - 90% |

### Weight & dimensions

| | |
|---|---|
| Width | 140 mm |
| Depth | 214 mm |
| Height | 255 mm |
| Weight | 2.9 kg |

### Packaging data

| | |
|---|---|
| Quantity per pack | 1 pc(s) |
| Package width | 390 mm |
| Package depth | 410 mm |
| Package height | 245 mm |
| Package weight | 5.04 kg |

### Print technology

| | |
|---|---|
| Column capacity | 48/57 |

### Logistics data

| | |
|---|---|
| Pallet weight (UK) | 0 g |
| Harmonized System (HS) code | 84433210 |
| Products per pallet (UK) | 32 pc(s) |

## Features

| | |
|---|---|
| Country of origin | Philippines |
| Mounting position | Vertical |
| Built-in sensors details | Paper End Sensor, Paper Near End Sensor |

## Design

| | |
|---|---|
| Product colour * | White |
| Built-in display | ✔ |

## Technical details

| | |
|---|---|
| Font styles | ANK |
| Lifetime | 17000000 lines |

## Other features

| | |
|---|---|
| Buffer size | 12 KB |
| Mean cycles between failures (MCBF) | 65000000 |
| Print head life | 150.000.000 Impulse |

8715946696614