

Epson TM-U220D (052B0): USB+DMD, PS, EDG, EU

Brand : Epson

Product code: C31C515052B0

Product name : Epson TM-U220D (052B0): USB+DMD, PS, EDG, EU

TM-U220D, Serial Impact Dot Matrix, 4.7-6 lps, 76/69.5/57.5mm, USB, 24V DC, 31W, Black

[Epson TM-U220D \(052B0\): USB+DMD, PS, EDG, EU:](#)

EASY-TO-USE IMPACT PRINTER

If you need a hard worker that's easy to use and versatile, this is the ideal impact receipt printer.

Innovative, high-performance and reliable, the TM-U220 impact receipt printer series is exceptionally easy-to-use. Printing in 2-colour as standard, the series includes a host of features such as drop-in paper load, selectable auto-cutter and clamshell covers for fast access and maintenance.

Epson TM-U220D (052B0): USB+DMD, PS, EDG, EU. Print technology: Dot matrix. Maximum roll diameter: 8.3 cm, Supported paper width: 76 mm. Connectivity technology: Wired, Standard interfaces: USB 2.0. Sound pressure level (printing): 64 dB, Mean time between failures (MTBF): 180000 h, Country of origin: Japan. Product colour: Grey



Printing		Weight & dimensions	
Colour	✓	Height	139 mm
Print technology *	Dot matrix	Weight	2.3 kg
Paper handling		Packaging data	
Maximum roll diameter	8.3 cm	Cables included	AC
Supported paper width	76 mm	Quantity per pack	1 pc(s)
Ports & interfaces		Package width	240 mm
Connectivity technology *	Wired	Package depth	375 mm
Standard interfaces	USB 2.0	Package height	250 mm
Features		Package weight	3.86 kg
Sound pressure level (printing)	64 dB	Print technology	
Mean time between failures (MTBF)	180000 h	Column capacity	33/40
Country of origin	Japan	Logistics data	
Mounting position	Horizontal/Vertical	Pallet weight (UK)	0 g
Wall mountable	✓	Harmonized System (HS) code	84433210
Maximum number of copies	1 copies	Products per pallet	72 pc(s)
Built-in sensors details	Roll paper cover open sensor, Paper End Sensor	Products per pallet layer	8 pc(s)
Safety	TÜV	Pallet gross width	120 cm
Certification	CE	Pallet gross height	100 cm
Design		Pallet gross weight	0 g
Product colour *	Grey	Products per pallet (UK)	108 pc(s)
Power		Products per pallet layer (UK)	12 pc(s)
AC input voltage	24 V	Pallet width (UK)	100 cm
Operational conditions		Pallet length (UK)	120 cm
Operating relative humidity (H-H)	10 - 90%	Pallet height (UK)	2.6 m
Storage relative humidity (H-H)	10 - 90%	Technical details	
		Changeable interface	✓
		Lifetime	7500000 lines

Weight & dimensions		Other features	
Width	160 mm	Dimensions (WxDxH)	160 x 286 x 139 mm
Depth	248 mm	Buffer size	128 KB
		Mean cycles between failures (MCBF)	18000000



8715946486550

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date