

## Epson TM-P80 (652A0) 203 x 203 DPI Wired & Wireless Thermal POS printer

**Brand :** Epson

**Product code:** C31CD70652A0

**Product name :** TM-P80 (652A0)

Thermal Line, 100mm/sec, 203 x 203DPI, USB 2.0 Type Mini-B, Bluetooth, 53dB, 110 x 140 x 64mm, 0.5kg, Black

Epson TM-P80 (652A0) 203 x 203 DPI Wired & Wireless Thermal POS printer:

Epson TM-P80 (652A0): Receipt, NFC, BT, PS, UK

Epson TM-P80 (652A0). Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 5.1 cm, Media thickness: 0.05 - 0.08 mm. Connectivity technology: Wired & Wireless, USB connector: Mini-USB Type-B, Standard interfaces: Bluetooth, NFC, USB. Sound pressure level (printing): 53 dB, Mean time between failures (MTBF): 120000 h, Country of origin: China. Product colour: Black



Printing		Weight & dimensions	
Maximum resolution	203 x 203 DPI	Width	110 mm
Print speed	100 mm/sec	Depth	140 mm
Print technology *	Thermal	Height	64 mm
Type *	POS printer	Weight	500 g
Paper handling		Packaging data	
Maximum roll diameter	5.1 cm	Cables included	AC, USB
Media thickness	0.05 - 0.08 mm	Quantity per pack	1 pc(s)
Ports & interfaces		Package width	195 mm
USB port *	✓	Package depth	240 mm
USB connector	Mini-USB Type-B	Package height	172 mm
Bluetooth	✓	Package weight	1.64 kg
Connectivity technology *	Wired & Wireless	Packaging content	
Near Field Communication (NFC)	✓	AC adapter included	✓
Standard interfaces	Bluetooth, NFC, USB	Logistics data	
Features		Harmonized System (HS) code	84433210
Sound pressure level (printing)	53 dB	Products per pallet	160 pc(s)
Mean time between failures (MTBF)	120000 h	Products per pallet layer	32 pc(s)
Country of origin	China	Pallet gross width	80 cm
Safety	UL, CSA	Pallet gross length	120 cm
Design		Pallet gross height	2 m
Product colour *	Black	Products per pallet (UK)	240 pc(s)
Power		Products per pallet layer (UK)	48 pc(s)
Power source type *	AC, Battery	Pallet width (UK)	100 cm
Battery life (max)	46 h	Pallet length (UK)	120 cm
		Pallet height (UK)	2 m
Operational conditions		Other features	
Storage temperature (T-T)	-25 - 70 °C	Electromagnetic compatibility	FCC class A, CE marking
Operating relative humidity (H-H)	10 - 90%	LED indicators	✓
		Mean cycles between failures (MCBF)	16000000



8715946603483

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-OCT-2024. Prints or copies of Information are only valid on the printed Publication date