

EPSON

## Epson TM-P80 (652A0) 203 x 203 DPI Wired & Wireless Thermal POS printer

**Brand :** Epson

**Product code:** C31CD70652A0

**Product name :** TM-P80 (652A0)

Thermal Line, 100mm/sec, 203 x 203DPI, USB 2.0 Type Mini-B, Bluetooth, 53dB, 110 x 140 x 64mm, 0.5kg, Black

[Epson TM-P80 \(652A0\) 203 x 203 DPI Wired & Wireless Thermal POS printer:](#)

Epson TM-P80 (652A0): Receipt, NFC, BT, PS, UK

Epson TM-P80 (652A0). Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 5.1 cm, Media thickness: 0.05 - 0.08 mm. Connectivity technology: Wired & Wireless, USB connector: Mini-USB Type-B, Standard interfaces: Bluetooth, NFC, USB. Sound pressure level (printing): 53 dB, Mean time between failures (MTBF): 120000 h, Country of origin: China. Product colour: Black



| Printing                          |                     | Weight & dimensions            |                         |
|-----------------------------------|---------------------|--------------------------------|-------------------------|
| Maximum resolution                | 203 x 203 DPI       | Width                          | 110 mm                  |
| Print speed                       | 100 mm/sec          | Depth                          | 140 mm                  |
| Print technology *                | Thermal             | Height                         | 64 mm                   |
| Type *                            | POS printer         | Weight                         | 500 g                   |
| Paper handling                    |                     | Packaging data                 |                         |
| Maximum roll diameter             | 5.1 cm              | Cables included                | AC, USB                 |
| Media thickness                   | 0.05 - 0.08 mm      | Quantity per pack              | 1 pc(s)                 |
| Ports & interfaces                |                     | Package width                  | 195 mm                  |
| USB port *                        | ✓                   | Package depth                  | 240 mm                  |
| USB connector                     | Mini-USB Type-B     | Package height                 | 172 mm                  |
| Bluetooth                         | ✓                   | Package weight                 | 1.64 kg                 |
| Connectivity technology *         | Wired & Wireless    | Packaging content              |                         |
| Near Field Communication (NFC)    | ✓                   | AC adapter included            | ✓                       |
| Standard interfaces               | Bluetooth, NFC, USB | Logistics data                 |                         |
| Features                          |                     | Harmonized System (HS) code    | 84433210                |
| Sound pressure level (printing)   | 53 dB               | Products per pallet            | 160 pc(s)               |
| Mean time between failures (MTBF) | 120000 h            | Products per pallet layer      | 32 pc(s)                |
| Country of origin                 | China               | Pallet gross width             | 80 cm                   |
| Safety                            | UL, CSA             | Pallet gross length            | 120 cm                  |
| Design                            |                     | Pallet gross height            | 2 m                     |
| Product colour *                  | Black               | Products per pallet (UK)       | 240 pc(s)               |
| Power                             |                     | Products per pallet layer (UK) | 48 pc(s)                |
| Power source type *               | AC, Battery         | Pallet width (UK)              | 100 cm                  |
| Battery life (max)                | 46 h                | Pallet length (UK)             | 120 cm                  |
| Pallet height (UK)                |                     | Pallet height (UK)             | 2 m                     |
| Operational conditions            |                     | Other features                 |                         |
| Storage temperature (T-T)         | -25 - 70 °C         | Electromagnetic compatibility  | FCC class A, CE marking |

**Operational conditions**

Operating relative humidity (H-H) 10 - 90%

**Other features**

|                                     |          |
|-------------------------------------|----------|
| LED indicators                      | ✓        |
| Mean cycles between failures (MCBF) | 16000000 |



8715946603483

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date