

Epson M30II-HW 203 x 203 DPI Wired Thermal POS printer

Brand : Epson

Product code: C31CH92141F1

Product name : M30II-HW

- conic design: Stylish, practical design with small footprint and clean lines
- Cost effective: Entry-level model (refreshed version of its predecessor, the TM-m30)
- Fast printing: Increased print speed of 250mm/s
- Direct printing from mobile devices: Without the need to install or update drivers
- Reliable: Epson's tried and trusted build quality

Compact mPOS receipt printer TM-M30II-HW, 203 DPI, 250 mm/sec, 5 Years TSE

Epson M30II-HW. Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Supported paper width: 58 - 80 mm, Maximum printing width: 8 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Country of origin: Philippines. Product colour: White



Printing		Operational conditions	
Maximum resolution	203 x 203 DPI	Operating relative humidity (H-H)	10 - 90%
Print speed	250 mm/sec	Storage relative humidity (H-H)	10 - 90%
Print technology *	Thermal	Weight & dimensions	
Type *	POS printer	Width	127 mm
Paper handling		Depth	127 mm
Supported paper width	58 - 80 mm	Height	127 mm
Maximum printing width	8 cm	Weight	1.3 kg
Ports & interfaces		Packaging data	
USB port *	✓	Quantity per pack	1 pc(s)
USB 2.0 ports quantity	2	Package width	195 mm
USB connector	USB Type-A / USB Type-B	Package depth	235 mm
Bluetooth	✓	Package height	240 mm
Connectivity technology *	Wired	Package weight	2.39 kg
Near Field Communication (NFC)	✓	Logistics data	
Network		Pallet weight (UK)	0 g
Ethernet LAN *	✓	Harmonized System (HS) code	84433210
Wi-Fi *	✗	Products per master (outer) case	4 pc(s)
Features		Master (outer) case width	400 mm
Sound pressure level (printing)	55 dB	Master (outer) case length	490 mm
Mean time between failures (MTBF)	360000 h	Master (outer) case height	255 mm
Country of origin	Philippines	Master (outer) case gross weight	0 g
Design		Products per pallet	128 pc(s)
Product colour *	White	Pallet gross weight	0 g
Power		Products per pallet (UK)	192 pc(s)
Power source type *	AC	Technical details	
		Master (outer) case GTIN (EAN/UPC)	8715946696201

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-20 - 60 °C



8715946688572

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date