

Epson M30II-HW 203 x 203 DPI Langallinen Thermal Maksupäätetulostin

Tuotemerkki : Epson

Tuotekoodi: C31CH92142F1

Tuotteen nimi : M30II-HW

- Tyylikäs rakenne: Hienostunut ja käytännöllinen rakenne, pieni tilantarve
 - Edullinen: Perustason malli (edeltäjänsä TM-m30:n päivitetty versio)
 - Nopea tulostus: Suurempi tulostusnopeus, jopa 250 mm/s
 - Suoratulostus mobiililaitteista: Ei ohjainten asennus- tai päivitystarvetta
 - Luotettava: Epsonin hyväksi todettu ja luotettu laatu
- Pienikokoinen mPOS-kuittitulostin TM-M30II-HW, 203 DPI, 250 mm/sec, 5 Years TSE
Epson M30II-HW. Tulostustekniikka: Thermal, Malli: Maksupäätetulostin, Suurin resoluutio: 203 x 203 DPI.
Tuetut paperin leveydet: 58 - 80 mm, Tulostuksen enimmäisleveys: 8 cm. Yhteysteknologia: Langallinen, USB-liitin: USB Type-A / USB Type-B. Äänenpainetaso (tulostus): 55 dB, Keskimääräinen vikaantumisaika: 360000 h, Alkuperämaa: Filippiinit. Tuotteen väri: musta



Printing		Operational conditions	
Maximum resolution	203 x 203 DPI	Operating relative humidity (H-H)	10 - 90%
Print speed	250 mm/sec	Storage relative humidity (H-H)	10 - 90%
Print technology *	Thermal	Weight & dimensions	
Type *	POS printer	Width	127 mm
Paper handling		Depth	127 mm
Supported paper width	58 - 80 mm	Height	127 mm
Maximum printing width	8 cm	Weight	1.3 kg
Ports & interfaces		Packaging data	
USB port *	✓	Quantity per pack	1 pc(s)
USB 2.0 ports quantity	2	Package width	195 mm
USB connector	USB Type-A / USB Type-B	Package depth	235 mm
Connectivity technology *	Wired	Package height	240 mm
Near Field Communication (NFC)	✓	Package weight	2.37 kg
Network		Logistics data	
Ethernet LAN *	✓	Pallet weight (UK)	0 g
Wi-Fi *	✗	Harmonized System (HS) code	84433210
Features		Products per master (outer) case	4 pc(s)
Sound pressure level (printing)	55 dB	Master (outer) case width	400 mm
Mean time between failures (MTBF)	360000 h	Master (outer) case length	490 mm
Country of origin	Philippines	Master (outer) case height	255 mm
Design		Master (outer) case gross weight	0 g
Product colour *	Black	Products per pallet	128 pc(s)
Power		Pallet gross weight	0 g
Power source type *	AC	Products per pallet (UK)	192 pc(s)
Operational conditions		Technical details	
Operating temperature (T-T)	5 - 45 °C	Master (outer) case GTIN (EAN/UPC)	8715946696249
Storage temperature (T-T)	-20 - 60 °C		



8715946688596

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date