



Product 512944



512944 Active holder with cig-plug With tilt swivel. 2A charging. With USB A outlet in the cig-plug, 1A charging. 12/24V.

Keep your phone's battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. With cig-plug cable, 2A charging via the Micro-USB connector. You can charge a second device via the USB A outlet in the cig-plug, 1A charging. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the phone in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 20° and swivels 360°. Mounting plate 42x50 mm with predrilled AMPS-holes +2x3,5 mm centered holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Attach onto ProClip Mounting Platform.

Dimensions: 78 x 99 x 47 mm (W x H x D mm)

Weight: 131 g

Cable length (+plug 8 cm): 46 cm, stretched:100 cm (or a bit more if needed).

Charging specifications:

Input voltage: DC/10-30V

Charging voltage: DC/4.75-5.25V

Output current(Typ): 2.0A

LED charging indicator: Power on.

Operating temperature: 0°C ~ +40°C

Storage temperature: -20°C ~ +60°C

Approvals: E, CE, FCC, ROHS

EAN: 7320285129443

Item no 512944 fits:

Samsung Galaxy J5 (2016) (For all countries)

INSTALLATION INSTRUCTIONS

1.



2.



3.



4.



Please read all of the instructions and look at the pictures before attaching the holder.

1. Loosen the screw in the center of the holder so you can remove the tilt swivel attaching plate on the back.
 2. Place the attaching plate onto the desired position. Screw the attaching plate into place with the enclosed screws.
 3. Place the holder over the attaching plate so the screw fits in the hole in the tilt swivel. Screw a few turns on the screw, just so the thread starts to pull. Pull the holder toward you and hold it slightly tensed, in the same time tighten the screw so the holder is pulled toward the tilt swivel. Tighten the screw firm at first, then loosen it a bit so the holder is firmly in place, but still can be adjusted.
 4. The holder is in place.
-