



Product 513944



513944 Active holder for fixed installation With tilt swivel. 2A charging. 12/24V.

Keep your phone's battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. For fixed installation. The holder is to be connected inside the dashboard, providing an elegant installation without any cables hanging over the interior. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the phone in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 20° and swivels 360°. Mounting plate 42x50 mm with predrilled AMPS-holes +2x3,5 mm centered holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 2A fuse. Professional installation recommended. Attach onto ProClip Mounting Platform.

Dimensions: 78 x 99 x 47 mm (W x H x D mm)

Weight: 179 g

Cable length: Total length: 342 cm (Holder to box: 172 cm, Connectors+box 14 cm, Box to open end: 156 cm.)

Charging specifications:

Input voltage: DC/10-30V

Charging voltage: DC/4.75-5.3V

Output current(Typ): 2.0A

Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output short protection

LED charging indicator: Power input indicator(Green), Ovp/Ocp/Output short(Red)

Operating temperature: 0°C ~ +40°C

Storage temperature: -20°C ~ +80°C

Approvals: E, CE, FCC, ROHS.

EAN: 7320285139442

Item no 513944 fits:

Samsung Galaxy J5 (2016) (For all countries)

INSTALLATION INSTRUCTIONS

1.



2.



3.



4.



Please read all of the instructions and look at the pictures before attaching the holder. Important Note: The charger unit is fused internally with 2 A automotive re-settable thermal fuse, but if an external fuse is to be installed then connect a 2 A fuse holder and fuse inline with the Red wire close to the power source. Route the cable from the holder into the vehicle dashboard and secure the charger unit in place. Ensure the charger unit is securely mounted behind the dashboard in a well ventilated area that does not get hot! Route the power cable from the charger unit to the power supply source in the vehicle and connect as follows: 1. Connect the White wire to a Negative Ground connection of the vehicle or the vehicle chassis. 2. Connect the Red wire to a 12 Volt power supply in the vehicle that is controlled by the ignition switch of the vehicle.

Installation of the holder: 1. Loosen the screw in the center of the holder so you can remove the tilt swivel attaching plate on the back. 2. Place the attaching plate onto the desired position. Screw the attaching plate into place with the enclosed screws. Place the holder over the attaching plate so the screw fits in the hole in the tilt swivel. 3. Screw a few turns on the screw, just so the thread starts to pull. Pull the holder toward you and hold it slightly tensed, in the same time tighten the screw so the holder is pulled toward the tilt swivel. Tighten the screw until the holder is firmly in place, but still can be adjusted. 4. The holder is in place.