



Product 527945



527945 Active holder for fixed installation With tilt swivel. 12V/2A

Use an active holder for your Galaxy A5 (2017) on the road and you will always have a freshly charged battery! In addition, you will always have your Galaxy A5 (2017) within easy sight and reach. Safe, comfortable and convenient! The active holder is to be connected inside the dashboard. It provides an elegant installation without any cables hanging over the interior. The holder has a neat and discreet design which blends well with the vehicle's interior. Your Galaxy A5 (2017) is held securely in place in an upright position for maximum cellular reception.

When you place the Galaxy A5 (2017) in the holder, it automatically connects to the charging unit. 12 Volt. The product is E-approved. Connect the power cable with a 2 A fuse. Professional installation recommended.

The holder is made of ABS and has a perfect fit. It is easy to put the device into the holder, and just as easy to take it with you when leaving the vehicle. The holder is equipped with a tilt swivel so you can adjust the angle of your device in order to avoid light reflection on the screen. You can tilt the holder 22° in each direction. Attach onto ProClip Mounting Platform.

Dimensions: 70 x 95 x 47 mm (W x H x D mm)

Weight: 168 g

Cable length: Total length: 398 cm (Holder to box: 145 cm, Connectors+box 10 cm, Box to open end: 243 cm.)

EAN: 7320285279452

Item no 527945 fits:

Samsung Galaxy A5 (2017) (For all countries)

INSTALLATION INSTRUCTIONS

1.



2.



3.



4.



Please read all of the instructions and look at the pictures before attaching the holder. Important Note: Connect to a 2 A fuse holder and fuse inline with the Red wire close to the power source. Route the cable from the holder into the vehicle dashboard and secure the charger unit in place. Ensure the charger unit is securely mounted behind the dashboard in a well ventilated area that does not get hot! Route the power cable from the charger unit to the power supply source in the vehicle and connect as follows: 1. Connect the White wire to a Negative Ground connection of the vehicle or the vehicle chassis. 2. Connect the Red wire to a 12 Volt power supply in the vehicle that is controlled by the ignition switch of the vehicle.

Installation of the holder: 1. Loosen the screw in the center of the holder so you can remove the tilt swivel attaching plate on the back. 2. Place the attaching plate onto the desired position. Screw the attaching plate into place with the enclosed screws. Place the holder over the attaching plate so the screw fits in the hole in the tilt swivel. 3. Screw a few turns on the screw, just so the thread starts to pull. Pull the holder toward you and hold it slightly tensed, in the same time tighten the screw so the holder is pulled toward the tilt swivel. Tighten the screw until the holder is firmly in place, but still can be adjusted. 4. The holder is in place.