



Lindy 2m Cat.6A U/FTP Ultra Slim Network Cable, Grey

Brand : Lindy

Product code: 47594

Product name : 2m Cat.6A U/FTP Ultra Slim Network Cable, Grey

2m Cat.6A U/FTP Ultra Slim Network Cable, Grey

[Lindy 2m Cat.6A U/FTP Ultra Slim Network Cable, Grey:](#)

Cat.6AU/FTP Ultra slim network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10GBase-T.

Cat 6A cable, for operating frequencies up to 500MHz, shielded with foil shielded with single pair shielding (U/FTP). Designed as an ultra slim cable for use in environments with restricted or limited installation space. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The very flexible and thin cable construction allows the cables to be installed in restricted or limited spaces such as server rooms or network hubs.

Available lengths: 0.3m, 1m, 1.5m, 2m, 3m, 5m.



Features		Features	
Product colour *	Grey	AWG wire size	28
Cable length *	2 m	Frequency	500 MHz
Cable standard *	Cat6a	Bend radius (min)	6 cm
Cable shielding *	U/FTP (STP)	Operational conditions	
Connector 1 *	RJ-45	Operating temperature (T-T)	-10 - 60 °C
Connector 2 *	RJ-45	Storage temperature (T-T)	-10 - 40 °C
Connector 1 gender *	Male	Weight & dimensions	
Connector 2 gender *	Male	Width	11 mm
Connector 1 form factor	Straight	Depth	28 mm
Connector 2 form factor	Straight	Height	6 mm
Connector contacts plating	Nickel	Outer diameter	3.6 mm
Connector shielding	✓	Packaging data	
Connector shield material	Aluminium	Package type	Polybag
Jacket material	Polyvinyl chloride (PVC)	Technical details	
Conductor material	Copper	Sustainability compliance	✓
		Compliance certificates	REACH, RoHS



4002888475945

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-NOV-2024. Prints or copies of Information are only valid on the printed Publication date