



DELL 452-BCCX kannettavien tietokoneiden telakka ja porttitoistin Langallinen musta

Tuotemerkki : DELL

Tuotekoodi: 452-BCCX

Tuotteen nimi : 452-BCCX



DELL 452-BCCX. Yhteisteknologia: Langallinen. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s.
Tuotteen väri: musta, Tuotemerkin yhteensopivuus: Dell. Virtalähteen malli: DC. Windows-
käyttöjärjestelmätuki: Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise,
Windows 10 Enterprise x64,...



| Ports & interfaces | | Performance | |
|---|--------------------|-------------------------------------|---|
| Connectivity technology * | Wired | LED indicators | ✓ |
| USB 2.0 ports quantity * | 2 | Brand compatibility | Dell |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 3 | Power | |
| HDMI ports quantity * | 1 | Power source type | DC |
| VGA (D-Sub) ports quantity | 1 | Software | |
| Mini DisplayPorts quantity | 1 | | Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64 |
| Microphone in * | ✓ | Windows operating systems supported | |
| Headphone outputs * | 1 | | |
| DC-in jack | ✓ | | |
| Network | | | |
| Ethernet LAN * | ✓ | | |
| Ethernet LAN (RJ-45) ports | 1 | | |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | | |
| Performance | | | |
| Card reader integrated * | ✗ | | |
| Cable lock slot | ✓ | | |
| Product colour * | Black | | |
| | | Weight & dimensions | |
| | | Width | 155 mm |
| | | Depth | 109 mm |
| | | Height | 21.1 mm |
| | | Weight | 422 g |

Packaging content

| | |
|---------------------|-------------|
| Cables included | DisplayPort |
| AC adapter included | ✓ |
| Manual | ✓ |

Logistics data

| | |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733020 |
|-----------------------------|----------|



5397063840076

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-NOV-2024. Prints or copies of Information are only valid on the printed Publication date