

Verbatim 53656 ulkoinen SSD 512 GB USB Type-C 3.2 Gen 1 (3.1 Gen 1) Harmaa

Tuotemerkki : Verbatim

Tuotekoodi: 53656

Tuotteen nimi : 53656

Verbatim 53656. SSD-kapasiteetti: 512 GB, SSD-malli: M.2. USB-liitin: USB Type-C, USB-versio: 3.2 Gen 1 (3.1 Gen 1). Lukunopeus: 324 MB/s, Kirjoitusnopeus: 358 MB/s. Tiedonsiirtonopeus: 5 Gbit/s. Tuotteen väri: Harmaa



Solid state drive		Weight & dimensions	
SSD form factor	M.2	Depth	111 mm
SSD capacity *	512 GB	Height	13 mm
NVMe *	✗	Weight	58.5 g
Read speed *	324 MB/s	Packaging data	
Write speed *	358 MB/s	Package width	90 mm
Ports & interfaces		Package depth	30 mm
Thunderbolt technology *	✗	Package height	150 mm
USB connector *	USB Type-C	Package weight	132 g
USB version *	3.2 Gen 1 (3.1 Gen 1)	Package type	Box
Wi-Fi *	✗	Packaging content	
Data transfer rate	5 Gbit/s	Cables included	USB Type-C to USB Type-A
Features		Manual	✓
Housing material *	Aluminium, Plastic	Bundled software	Nero Backup Software
Product colour *	Grey	Other features	
Windows operating systems supported	Windows 10, Windows 7, Windows 8	Built-in USB hub	✗
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	Card reader integrated	✗
		USB powered	✓
		Logistics data	
		Pallet gross length	123 cm
		Pallet gross width	80 cm
		Pallet gross height	120 cm
		Harmonized System (HS) code	84717070

Features		Logistics data	
Compliance certificates	CE, RoHS	Master (outer) cases per pallet	30 pc(s)
Country of origin	China	Layers per pallet	10 pc(s)
Security		Products per pallet	300 pc(s)
Hardware encryption *	✓	Master (outer) case width	142 mm
Security algorithms	256-bit AES	Master (outer) case length	116 mm
Power		Master (outer) case height	200 mm
Operating voltage	5 V	Master (outer) case gross weight	646 g
Operational conditions		Products per master (outer) case	4 pc(s)
Operating temperature (T-T)	5 - 50 °C		
Storage temperature (T-T)	-40 - 70 °C		
Operating relative humidity (H-H)	5 - 90%		
Weight & dimensions			
Width	40 mm		



0023942536567



023942536567

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.