



## BenQ WDC10HC langaton esitysjärjestelmä HDMI Työpöytä

**Tuotemerkki :** BenQ

**Tuotekoodi:** 9H.JLD78.N6E

**Tuotteen nimi :** WDC10HC

BenQ WDC10HC. Kotelo: Työpöytä, Tuotteen väri: musta. Tuetut grafiikan erottelutarkkuudet: 800 x 600 (SVGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA),..., Tuetut videomoodit: 720p, 1080p, Suurin kuvataajuus: 60 fps. Antennityyppi: Ulkoinen, Antennin vahvistustaso (maks.): 2 dBi. Wi-Fi-standardit: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Langattoman LAN:in datansiirtonopeus (maksimi): 867 Mbit/s, Wi-Fi-standardi: Wi-Fi 5 (802.11ac). Käyttöliittymä: HDMI



Design		Power	
Form factor *	Desktop	Power source type *	DC
Product colour	Black	Output voltage	5 V
LED indicators	✓	Input current	1.5 A
Features		Power consumption (max)	5 W
Supported graphics resolutions	800 x 600 (SVGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	System requirements	
		Windows operating systems supported	✓
		Mac compatibility	✓
		Operational conditions	
Supported video modes	720p, 1080p	Operating temperature (T-T)	0 - 40 °C
Maximum frame rate	60 fps	Operating relative humidity (H-H)	10 - 80%
Number of simultaneously connected devices (max)	16	Storage temperature (T-T)	-10 - 60 °C
Security updates end date	31/12/2024	Storage relative humidity (H-H)	5 - 90%
Antenna		Weight & dimensions	
Antenna type	External	Weight	1.24 kg
Antenna gain level (max)	2 dBi	Package width	390 mm
Antennas quantity	2	Package depth	485 mm
Network		Package height	205 mm
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Package weight	6.28 kg
Wi-Fi data rate (max)	867 Mbit/s	Packaging content	
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	AC adapter included	✓
Frequency band	5 GHz	Cables included	HDMI, USB
Ethernet LAN	✓	Quick start guide	✓
Ethernet LAN data rates	10,100 Mbit/s	Logistics data	
Cabling technology	10/100Base-T(X)	Country of origin	Taiwan
Security algorithms	128-bit AES, WPA2, WPA2-PSK	Products per pallet	144 pc(s)
Maximum operating distance	8 m	Quantity per pack	3 pc(s)
		Harmonized System (HS) code	8517620000

Ports & interfaces

Interface *	HDMI
Number of HDMI outputs	1
HDMI version	1.4
Ethernet LAN (RJ-45) ports	1
DC-in jack	✓



4718755083945

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-APR-2025. Prints or copies of Information are only valid on the printed Publication date