



BenQ SL4302K 109.2 cm (43") LED 500 cd/m² 4K Ultra HD Black Android 8.0

Brand : BenQ

Product code: 9H.F66PK.NA2

Product name : SL4302K



43", 3840x2160px, 500 cd/m², 1200:1, 2x 10W, VGA, 3x HDMI 2.0, DisplayPort 1.2, 3.5mm, RJ-45, 4x USB 2.0/3.0, RS232, Android 8.0

BenQ SL4302K. Display diagonal: 109.2 cm (43"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Operating system installed: Android 8.0. Product colour: Black



Display		Design	
Panel type	IPS	Placement supported *	Indoor
LED backlighting type	Edge-LED	Orientation	Horizontal/Vertical
Display diagonal *	109.2 cm (43")	Product colour *	Black
Display technology *	LED	VESA mounting *	✓
Display resolution *	3840 x 2160 pixels	Panel mounting interface	400 x 400 mm
Display brightness *	500 cd/m ²	Performance	
HD type *	4K Ultra HD	On Screen Display (OSD)	✓
Touchscreen *	✗	Number of OSD languages	26
Contrast ratio (typical)	1200:1	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech
Active display area (W x H)	941.2 x 529.4 mm	Power	
Panel life	50000 h	Power consumption (standby) *	0.5 W
Ports & interfaces		Energy efficiency class (SDR)	G
HDMI ports quantity *	3	Energy consumption (SDR) per 1000 hours	96 kWh
HDMI version	2.0	AC input voltage	100 - 240 V
HDMI input ports quantity	2	AC input frequency	50 - 60 Hz
HDMI output ports quantity	1	Computer system	
DVI port *	✗	Internal memory	4 GB
VGA (D-Sub) input ports	1	Internal storage capacity	32 GB
DisplayPorts quantity *	1	Operating system installed	Android 8.0
DisplayPorts in	1	Weight & dimensions	
USB port *	✓	Display width	965.5 mm
USB ports quantity	4	Display depth	57.5 mm
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Display height	553.9 mm
Ethernet LAN *	✓	Display weight	17.2 kg
Ethernet LAN (RJ-45) ports	1		
Wi-Fi *	✗		
PC Audio in	✓		
RS-232 interface	✓		

Audio		Packaging data	
Built-in speaker(s) *	✓	Package weight	24.5 kg
Number of built-in speakers	2	Operational conditions	
RMS rated power	20 W	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-10 - 60 °C



4718755081033

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date