



BenQ SL5502K 139.7 cm (55") LED 500 cd/m² 4K Ultra HD Black Android

Brand : BenQ

Product code: 9H.F67PK.NA2

Product name : SL5502K

55", 3840x2160px, 16:9, 500 cd/m², 1200:1, 2x 10W, VGA, 2x HDMI, DisplayPort, 4x USB, RJ-45, Android BenQ SL5502K. Display diagonal: 139.7 cm (55"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Operating system installed: Android. Product colour: Black



Display		Design	
LED backlighting type	Direct-LED	Placement supported *	Indoor
Display diagonal *	139.7 cm (55")	Orientation	Horizontal/Vertical
Display technology *	LED	Product colour *	Black
Display resolution *	3840 x 2160 pixels	VESA mounting *	✓
Display brightness *	500 cd/m ²	Panel mounting interface	400 x 400 mm
HD type *	4K Ultra HD	Performance	
Touchscreen *	✗	On Screen Display (OSD)	✓
Native aspect ratio	16:9	Number of OSD languages	26
Contrast ratio (typical)	1200:1	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Active display area (W x H)	1209.6 x 680.4 mm		
Panel life	50000 h		
Ports & interfaces		Power	
HDMI ports quantity *	2	Power consumption (typical) *	85.6 W
DVI port *	✗	Power consumption (standby) *	0.5 W
VGA (D-Sub) input ports	1	AC input voltage	100 - 240 V
DisplayPorts quantity *	1	AC input frequency	50 - 60 Hz
USB port *	✓	Computer system	
USB ports quantity	4	Internal memory	4 GB
Ethernet LAN *	✓	Internal storage capacity	32 GB
Ethernet LAN (RJ-45) ports	1	Operating system installed	Android
Wi-Fi *	✗	Weight & dimensions	
RS-232 interface	✓	Width	1236.4 mm
Audio		Depth	63.1 mm
Built-in speaker(s) *	✓	Height	707.2 mm
Number of built-in speakers	2	Weight	26.4 kg
RMS rated power	20 W	Packaging data	
		Package weight	31.4 kg

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 60 °C



4718755081040

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date