

AXIS M7116 Video Encoder

Cost-effective, 16-channel video encoder with Zipstream

AXIS M7116 is a cost-effective, 16 channel video encoder that adds the benefits of IP surveillance to analog camera systems. It supports standard resolution analog cameras as well as PTZ control over RS-485. This rack-mounted encoder features memory card slots for edge storage as well as support for intelligent analytics such as motion detection and active tampering alarm. Including Zipstream with H.264/H.265, it significantly reduces bandwidth and storage requirements without compromising image quality. Furthermore, it offers enhanced security features such as signed firmware and secure boot.

- > **30 fps on all 16 channels**
- > **PTZ control**
- > **Zipstream with support for H.264/H.265**
- > **Signed firmware and secure boot**
- > **Support for intelligent analytics**



AXIS M7116 Video Encoder

System on chip (SoC)		Cybersecurity	
Model	ARTPEC-7	Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot
Memory	1024 MB RAM, 512 MB Flash Battery backed-up real-time clock	Network security	IEEE 802.1X (EAP-TLS) ^a , HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Video		Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High profiles H.265 (MPEG-H Part 2/HEVC) Main profile Motion JPEG	General	
Resolution	176x144/176x120 (PAL/NTSC) to 720x576/720x480 (PAL/NTSC)	Casing	Metal casing 1U stand alone, rackmount or wallmount Color: white NCS S 1002-B
Frame rate	25/30 fps in all resolutions Up to 30 fps in quad view in full resolution	Sustainability	PVC free
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Quad view	Power	max 26 W
Image settings	Rotation: 0°, 90°, 180°, 270°, de-interlace filter, compression, color, brightness, contrast, aspect ratio correction, mirroring of images, text and image overlay, polygon privacy mask, video termination, sharpness, noise reduction	Connectors	16 pcs analog video BNC inputs 1 pc 1000 BASE-TX Ethernet (RJ45) 4 pcs terminal block for RS485/RS422 serial communication (full duplex) 1 pc DC input terminal block
Pan/Tilt/Zoom	Wide range of analog PTZ cameras supported, drivers included in the firmware Up to 100 preset positions/camera, Guard tour, PTZ control queue Supports Windows compatible joysticks	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Network		Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
IP address	Four IP address, one per four channels	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a , network access control, user access log, multi-level user	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)	Dimensions	44 x 145 x 440 mm (1.7 x 5.7 x 17.3 in)
System integration		Weight	2050 g (4.5 lb)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Included accessories	Installation guide, Windows [®] decoder 1-user license, DC input plug, 8 pcs 2-pin RS485/RS422 plugs, mains power supply, mounting and connector kit
Event conditions	Device status: IP address removed, network lost, new IP address, storage failure, system ready Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, live stream open, tampering Video encoder: video connected	Optional accessories	For accessories, see axis.com
Event actions	Guard tours, upload of images or video clips, notification, overlay text, preset positions, recordings, SNMP trap messages, status LED, video clips MQTT publish	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Data streaming	Event data	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Analytics		Warranty	5-year warranty, see axis.com/warranty
Applications	Included AXIS Video Motion Detection, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p>	