

Epson TM-T88VII (111A0): USB, Ethernet, Serial, PS, UK, White

Tuotemerkki : Epson

Tuotekoodi: C31CJ57111A0

Tuotteen nimi : TM-T88VII (111A0): USB, Ethernet, Serial, PS, UK, White

TM-T88VII (111A0): USB, Ethernet, Serial, PS, UK, White

[Epson TM-T88VII \(111A0\): USB, Ethernet, Serial, PS, UK, White:](#)



Luotettava ja suorituskykyinen

Vältä käyttökatoja valitsemalla todistetusti toimiva ja luotettava markkinoiden johtava1 laite. Nopea tulostus (500 mm/s) ja laadukkaat kuitit takaavat käyttäjän tyytyväisyyden.

Yhteensopiva vanhemman tekniikan kanssa

TM-T88VII on täysin yhteensopiva nykyisten T88V- ja T88VI-ohjelmistojen kanssa, joten yrityksen infrastruktuuriin uudistamiseen ei liity korkeita kustannuksia. Tulostin vie saman verran tilaa kuin aiemmat mallit, joten et joudu vaihtamaan työtasoa tai kassapöytää.

Ekologinen

TM-T88VII:n ympäristövaikutukset ovat pienemmät, sillä sen melutaso on alhaisempi, virrankulutus vähäisempi ja virransyöttö pienempi ja tehokkaampi. Tulostin on nyt yhteensopiva ympäristöystävällisemmän fenolittoman paperin kanssa.



| | | | |
|-----------------------------------|------------------------------------|-----------------------------------|--|
| Printing | | Power | |
| Maximum resolution | 180 x 180 DPI | Power consumption (printing) | 27.9 W |
| Print speed | 500 mm/sec | AC input voltage | 24 V |
| Character size | 1.41 x 3.39 mm | Power consumption | 27900 mA |
| Printing characters | Text, Graphic, Barcode, 2D barcode | Power consumption (standby) | 1400 mA |
| Character sets | ANK | Power consumption (standby) | 1.4 W |
| Print technology * | Thermal | Operational conditions | |
| Type * | POS printer | Operating temperature (T-T) | 5 - 45 °C |
| Paper handling | | Storage temperature (T-T) | -10 - 50 °C |
| Printing media thickness | 48 - 80 µm | Operating relative humidity (H-H) | 10 - 90% |
| Maximum roll diameter | 8.3 cm | Storage relative humidity (H-H) | 10 - 90% |
| Supported paper width | 80 mm | System requirements | |
| Media thickness | 48 - 80 mm | Pre-installed software | Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print |
| Ports & interfaces | | Weight & dimensions | |
| USB port * | ✓ | Width | 145 mm |
| USB connector | USB Type-A / USB Type-B | Depth | 195 mm |
| Serial interface * | ✓ | Height | 148 mm |
| Serial interface type | RS-232 | Weight | 1.7 kg |
| Connectivity technology * | Wired & Wireless | Packaging data | |
| Near Field Communication (NFC) | ✓ | Quantity per pack | 1 pc(s) |
| Optional connectivity | Wireless LAN | Package width | 195 mm |
| Network | | Package depth | 235 mm |
| Ethernet LAN * | ✓ | Package height | 260 mm |
| Features | | Package weight | 2.7 kg |
| Sound pressure level (printing) | 52 dB | Print technology | |
| Sound pressure level (standby) | 52 dB | Column capacity | 42/56 |
| Mean time between failures (MTBF) | 360000 h | | |

| Features | | Logistics data | |
|--------------------------|--|-------------------------------------|----------------|
| Autocutter durability | 3 million cuts | Pallet weight (UK) | 0 g |
| Paper save function | ✓ | Harmonized System (HS) code | 84433210 |
| Print head life | 200 km | Products per pallet | 112 pc(s) |
| Country of origin | Philippines | Pallet gross weight | 0 g |
| Mounting position | Horizontal/Vertical | Products per pallet (UK) | 168 pc(s) |
| Wall mountable | ✓ | Technical details | |
| Built-in sensors details | Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor | Changeable interface | ✓ |
| Certification | CE | Lifetime | 20000000 lines |
| Design | | Other features | |
| Product colour * | White | Buffer size | 4 KB |
| | | Mean cycles between failures (MCBF) | 70000000 |



8715946697086

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-DEC-2024. Prints or copies of Information are only valid on the printed Publication date