

Epson TM-T88VII (152A0): USB, Ethernet, Fixed Interface, PS, UK, Black

Tuotemerkki : Epson

Tuotekoodi: C31CJ57152A0

Tuotteen nimi : TM-T88VII (152A0): USB, Ethernet, Fixed Interface, PS, UK, Black

TM-T88VII (152A0): USB, Ethernet, Fixed Interface, PS, UK, Black

Epson TM-T88VII (152A0): USB, Ethernet, Fixed Interface, PS, UK, Black:

Luotettava ja suorituskykyinen

Vältä käyttökatoja valitsemalla todistetusti toimiva ja luotettava markkinoiden johtava1 laite. Nopea tulostus (500 mm/s) ja laadukkaat kuitit takaavat käyttäjän tyytyväisyyden.

Yhteensopiva vanhemman tekniikan kanssa

TM-T88VII on täysin yhteensopiva nykyisten T88V- ja T88VI-ohjelmistojen kanssa, joten yrityksen infrastruktuurin uudistamiseen ei liity korkeita kustannuksia. Tulostin vie saman verran tilaa kuin aiemmat mallit, joten et joudu vaihtamaan työtasoa tai kassapöytää.

Ekologinen

TM-T88VII:n ympäristövaikutukset ovat pienemmät, sillä sen melutaso on alhaisempi, virrankulutus vähäisempi ja virransyöttö pienempi ja tehokkaampi. Tulostin on nyt yhteensopiva ympäristöystävällisemmän fenolittoman paperin kanssa.



| | | | |
|-----------------------------------|------------------------------------|-----------------------------------|--|
| Printing | | Power | |
| Maximum resolution | 180 x 180 DPI | Power consumption (printing) | 28.6 W |
| Print speed | 500 mm/sec | AC input voltage | 24 V |
| Printing characters | Text, Graphic, Barcode, 2D barcode | Power consumption | 28600 mA |
| Character sets | ANK | Power consumption (standby) | 1400 mA |
| Print technology * | Thermal | Power consumption (standby) | 1.4 W |
| Type * | POS printer | Operational conditions | |
| Paper handling | | Operating temperature (T-T) | 5 - 45 °C |
| Printing media thickness | 48 - 80 µm | Storage temperature (T-T) | -10 - 50 °C |
| Maximum roll diameter | 8.3 cm | Operating relative humidity (H-H) | 10 - 90% |
| Supported paper width | 80 mm | Storage relative humidity (H-H) | 10 - 90% |
| Media thickness | 48 - 80 mm | System requirements | |
| Ports & interfaces | | Pre-installed software | Server Direct Print, ePOS-Device, ePOS-Display, ePOS-Print |
| USB port * | ✓ | Weight & dimensions | |
| USB connector | USB Type-A / USB Type-B | Width | 145 mm |
| Connectivity technology * | Wired & Wireless | Depth | 195 mm |
| Near Field Communication (NFC) | ✓ | Height | 148 mm |
| Optional connectivity | Wireless LAN | Weight | 1.7 kg |
| Network | | Packaging data | |
| Ethernet LAN * | ✓ | Quantity per pack | 1 pc(s) |
| Features | | Package width | 195 mm |
| Sound pressure level (printing) | 52 dB | Package depth | 235 mm |
| Sound pressure level (standby) | 52 dB | Package height | 260 mm |
| Mean time between failures (MTBF) | 360000 h | Package weight | 2.7 kg |
| Autocutter durability | 3 million cuts | Print technology | |
| Paper save function | ✓ | Column capacity | 42/56 |
| Print head life | 200 km | | |

| Features | | Logistics data | |
|--------------------------|--|-------------------------------------|----------------|
| Country of origin | Philippines | Pallet weight (UK) | 0 g |
| Mounting position | Horizontal/Vertical | Harmonized System (HS) code | 84433210 |
| Wall mountable | ✓ | Products per pallet | 112 pc(s) |
| Built-in sensors details | Paper End Sensor, Paper Near End Sensor, Cover Open Sensor, Receipt paper sensor | Pallet gross weight | 0 g |
| Certification | CE | Products per pallet (UK) | 168 pc(s) |
| Design | | Technical details | |
| Product colour * | Black | Lifetime | 20000000 lines |
| | | Other features | |
| | | Buffer size | 4 KB |
| | | Mean cycles between failures (MCBF) | 70000000 |



8715946697208

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.