

Delock WLAN Antenna RP-SMA 802.11 ac/a/h/b/g/n 0 dBi 3 m ULA100 omnidirectional white outdoor

Description

This Delock WLAN antenna can be installed outdoors or indoors and take advantage of all two bands for WLAN.



Specification

- Connector: RP-SMA plug
- Frequency range:
 - 2400 - 2500 MHz
 - 5150 - 5875 MHz
- Antenna gain: 0 dBi
- Impedance: 50 Ohm
- Polarisation: linear vertical
- VSWR: 2.0 - 2.5
- Operating temperature: -10 °C ~ 50 °C
- Protection class: IP67
- Screw mounting 13 mm central hole
- Colour: white
- Dimension: (L x W x H): ca. 77 x 45 x 45 mm
- Cable category: coaxial
- Cable type: ULA100
- Cable attenuation:
 - 1.40 dB @ 2500 MHz per meter
 - 2.30 dB @ 5875 MHz per meter
- Cable diameter: 2,79 mm
- Cable length incl. connector: ca. 3 m

Item No. 89449

EAN: 4043619894499

Country of origin: Taiwan, Republic of China

Package: Poly bag


System requirements

- Device with RP-SMA jack

Package content

- WLAN antenna
- Screw nut

Images



General	
Mounting type:	Screw mounting with 13 mm bore hole
Protection category:	IP67
Suitable for indoor:	yes
Suitable for outdoor:	yes
Interface	
connector:	1 x RP-SMA plug
Technical characteristics	
Frequency range:	2.400 - 2.500 GHz 4.900 - 5.875 GHz
Gain:	0 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 50 °C
Polarisation:	linear vertical
VSWR:	2.0 - 2.5
Physical characteristics	
Cable category:	coaxial
Cable type:	ULA 100
Cable attenuation:	1.4 dB @ 2.500 GHz pro Meter 2.3 dB @ 5.875 GHz pro Meter
Cable colour:	white
Cable length:	3 m (incl. connectors)
Cable diameter:	2.79 mm
Diameter:	45 mm
Height:	77 mm
Colour:	white