

Epson EB-2250U data projector Standard throw projector 5000 ANSI lumens 3LCD WUXGA (1920x1200) White



Brand : Epson

Product code: V11H871040

Product name : EB-2250U

3LCD, 3800-5000 lum, 1920 x 1200, 16:10, USB 2.0 A, USB 2.0 B, RS-232C, 2x RJ-45, 3x VGA, 2x HDMI, 377 x 291 x 110 mm, 4800 g

Epson EB-2250U. Projector brightness: 5000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Lamp, Service life of light source: 5000 h, Service life of light source (economic mode): 10000 h. Focus: Manual, Focal length range: 23 - 38.4 mm, Aperture range (F-F): 1.5 - 2. Video processing: 10 bit, Colour modes (2D): Cinema, Dynamic, Video colour modes: Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM simulation mode. Serial interface type: RS-232C

Projector		Features	
Screen size compatibility *	1270 - 7620 mm (50 - 300")	Noise level (economic mode)	29 dB
Projection distance	1.5 - 9 m	Noise level *	39 dB
Projection distance (wide)	0 - 1.5 m	Country of origin	Philippines
Projection distance (tele)	0 - 9 m	Password protection	✓
Contrast ratio (dynamic)	15000:1	Multimedia	
Projector brightness *	5000 ANSI lumens	Built-in speaker(s) *	✓
Projection technology *	3LCD	RMS rated power	16 W
Projector native resolution *	WUXGA (1920x1200)	Design	
Contrast ratio (typical) *	15000:1	Product type *	Standard throw projector
Native aspect ratio *	16:10	Product colour *	White
Number of colours	1.07 billion colours	Placement	Ceiling, Desktop
Projector brightness (economic mode)	3800 ANSI lumens	Cable lock slot	✓
Vertical scan range	200 - 240 Hz	Cable lock slot type	Kensington
Keystone correction, horizontal	-20 - 20°	Display	
Keystone correction, vertical	-30 - 30°	Built-in display *	✗
Matrix size	1.93 cm (0.76")	Power	
Matrix type	3-panel (p-Si TFT active)	Power source *	AC
Light source		Power consumption (typical) *	405 W
Light source type *	Lamp	Power consumption (standby) *	0.5 W
Service life of light source *	5000 h	Power consumption (economy mode)	323 W
Service life of light source (economic mode)	10000 h	AC input voltage	220-240 V
Lamp power	300 W	AC input frequency	50 - 60 Hz
Lamps quantity	1 lamp(s)	Operational conditions	
Lens system		Operating temperature (T-T)	5 - 40 °C
Focus *	Manual	Storage temperature (T-T)	-10 - 60 °C
Focal length range	23 - 38.4 mm	Operating relative humidity (H-H)	20 - 80%
Aperture range (F-F)	1.5 - 2	Storage relative humidity (H-H)	10 - 90%
Zoom type	Manual	Weight & dimensions	
Zoom ratio	1.6:1	Width	377 mm
Digital zoom	1.6x	Depth	291 mm
Throw ratio	1.38 - 2.28:1	Height	110 mm
Video		Weight *	4.6 kg
Full HD *	✓	Package width	383 mm
3D *	✗	Package depth	530 mm
Video processing	10 bit	Package height	210 mm
Colour modes (2D)	Cinema, Dynamic	Package weight	6.4 kg
Video colour modes	Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM simulation mode		

Ports & interfaces		Packaging content	
USB 2.0 ports quantity	2	Remote control included *	✓
USB 2.0 Type-B ports quantity	1	Batteries included	✓
Serial interface type *	RS-232C	Cables included	AC, HDMI
PC Audio in	✓	Manual	✓
PC Audio out	✓	Bundled software	EasyMP Monitor, EasyMP Multi PC Projection
VGA (D-Sub) ports quantity *	3	Technical details	
HDMI ports quantity *	2	Sustainability certificates	TCO
Composite video in *	1	Logistics data	
Component video (YPbPr/YCbCr) in *	3	Quantity per pack	1 pc(s)
DVI port *	✗	Products per pallet	40 pc(s)
Mobile High-Definition Link (MHL)	✓	Pallet gross weight	0 g
AC (power) in	✓	Pallet gross length	120 cm
Network		Pallet gross width	80 cm
Ethernet LAN *	✓	Pallet gross height	3.5 m
Ethernet LAN (RJ-45) ports	1	Products per pallet layer	4 pc(s)
Ethernet LAN data rates	10,100,1000 Mbit/s	Products per pallet layer (UK)	5 pc(s)
Wi-Fi *	✗	Products per pallet (UK)	50 pc(s)
Storage		Pallet weight (UK)	0 g
Card reader integrated *	✗	Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
		Pallet height (UK)	3.5 m
		Harmonized System (HS) code	85286200
		Other features	
		RS-232 ports	1
		RS-232C	✓



8715946628646



4058154162460

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.