



ATEN SN3001P päätepalvelin RS-232

Tuotemerkki : ATEN

Tuotekoodi: SN3001P-AX

Tuotteen nimi : SN3001P

ATEN SN3001P. Kaapelitekniikka: 10/100Base-T(X). Virtalähteen malli: DC, PoE, Tehonkulutus (maks.): 1,22 W, Virrankulutus: 0,975 W. Tietoturva-algoritmit: 802.1x RADIUS, 2048-bit RSA, TLS. LED-merkkivalot: LAN, Teho, Tila. Paino: 210 g, Mitat (LxSxK): 117 x 98 x 26 mm, Pakkauksen leveys: 59 mm



Technical details		Weight & dimensions	
Serial ports quantity *	1	Dimensions (WxDxH)	117 x 98 x 26 mm
Serial interface type	RS-232	Package width	59 mm
Isolation	1.5 kV	Package length	23.9 cm
Ethernet LAN data rates	10,100 Mbit/s	Package height	160 mm
Networking standards	IEEE 802.3af	Package weight	440 g
Baud rate	921.6 Kbit/s	Operational conditions	
RS-232 signals	CTS, DCD, DSR, DTR, GND, RTS, RXD, TXD	Operating temperature (T-T)	0 - 60 °C
Data bits	5, 6, 7, 8	Storage temperature (T-T)	-40 - 75 °C
Flow Control type	DTR/DSR, RTS/CTS, XON/XOFF	Operating relative humidity (H-H)	5 - 95%
Parity bit	Even, Mark, No, Space	Storage relative humidity (H-H)	5 - 95%
Stop bits	1, 1.5, 2	Design	
Compliance certificates	RoHS	Product colour	Black
	EMC: EN 55032/35 EMI: CISPR 32, FCC Part 15B Class A EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV (Power Adapter), 1kV (Terminal Block); Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 10 MHz: 3 V/m; 10 kHz to 30 MHz: 3 to 1 V/m; 30 kHz to 80 MHz: 1 V/m IEC 61000-4-8 PFMF IEC 61000-4-11 DIPs	Housing material	Metal
		Reset button	✓
		Safety	UL 60950-1, UL 62368-1
Certification		Packaging content	
		DIN rail kit included	✓
		Terminal block included	✓
		Number of foot pads	4 pc(s)
		User guide	✓
Ports & interfaces		Logistics data	
Ethernet LAN (RJ-45) ports	1	Country of origin	Taiwan
Terminal block port	✓	Products per master (outer) case	10 pc(s)
Cabling technology	10/100Base-T(X)	Master (outer) case gross weight	4.97 kg
Power		Package volume	2265.35 cm ³
Power source type	DC, PoE	Master (outer) case volume	27467.34 cm ³
Power consumption (max)	1.22 W	Master (outer) case length	490 mm
Power consumption (typical)	0.975 W	Master (outer) case width	315 mm
Output voltage	9 - 48 V	Master (outer) case height	178 mm
		Master (outer) case net weight	3 kg
Security			
Security algorithms	802.1x RADIUS, 2048-bit RSA, TLS		

Indication

LED indicators LAN, Power, Status

Weight & dimensions

Weight 210 g



4710469341045

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date