



## ATEN SN3001 päättepalvelin RS-232

**Tuotemerkki :** ATEN

**Tuotekoodi:** SN3001-AX-G

**Tuotteen nimi :** SN3001

ATEN SN3001. Kaapelitekniikka: 10/100Base-T(X). Virtalähteen malli: DC, Tehonkulutus (maks.): 0,804 W, Virrankulutus: 0,634 W. Tietoturva-algoritmit: 802.1x RADIUS, 2048-bit RSA, TLS. LED-merkkivalot: Teho, Tila. Paino: 200 g, Mitat (LxSxK): 117 x 98 x 26 mm, Pakkauksen leveys: 59 mm



| Technical details             |   | Weight & dimensions               |                          |
|-------------------------------|---|-----------------------------------|--------------------------|
| Serial ports quantity *       | 1   | Weight                            | 200 g                    |
| Serial interface type         | RS-232  | Dimensions (WxDxH)                | 117 x 98 x 26 mm         |
| Isolation                     | 1.5 kV  | Package width                     | 59 mm                    |
| Ethernet LAN data rates       | 10,100 Mbit/s   | Package length                    | 23.9 cm                  |
| Baud rate                     | 921.6 Kbit/s  | Package height                    | 160 mm                   |
| RS-232 signals                | CTS, DCD, DSR, DTR, GND, RTS, TXD, Tx   | Package weight                    | 480 g                    |
| Data bits                     | 5, 6, 7, 8  | <b>Operational conditions</b>     |                          |
| Flow Control type             | DTR/DSR, RTS/CTS, XON/XOFF  | Operating temperature (T-T)       | 0 - 60 °C                |
| Parity bit                    | Even, Mark, No, Odd, Space  | Storage temperature (T-T)         | -40 - 75 °C              |
| Stop bits                     | 1, 1.5, 2   | Operating relative humidity (H-H) | 5 - 95%                  |
| Compliance certificates       | RoHS  | <b>Design</b>                     |                          |
| Certification                 | EMC: EN 55032/35 EMI: CISPR 32, FCC Part 15B Class A EMS: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV (Power Adapter), 1kV (Terminal Block); Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 10 MHz: 3 V/m; 10 kHz to 30 MHz: 3 to 1 V/m; 30 kHz to 80 MHz: 1 V/m IEC 61000-4-8 PFMF IEC 61000-4-11 DIPs | Product colour                    | Black                    |
|                               |   | Housing material                  | Metal                    |
|                               |   | Reset button                      | ✓                        |
|                               |   | Safety                            | UL 60950-1, UL 62368-1   |
| <b>Ports &amp; interfaces</b> |   | <b>Packaging content</b>          |                          |
| Ethernet LAN (RJ-45) ports    | 1   | DIN rail kit included             | ✓                        |
| Terminal block port           | ✓   | Terminal block included           | ✓                        |
| Cabling technology            | 10/100Base-T(X)   | Number of foot pads               | 4 pc(s)                  |
| <b>Power</b>                  |   | User guide                        | ✓                        |
| Power source type             | DC  | AC adapter included               | ✓                        |
| Power consumption (max)       | 0.804 W   | <b>Logistics data</b>             |                          |
| Power consumption (typical)   | 0.634 W   | Country of origin                 | Taiwan                   |
| Input voltage                 | 100 - 240 V   | Products per master (outer) case  | 10 pc(s)                 |
| Input frequency               | 50 - 60 Hz  | Master (outer) case gross weight  | 9.18 kg                  |
| Output voltage                | 9 - 48 V  | Package volume                    | 2265.35 cm <sup>3</sup>  |
|                               |   | Master (outer) case volume        | 27467.34 cm <sup>3</sup> |
|                               |   | Master (outer) case length        | 490 mm                   |
|                               |   | Master (outer) case width         | 315 mm                   |
|                               |   | Master (outer) case height        | 178 mm                   |
|                               |   | Master (outer) case net weight    | 4.1 kg                   |

**Security**

Security algorithms 802.1x RADIUS, 2048-bit RSA, TLS

**Indication**

LED indicators Power, Status



4710469341021

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date