



## TP-Link TL-SX1008 verkkokytkin Hallitsematon 10G Ethernet (100/1000/10000) 1U musta

**Tuotemerkki** : TP-Link

**Tuotekoodi**: TL-SX1008

**Tuotteen nimi** : TL-SX1008



TP-Link TL-SX1008. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. MAC-osoitetaulukko: 32000 entries, Kytkentäkapasiteetti: 160 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3bz, IEEE 802.3p, IEEE 802.3x. Telineasennus, Kotelo: 1U



|   |  |                                   |             |
|---|--|-----------------------------------|-------------|
| <b>Management features</b>                      |  | <b>Power</b>                      |             |
| Switch type *                                   | Unmanaged  | AC input voltage                  | 100 - 240 V |
| <b>Ports &amp; interfaces</b>                   |  | AC input frequency                | 50 - 60 Hz  |
| Basic switching RJ-45 Ethernet ports quantity * | 8  | Input current                     | 0.8 A       |
| Basic switching RJ-45 Ethernet ports type *     | 10G Ethernet (100/1000/10000)  | Power consumption (max)           | 28.4 W      |
| 10G Ethernet (copper) ports quantity            | 8  | <b>Power over Ethernet (PoE)</b>  |             |
| <b>Network</b>                                  |  | Power over Ethernet (PoE) *       | ✗           |
| Networking standards *                          | IEEE 802.3, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3bz, IEEE 802.3p, IEEE 802.3x | <b>Operational conditions</b>     |             |
| 10G support *                                   | ✓  | Operating temperature (T-T)       | 0 - 50 °C   |
| Auto MDI/MDI-X                                  | ✓  | Storage temperature (T-T)         | -40 - 70 °C |
| Auto-negotiation                                | ✓  | Operating relative humidity (H-H) | 10 - 90%    |
| <b>Data transmission</b>                        |  | Storage relative humidity (H-H)   | 5 - 90%     |
| Switching capacity *                            | 160 Gbit/s   | <b>Weight &amp; dimensions</b>    |             |
| Forwarding rate                                 | 119 Mpps   | Width                             | 294 mm      |
| MAC address table *                             | 32000 entries  | Depth                             | 180 mm      |
| Store-and-forward                               | ✓  | Height                            | 44 mm       |
| Jumbo frames support                            | ✓  | <b>Packaging content</b>          |             |
| Jumbo frames                                    | 10000  | Cables included                   | AC          |
| Packet buffer memory                            | 16 MB  | Quick start guide                 | ✓           |
| <b>Design</b>                                   |  | Rack mount kit                    | ✓           |
| Rack mounting *                                 | ✓  | <b>Packaging data</b>             |             |
| Form factor                                     | 1U   | Package type                      | Box         |
| Product colour                                  | Black  | Package width                     | 250 mm      |
|   |  | Package depth                     | 400 mm      |
|   |  | Package height                    | 80 mm       |
|   |  | Package weight                    | 2.07 kg     |

| Design                  |          | Certificates                |               |
|-------------------------|----------|-----------------------------|---------------|
| LED indicators          | ✓        | Certification               | CE, FCC ,RoHS |
| Number of fans          | 1 fan(s) | Logistics data              |               |
| Power                   |          | Harmonized System (HS) code | 85176990      |
| Power source *          | AC       |                             |               |
| Power supply included * | ✓        |                             |               |



6935364030926



6935364030919



0845973088064



845973088064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.