

## Lenovo 4XB7A17125 internal solid state drive 480 GB 2.5" Serial ATA III 3D TLC NAND

Brand: Lenovo Product code: 4XB7A17125

**Product name:** 4XB7A17125

ThinkSystem 2.5" S4620 480GB Mixed Use SATA 6Gb HS SSD


Lenovo 4XB7A17125 internal solid state drive 480 GB 2.5" Serial ATA III 3D TLC NAND:

By combining the latest Intel 3D NAND TLC Flash Memory technology with Intel's latest controller technology, the design of the S4620 SSDs delivers consistent performance, reduced power consumption, and end-to-end data protection, as well as being optimized for IOPS/watt and cost/IOPS.

Rigorous testing of S4620 SSDs by Lenovo through the ServerProven program assures a high degree of storage subsystem compatibility and reliability.

Lenovo 4XB7A17125. SSD capacity: 480 GB, SSD form factor: 2.5", Read speed: 550 MB/s, Write speed: 500 MB/s, Data transfer rate: 6 Gbit/s, Component for: Server/workstation

Features		Features	
Security algorithms SSD capacity * SSD form factor * Interface * Memory type * Component for * Hardware encryption * Data transfer rate Read speed Write speed Random read (4KB) Random write (4KB) Read latency Write latency S.M.A.R.T. support Hot-swap Mean time between failures (MTBF)	256-bit AES 480 GB 2.5"  Serial ATA III 3D TLC NAND  Server/workstation  ✓ 6 Gbit/s 550 MB/s 82000 IOPS 50000 IOPS 36 µs 36 µs ✓ ✓ 2000000 h	Certification	FCC Title 47, Part 15B, Class B EN-55035:2017 EN-55022:2006 EN-55032:2012 Low Voltage Directive (LVD) 2014/35/EU EMC Directive 2014/30/EU RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU UL 60950-1, 2nd Edition, 2014-10-14 CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-010 UL/CSA 62368-1, 2nd Edition AS/NZ CISPR 32:2015 AS/NZ CISPR 22:2009 +A1:2010 Taiwan BSMI EMC standard CNS 13438 Korea KCC Article 11.1 Morocco Decree # 2574-14 (EMC) Canada ICES-003 Japan VCCI China EFUP
		Power	
		Power consumption (write)	3 W
		Weight & dimensions	
		Width Depth Height Weight	70 mm 100 mm 7 mm 70 g
		Packaging data	3
		Package width Package depth Package height Package weight	174 mm 133 mm 63 mm 434 g
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Operating vibration Non-operating vibration Operating shock Non-operating shock Maximum operating altitude	0 - 70 °C 5 - 95% 2.17 G 3.13 G 1000 G 1000 G 3050 m
		Logistics data	
		Harmonized System (HS) code	84717070







889488589241

0889488589241

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.