

Lenovo 4XB7A17126 internal solid state drive 960 GB 2.5" Serial ATA III 3D TLC NAND

Brand : Lenovo

Product code: 4XB7A17126

Product name : 4XB7A17126

ThinkSystem 2.5" S4620 960GB Mixed Use SATA 6Gb HS SSD

Lenovo 4XB7A17126 internal solid state drive 960 GB 2.5" Serial ATA III 3D TLC NAND:

By combining the latest Intel 3D NAND TLC Flash Memory technology with Intel's latest controller technology, the design of the S4620 SSDs delivers consistent performance, reduced power consumption, and end-to-end data protection, as well as being optimized for IOPS/watt and cost/IOPS.

Rigorous testing of S4620 SSDs by Lenovo through the ServerProven program assures a high degree of storage subsystem compatibility and reliability.

Lenovo 4XB7A17126. SSD capacity: 960 GB, SSD form factor: 2.5", Read speed: 550 MB/s, Write speed: 510 MB/s, Data transfer rate: 6 Gbit/s, Component for: Server/workstation

Features Features Security algorithms 256-bit AES FCC Title 47, Part 15B, Class B EN-55035:2017 EN-55022:2006 960 GB SSD capacity * EN-55032:2012 Low Voltage SSD form factor * 2.5" Directive (LVD) 2014/35/EU EMC Interface * Serial ATA III Directive 2014/30/EU RoHS Directive 2011/65/EU WEEE 3D TLC NAND Memory type * Directive 2012/19/EU UL 60950-1, Component for * Server/workstation 2nd Edition, 2014-10-14 CSA C22.2 Certification No. 60950-1-07, 2nd Edition, Hardware encryption * 2014-010 UL/CSA 62368-1, 2nd Data transfer rate 6 Gbit/s Edition AS/NZ CISPR 32:2015 AS/NZ Read speed 550 MB/s CISPR 22:2009 +A1:2010 Taiwan 510 MB/s BSMI EMC standard CNS 13438 Write speed Korea KCC Article 11.1 Morocco 85000 IOPS Random read (4KB) Decree # 2574-14 (EMC) Canada Random write (4KB) 56000 IOPS ICES-003 Japan VCCI China EFUP Read latency 36 µs Power Write latency 36 µs S.M.A.R.T. support Hot-swap Mean time between failures (MTBF) 2000000 h

Power consumption (write)	3 W
Weight & dimensions	
Width Depth Height Weight	70 mm 100 mm 7 mm 70 g
Packaging data	
Package width Package depth Package height Package weight	174 mm 133 mm 63 mm 434 g
Operational conditions	
Operating temperature (T-T) Operating relative humidity (H-H) Operating vibration Non-operating vibration Operating shock Non-operating shock Maximum operating altitude	0 - 70 °C 5 - 95% 2.17 G 3.13 G 1000 G 1000 G 3050 m
Logistics data	
Harmonized System (HS) code	84717070







889488589258

0889488589258

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.