



ICY BOX IB-DK2241AC Langallinen USB 3.2 Gen 1 (3.1 Gen 1) Type-A musta

Tuotemerkki : ICY BOX

Tuotekoodi: 20850

Tuotteen nimi : IB-DK2241AC

ICY BOX IB-DK2241AC. Yhteysteknologia: Langallinen, Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Kuulokkeiden liitettävyys: 3,5 mm. Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s. Tuotteen väri: musta, Tiedonsiirtonopeus: 5 Gbit/s, HD-tyyppi: 2K. Virtalähteen malli: AC, AC-syöttöjännite: 100-240 V, Ulostulojännite: 5 V. Tuotteen leveys: 80 mm, Tuotteen syvyys: 30 mm, Tuotteen korkeus: 183 mm



Ports & interfaces		Power	
Connectivity technology *	Wired	Output current	4 A
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Power consumption (max)	20 W
USB 2.0 ports quantity *	4	Software	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Windows operating systems supported	✓
HDMI ports quantity *	1	Mac operating systems supported	✓
DVI-I ports quantity	1	Weight & dimensions	
Microphone in *	✓	Width	80 mm
Headphone outputs *	1	Depth	30 mm
Headphone connectivity	3.5 mm	Height	183 mm
Network		Weight	220 g
Ethernet LAN *	✓	Packaging data	
Ethernet LAN (RJ-45) ports	1	Quantity per pack	1 pc(s)
Ethernet LAN data rates	10,100,1000 Mbit/s	Package width	154 mm
Performance		Package depth	68 mm
Card reader integrated *	✗	Package height	204 mm
Data transfer rate	5 Gbit/s	Package weight	800 g
HD type	2K	Packaging content	
Maximum digital resolution	2048 x 1152 pixels	Cables included	USB
Number of displays supported	2	AC adapter included	✓
Hot-Plug support	✓	Manual	✓
Product colour *	Black	Logistics data	
LED indicators	✓	Products per master (outer) case	10 pc(s)
Plug and Play	✓	Master (outer) case width	215 mm
Charging function	✓		

Performance		Logistics data	
Housing material	Acrylonitrile butadiene styrene (ABS), Metal, Polycarbonate (PC)	Master (outer) case length	357 mm
Country of origin	China	Master (outer) case height	330 mm
Brand compatibility	Any brand	Master (outer) case gross weight	8.5 kg
		Harmonized System (HS) code	84733020
Power		Other features	
Power source type	AC	Number of microphone inputs	1
AC input voltage	100-240 V		
Output voltage	5 V		



4250078189800

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-DEC-2024. Prints or copies of Information are only valid on the printed Publication date