

USB4™ 20 Gbps Cable 2 m

Description

This USB4™ cable by Delock enables the connection of various devices, such as smart phones, monitors, external enclosures and docking stations, via a USB Type-C™ or Thunderbolt™ 3 port of a PC or laptop. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.

USB4™ 20 Gbps

The cable enables data transfer rates up to 20 Gbps when connecting USB4™-compatible devices. Of course, USB 3.2 or USB 2.0 devices can also be connected.

Connect DisplayPort monitors

The Delock cable supports DisplayPort 1.4a as well as DisplayPort 2.0 Alternate Mode, enabling the connection of DisplayPort monitors with a screen resolution up to 4K 60 Hz.

USB Power Delivery (USB PD 3.0) support up to 100 watt

Supports the USB Power Delivery 3.0 standard, which allows connected devices to be powered with up to 100 W (20 V / 5 A).



2 m

Specification

- Connectors:
 - 1 x USB4™ 20 Gbps (Gen 2x2) USB Type-C™ male >
 - 1 x USB4™ 20 Gbps (Gen 2x2) USB Type-C™ male
- USB-IF certified cable
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Chipset: Cypress E-Marker
- Cable gauge:
 - 30 + 31 AWG data line
 - 21 + 32 AWG power line
- Contacts gold-plated
- Cable diameter: ca. 5 mm
- Data transfer rate up to 20 Gbps
- Display resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Supports HDR10
- Supports HDCP 1.4 and 2.3
- Supports PCI Express 3.0 protocol (4 lanes)
- Supports DisplayPort 1.4a protocol
- Supports DisplayPort Alt Mode 2.0
- Dual channel, bi-directional data transfer
- USB Power Delivery (USB PD 3.0) support up to 100 watt (20 V / 5 A)
- Colour: black
- Length incl. connectors: ca. 2 m

System requirements

- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB4™ 20 Gbps cable

Item no. 86980

EAN: 4043619869800

Country of origin: China

Package: Retail Box

Images



General

Specification:	HDCP 1.4
	USB Type-C™
	DisplayPort 1.4
	HDR10
	PCI Express 3.0
	HDCP 2.3
	USB4
	USB Power Delivery 3.0

Interface

Connector 1:	1 x USB4 Gen 2x2 Type-C™ male
Connector 2:	1 x USB4 Gen 2x2 Type-C™ male

Technical characteristics

Chipset:	Cypress E-Marker
Data transfer rate:	20 Gbps
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Maximum load:	100 W
Maximum current:	5 A
Data transmission:	Bi-directional
Voltage:	20 V

Physical characteristics

Cable diameter:	5 mm
Conductor gauge:	30 AWG data line
	31 AWG data line
	21 AWG power line
	32 AWG power line
Length:	2 m
Colour:	black