

DELL UltraSharp 27 4K USB-C Hub Monitor - U2723QE

Brand : DELL Product family: UltraSharp Product code: DELL-U2723QE

Product name : Dell UltraSharp 27 4K USB-C Hub Monitor -

U2723QE

- 68.6cm (27") 4K Ultra HD 3840 x 2160 LED IPS
- 8ms, 16:9, 400cd/m², 2000:1
- USB, HDMI, DisplayPort

68.6cm (27") 4K Ultra HD 3840 x 2160 LED IPS, 16:9, 400cd/m², 1.07B, 8ms, 178°/178°, 2000:1

DELL UltraSharp 27 4K USB-C Hub Monitor - U2723QE:

Be your most productive on a 27 inch monitor with brilliant color and contrast that features the industry's first IPS Black technology and a connectivity hub.

DELL UltraSharp 27 4K USB-C Hub Monitor - U2723QE. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Silver





| Display | | Ergonomics | |
|------------------------------------|-----------------------------------|--|--------------------|
| Display diagonal * | 68.6 cm (27") | Plug and Play | ✓ |
| Display resolution * HD type * | 3840 x 2160 pixels 4K Ultra HD | Power | |
| Native aspect ratio * | 16:9 | Energy efficiency class (SDR) * | F |
| Display technology * | LCD | Energy efficiency class (HDR) * | G |
| Panel type * | IPS | Energy consumption (SDR) per 1000 hours * | 26 kWh |
| Backlight type | LED | Energy consumption (HDR) per | 38 kWh |
| Touchscreen * | × | 1000 hours * | 38 KWII |
| Display brightness (typical) | 400 cd/m ² | Power consumption (typical) * | 25.9 W |
| Response time * | 8 ms | Power consumption (standby) * | 0.3 W |
| Anti-glare screen | ✓ | Power consumption (max) | 220 W |
| Screen shape * | Flat | Power consumption (off) | 0.2 W |
| Supported video modes | 480p, 576p, 720p, 1080i, 1080p | AC input voltage | 100 - 240 V |
| Contrast ratio (typical) * | 2000:1 | AC input frequency | 50 - 60 Hz |
| Maximum refresh rate * | 60 Hz | Input current | 2.7 A |
| Viewing angle, horizontal | 178° | Power supply type | Internal |
| Viewing angle, vertical | 178° | Energy efficiency scale | A to G |
| Display number of colours * | 1.07 billion colours | European Product Registry for Energy Labelling (EPREL) code | 955176 |
| Response time (fast) | 5 ms | 5, | |
| Pixel pitch | 0.1554 x 0.1554 mm | Operational conditions | |
| Pixel density | 163.18 ppi | Operating temperature (T-T) | 0 - 40 °C |
| Horizontal scan range | 15 - 140 kHz | Storage temperature (T-T) | -20 - 60 °C |
| Vertical scan range | 23 - 86 Hz | Operating relative humidity (H-H) | 10 - 80% |
| Viewable size, horizontal | 59.7 cm | Storage relative humidity (H-H) | 5 - 90% |
| Viewable size, vertical | 33.6 cm | Operating altitude | 0 - 5000 m |
| Display diagonal (metric) | 68.47 cm | Non-operating altitude | 0 - 12192 m |
| High Dynamic Range (HDR) supported | ✓ | Weight & dimensions | |
| | | \A/: - L - /:L L \ | 611.4 mm |
| DDC/CI | ✓ | Width (with stand) | |
| DDC/CI Surface hardness | √ 3H | Depth (with stand) Height (with stand) | 185 mm 385.2 mm |

| Display | | Weight & dimensions | |
|---|-----------------------|---|--|
| sRGB coverage (typical) | 100% | Weight (with stand) | 6.27 kg |
| DCI-P3 coverage | 98% | Width (without stand) | 611.4 mm |
| Heat dissipation (typical) | 98.27 BTU/h | Depth (without stand) | 54.3 mm |
| Performance | | Height (without stand) Weight (without stand) | 353 mm 4.48 kg |
| NVIDIA G-SYNC * | × | Bezel width (side) | 7.35 mm |
| AMD FreeSync * | × | Bezel width (top) | 7.35 mm |
| Flicker-free technology | ✓ | Bezel width (bottom) | 1 cm |
| Low Blue Light technology | ✓ | Stand weight | 1.79 kg |
| Multimedia | | Packaging data | |
| Built-in speaker(s) * | × | Package weight | 9.53 kg |
| Built-in camera * | × | Packaging content | |
| Design | | Stand included | 1 |
| Market positioning * | Office | Cables included | AC, DisplayPort, USB Type-C to USB Type-A, USB Type-C to USB Type-C |
| Product colour * Front bezel colour | Silver Black | Quick start guide | ✓ |
| Feet colour | Silver | Sustainability | |
| Ports & interfaces | | Sustainability certificates | ENERGY STAR, EPEAT Gold, TCO |
| Built-in USB hub * | ✓ | Doesn't contain | Arsenic, PVC/BFR |
| USB hub version | 3.2 Gen 2 (3.1 Gen 2) | Carbon footprint | |
| USB upstream port type | USB Type-C | Total carbon footprint (kg of CO2e) | 815 |
| Number of upstream ports Number of USB Type-C upstream | 2 | Total carbon emissions, standard deviation (kg of CO2e) | 203 |
| ports quantity | 1 | Carbon emissions, manufacturing (kg of CO2e) | 411 |
| USB Type-A downstream ports quantity | 5 | Carbon emissions, logistics (kg of | 85 |
| USB Power Delivery (USB PD) | ✓ | CO2e) Carbon emissions, energy usage (kg | |
| USB Power Delivery up to | 90 W | of CO2e) | 313 |
| HDMI * | ✓ | Carbon emissions, end-of-life (kg of | 5 |
| HDMI ports quantity | 1 | CO2e) | |
| HDMI version | 2.0 | Total carbon emissions, w/o use phase (kg of CO2e) | 502 |
| DisplayPorts quantity Audio output | 2 | PAIA version | 1.3.0 |
| · | | Other features | |
| Headphone out * Headphone outputs | 1 | Picture-by-Picture (PbP) | ✓ |
| Headphone connectivity | 3.5 mm | Maximum resolution | 3840 x 2160 pixels |
| HDCP | √ | RJ-45 ports quantity | 1 |
| | | Heavy metals free | Hg (mercury) |
| Network | | Compliance certificates | RoHS |
| Wi-Fi | X | Power management | ✓ |
| Ergonomics | | | ENERGY STAR certified Monitor. |
| VESA mounting * | ✓ | | EPEAT registered where applicable. TCO Certified & TCO Certified Edge. |
| Panel mounting interface | 100 x 100 mm | Compliance industry standards | RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage |
| Cable lock slot * | ✓ | | current requirements. Arsenic-Free |
| Height adjustment * | ✓ | | glass and Mercury-Free for the panel only. |
| Height adjustment | 15 cm | Logistics data | pana onji |
| Pivot | √ | Logistics data | 05205210 |
| Pivot angle | -90 - 90° | Harmonized System (HS) code | 85285210 |
| Swivelling Swivellangle range | √ .45 .45° | | |
| Swivel angle range | -45 - 45° ✓ | | |
| Tilt adjustment Tilt angle range | -5 - 21° | | |
| On Screen Display (OSD) | -5 - 21° | | |
| on selecti Display (OSD) | • | | |





5397184567753

5704174841043



5704174841036

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.