ZYXEL

Zyxel GS-1900-24 v2 Hallittu L2 Gigabit Ethernet (10/100/1000) 1U musta

Tuotemerkki : Zyxel Tuotekoodi: GS1900-24-EU0102F

Tuotteen nimi: GS-1900-24 v2







| Management features | | Design | |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------|
| Switch type * | Managed | Stackable * | ✓ |
| Switch layer | L2 | Form factor | 10 |
| Quality of Service (QoS) support | ✓ | Product colour | Black |
| Web-based management | ✓ | Reset button | ✓ |
| System event log | ✓ | LED indicators | ✓ |
| MIB support | RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493 | Performance | |
| | | Mean time between failures (MTBF) | 432.673 h |
| Ports & interfaces | | Power | |
| Basic switching RJ-45 Ethernet ports | 24 | Power source * | AC |
| quantity * | | Power supply included * | ✓ |
| Basic switching RJ-45 Ethernet ports type * | Gigabit Ethernet (10/100/1000) | AC input voltage | 100 - 240 V |
| SFP module slots quantity | 2 | AC input frequency | 50 - 60 Hz |
| Power connector | AC-in jack | Power consumption (max) | 16 W |
| Network | | Power over Ethernet (PoE) | |
| Networking standards * | IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Power over Ethernet (PoE) * | × |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 50 °C |
| | | Storage temperature (T-T) | -40 - 70 °C |
| 10G support * | X | Operating relative humidity (H-H) | 10 - 95% |
| Port mirroring | 1 | Storage relative humidity (H-H) | 10 - 95% |
| Full duplex | 1 | Heat dissipation | 55 BTU/h |
| Flow control support | 1 | Weight & dimensions | |
| Link aggregation | ✓ | Width | 440 mm |
| Spanning tree protocol | ✓ | Depth | 131 mm |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Height | 44 mm |
| | | Weight | 2.09 kg |

| Network | | Packaging content | |
|----------------------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MAC address auto-learning supported | ✓ ✓ Tagged VLAN, VLAN Identifier (VLAN ID), Voice VLAN | Cables included Rack mount kit | AC ✓ |
| VLAN support | | Packaging data | |
| Virtual LAN features | | Package type | Box |
| Data transmission | | Package width | 561 mm |
| Switching capacity * Forwarding rate MAC address table * | arding rate 39 Mpps address table * 8000 entries -and-forward | Package depth Package height Package weight | 217 mm 82 mm 2.85 kg |
| Store-and-forward | | Certificates | |
| Jumbo frames support Jumbo frames Packet buffer memory Security DHCP features IGMP snooping | | Certification | EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant |
| Security algorithms | | Logistics data | |
| MAC address filtering Static port security SSH/SSL support Password protection Authentication type | ✓ ✓ ✓ RADIUS, TACACS+ | Harmonized System (HS) code | 85176990 |
| Design | | | |
| Rack mounting * | ✓ | | |



4718937621231

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.