



Canon MAXIFY GX7050 MegaTank Inkjet A4 600 x 1200 DPI Wi-Fi

Brand : Canon

Product family: MAXIFY

Product code: 4471C006

Product name : GX7050
MegaTank

A4, 600 x 1200 dpi, CIS, 2.7" LCD, USB, Wi-Fi, LAN, 49 dB, 13 kg

[Canon MAXIFY GX7050 MegaTank Inkjet A4 600 x 1200 DPI Wi-Fi:](#)

Experience highly productive business printing with MegaTank using high yield, refillable ink tanks. Count on business quality prints and an extremely low total cost of ownership. Canon MAXIFY GX7050 MegaTank. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 600 x 1200 DPI. Copying: Colour copying. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Faxing: Colour faxing. Duplex functions: Copy, Print, Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black, White



Printing		Paper handling	
Print technology *	Inkjet	Paper tray media types *	Banner, Envelopes, Glossy paper, High resolution paper, Matte paper, Photo paper, Plain paper, Semi-glossy paper
Printing *	Colour printing	ISO A-series sizes (A0...A9) *	A4, A5, A6
Duplex printing *	✓	ISO B-series sizes (B0...B9)	B5
Maximum resolution *	600 x 1200 DPI	Envelopes sizes	Com-10, DL
Print speed (ISO/IEC 24734) black	24 ppm	Photo paper sizes	10x15,20x25 cm
Print speed (ISO/IEC 24734) colour	15.5 ppm	Borderless printing media sizes	13x13
Copying		Custom media width	89 - 216 mm
Duplex copying *	✓	Custom media length	127 - 1200 mm
Copying *	Colour copying	Paper tray media weight	64 - 105 g/m ²
Copy speed (colour, normal quality, A4)	12.7 cpm	Multi-Purpose Tray media weight	64 - 105 g/m ²
Copy speed (black, draft, A4)	22.2 cpm	Ports & interfaces	
Copy speed (colour, draft, A4)	12.2 cpm	Direct printing *	✓
Maximum number of copies	99 copies	USB port	✓
Copier resize	25 - 400%	USB connector	USB Type-B
N-in-1 copy function	✓	Optional connectivity	Ethernet, Wireless LAN
N-in-1 copy function (N=)	2, 4	Network	
ID-card copy function	✓	Wi-Fi *	✓
Edge erase function	✓	Ethernet LAN *	✓
Scanning		Ethernet LAN data rates	10,100 Mbit/s
Duplex scanning *	✓	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Scanning *	Colour scanning	Security algorithms	WEP, WPA-PSK, WPA2-PSK
Optical scanning resolution *	1200 x 1200 DPI	Mobile printing technologies	Apple AirPrint, Canon Easy-PhotoPrint, Mopria Print Service, PIXMA Cloud Link
Scanner type *	Flatbed & ADF scanner		
Scan technology	CIS		
Scan to	E-mail, Network folder, USB		
Input colour depth	16 bit		

Scanning		Performance	
Output colour depth	8 bit	Sound pressure level (printing)	49 dB
Input greyscale depth	16 bit	Design	
Output greyscale depth	8 bit	Product colour *	Black, White
Fax		Market positioning *	Home & office
Faxing *	Colour faxing	Built-in display *	✓
Fax resolution (black)	300 x 300 DPI	Display	LCD
Fax resolution (colour)	200 x 200 DPI	Display diagonal	6.86 cm (2.7")
Fax transmission speed	3 sec/page	Control type	Touch
Modem speed	33.6 Kbit/s	Colour display	✓
Fax memory	250 pages	Power	
Speed dialling	✓	Power consumption (copying)	23 W
Features		Power consumption (standby)	1.6 W
Maximum duty cycle *	45000 pages per month	Power consumption (off)	0.2 W
Duplex functions *	Copy, Print, Scan	Energy Star Typical Electricity Consumption (TEC)	0.15 kWh/week
Ink tank system	✓	AC input voltage	100 - 240 V
Number of print cartridges *	4	AC input frequency	50 - 60 Hz
Printing colours *	Black, Cyan, Magenta, Yellow	System requirements	
Replacement cartridges	GI-56 BK GI-56 C GI-56 M GI-56 Y	Windows operating systems supported	Windows 10, Windows 7, Windows 8.1
Input & output capacity		Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Total number of input trays *	3	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Total input capacity *	600 sheets	Other operating systems supported	Android, iOS
Paper tray 1 input capacity	100 sheets	Operational conditions	
Paper tray 2 input capacity	250 sheets	Operating relative humidity (H-H)	10 - 90%
Multi-Purpose tray	✓	Operating temperature (T-T)	5 - 35 °C
Multi-Purpose tray input capacity	250 sheets	Weight & dimensions	
Auto document feeder (ADF)	✓	Width	399 mm
Auto document feeder (ADF) input capacity	50 sheets	Depth	410 mm
Paper handling		Height	314 mm
Maximum ISO A-series paper size *	A4	Weight	13 kg
		Logistics data	
		Harmonized System (HS) code	84433100



4549292173611

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.