


ASUS PRIME H610M-D D4 Intel H610 LGA 1700 mikro ATX

Tuotemerkki : ASUS

Tuotekoodi: 90MB1A00-M0EAY0

Tuotteen nimi : PRIME H610M-D D4

ASUS PRIME H610M-D D4. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA, Tuetut tallennusasematyypit: HDD & SSD. Ethernet-liitännän tyyppi: Gigabitti Ethernet. Komponentti (tuotteelle): PC, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Processor socket *	LGA 1700	Ethernet LAN (RJ-45) ports *	1
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium®, Intel® Pentium® Gold	PS/2 ports quantity	1
Maximum number of SMP processors	1	VGA (D-Sub) ports quantity *	1
Memory	DDR4-SDRAM	HDMI ports quantity *	1
		HDMI version	2.1
		Headphone outputs	1
		Microphone in	✓
		Network	
		Ethernet LAN	✓
		Ethernet interface type	Gigabit Ethernet
Storage controllers	HDD & SSD	Wi-Fi *	✗
		Features	
		Motherboard chipset *	Intel H610
		Audio output channels *	7.1 channels
Graphics	2	Component for *	PC
		Motherboard form factor *	micro ATX
Internal I/O	1	Motherboard chipset family *	Intel
		Windows operating systems supported	Windows 10 x64, Windows 11 x64
USB 2.0 connectors *	1	Expansion slots	
		PCI Express x16 (Gen 3.x) slots	1
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	PCI Express x16 (Gen 4.x) slots	1
		Number of M.2 (M) slots	1
Number of SATA III connectors *	4	BIOS	
		BIOS type *	UEFI AMI
S/PDIF out connector	✓		

Internal I/O		BIOS	
Front panel audio connector	✓	BIOS memory size	128 Mbit
ATX Power connector (24-pin)	✓	Logistics data	
CPU fan connector	✓	Harmonized System (HS) code	84733020
Number of chassis fan connectors	1	Weight & dimensions	
EPS power connector (8-pin)	✓	Width	234 mm
Number of COM connectors	1	Depth	203 mm
TPM connector	✓	Height	51 mm
12V power connector	✓	Packaging content	
RGB LED pin header	✓	Cables included	SATA
Rear panel I/O ports		Drivers included	✓
USB 2.0 ports quantity *	4	Other features	
		Weight	842 g



4711081540489

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-MAR-2025. Prints or copies of Information are only valid on the printed Publication date