

## BenQ LU960 data projector Standard throw projector 5500 ANSI lumens DLP WUXGA (1920x1200) 3D Black

Brand : BenQ Product code: 9H.JN477.25E

**Product name:** LU960

- Dustproofing technology for long-lasting performance
- Support lens shift with Lens Lock
- < 16.67 ms low latency enables realistic simulation
- White balance calibration for seamless blending
- Support 360° and portrait installation

DLP, WUXGA,  $1920 \times 1200$ , 5500 ANSI, 10W, HDMI, USB, RS232, RJ45,  $479.6 \times 182.8 \times 402$  mm, 12 kg BenQ LU960. Projector brightness: 5500 ANSI lumens, Projection technology: DLP, Projector native resolution: WUXGA ( $1920 \times 1200$ ). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 38000 h. Zoom ratio: 1.1:1, Throw ratio: 1.127 - 1.697. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions:  $640 \times 512$ ,  $640 \times 640$ ,  $640 \times 160$ ,  $640 \times 352$ ,  $640 \times 360$ ,  $640 \times 400$ ,  $640 \times 480$  (VGA),  $640 \times 544$ , 640..., Supported video modes: 480, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232





Projector		Network	
Screen size compatibility * Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Horizontal scan range Vertical scan range Keystone correction, horizontal Keystone correction, vertical	762 - 7620 mm (30 - 300") 5500 ANSI lumens DLP WUXGA (1920x1200) 3000000:1 16:9 1.07 billion colours 15 - 135 kHz 23 - 120 Hz -40 - 40° -30 - 30°	Ethernet LAN (RJ-45) ports	1
		Features	
		Noise level (economic mode)	35 dB
		On Screen Display (OSD)	✓
		On Screen Display (OSD) languages	Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish
Light source		Number of OSD languages	28
Light source type * Service life of light source * Service life of light source (economic mode)	Laser 20000 h 38000 h	Noise level *	37 dB
		Multimedia	
		Built-in speaker(s) *	✓
Lens system		RMS rated power	10 W
Zoom capability	✓	Design	
Zoom ratio	1.1:1	Market positioning *	Business
Throw ratio	1.127 - 1.697	Product type *	Standard throw projector
Offset	0%	Product colour *	Black
Video		Cable lock slot	√ Vancinatan
Analog signal format system *	NTSC, PAL, SECAM	Cable lock slot type	Kensington
Full HD * ✓	✓	Power	
3D*	<b>✓</b>	Power source *	AC
		Power consumption (typical) *	450 W
		Power consumption (standby) * Power consumption (max)	0.5 W 500 W
		rower consumption (max)	JUU W

Video		Power	
	640 x 512, 640 x 640, 640 x 160, 640 x 352, 640 x 360, 640 x 400,	Power consumption (economy mode)	350 W
	640 x 480 (VGA), 640 x 544, 640 x 576, 640 x 960, 704 x 480, 704 x	AC input voltage	100 - 240 V
	576, 720 x 350, 720 x 400, 720 x 480, 720 x 480, 720 x 576, 720 x 720, 752 x 582, 768 x 432, 768 x 448, 800 x 450, 800 x 480 (WVGA), 800 x 500, 800 x 592, 800 x 600 (SVGA), 832 x 624, 832 x 642, 848 x 480, 854 x 480 (WVGA), 900 x 720, 960 x 960, 960 x 480, 960 x 576, 960 x 720, 1024 x 576 (WSVGA), 1024 x 600, 1024 x 640, 1024 x 768 (XGA), 1024 x 800, 1032 x 452, 1056 x 144, 1080 x 1080, 1152 x 864 (XGA+), 1152 x 870, 1200 x 1600, 1200 x 1920, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 768, 1280 x 800 (WXGA), 1280 x 800, 1280 x 960, 1280 x 1280, 1280 x 800, 1280 x 6480, 1366 x 768, 1360 x 1050, 1440 x 1050, 1440 x	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
		Width	479.6 mm
		Depth	402 mm
		Height	182.8 mm
		Weight *	12 kg
		Packaging content	
		Remote control included *	✓
		Batteries included	✓
		Cables included	AC
		Packaging content	Installation Guide Safety Guide Remote Control (RCA024) AA Batteryx2 Power Cord Warranty
		Other features	card (by Region)
		Other features Security updates end date	31/12/2024
Supported graphics resolutions		Security appeares end date	31/12/2024
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Ports & interfaces	_		
USB 2.0 ports quantity	1		
Mini-USB 2.0 ports quantity Audio (L/R) in *	1		
Audio (L/R) in Audio (L/R) out	1		
Serial interface type *	RS-232		
PC in (D-Sub)	<b>✓</b>		
HDMI ports quantity *	2		
Network			
Ethernet LAN *	✓		

Power

Video



4718755084010

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.