



## ATEN VP3520 Mediaesitysten matriisikytkin 46,7 W

**Tuotemerkki :** ATEN

**Tuotekoodi:** VP3520-AT-G

**Tuotteen nimi :** VP3520



ATEN VP3520. Tuotetyyppi: Mediaesitysten matriisikytkin, Suurin resoluutio ( HDMI ): 4096 x 2160 pikseliä, Tuetut resoluutiot: 4096 x 2160, 3840 x 2160, 1920 x 1080, 1920 x 1200, 1680 x 1050, 1600 x 1200, 1440 x 900, 1400 x.... Kotelon väri: musta, Kotelon materiaali: Metall, Ohjaustyyppi: Painikkeet. Tehonkulutus (maks.): 46,7 W, Virrankulutus: 45,8 W, AC-syöttöjännite: 110 - 220 V. Alkuperämaa: Taiwan, Tuotepakkauksen paino: 5,46 kg, Tuotepakkauksen pituus: 325 mm. Tuotteen leveys: 272,3 mm, Tuotteen syvyys: 432,4 mm, Tuotteen korkeus: 44 mm

Features		Power	
Product type *	Media presentation matrix switcher	AC input voltage	110 - 220 V
Maximum resolution (HDMI)	4096 x 2160 pixels	<b>Operational conditions</b>	
HDCP	✓	Operating temperature (T-T)	0 - 40 °C
HDCP version	2.2	Storage temperature (T-T)	-20 - 60 °C
High Dynamic Range (HDR) supported	✓	Operating relative humidity (H-H)	0 - 80%
Extended display identification data (EDID)	✓	Heat dissipation	310 BTU/h
	4096 x 2160, 3840 x 2160, 1920 x 1080, 1920 x 1200, 1680 x 1050, 1600 x 1200, 1440 x 900, 1400 x 1050, 1280 x 1024, 1280 x 800, 1024 x 768, 800 x 600, 720 x 400, 640 x 480	Heat dissipation (max)	314 BTU/h
Supported resolutions		<b>Logistics data</b>	
<b>Design</b>		Country of origin	Taiwan
Housing colour	Black	Master (outer) case gross weight	5.46 kg
Housing material	Metal	Master (outer) case length	325 mm
Rack mounting	✓	Master (outer) case width	250 mm
Control type	Buttons	Master (outer) case height	175 mm
Remote control included	✓	Master (outer) case net weight	4.18 kg
Rubber feet	✓	Harmonized System (HS) code	85299097
<b>Display</b>		<b>Technical details</b>	
Built-in display *	✗	Package volume	21520.8 cm <sup>3</sup>
<b>Ports &amp; interfaces</b>		<b>Weight &amp; dimensions</b>	
HDMI input ports quantity	3	Width	272.3 mm
HDMI output ports quantity	1	Depth	432.4 mm
RJ-45 input ports	2	Height	44 mm
RJ-45 output ports	1	Weight	3.8 kg
RS-232 ports	2	Package width	133 mm
Analog audio output terminal ports	1	Package depth	499 mm
Relay outputs	2	Package height	324 mm
<b>Power</b>		Package weight	5.46 kg
Power consumption (max) *	46.7 W	<b>Packaging content</b>	
Power consumption (typical)	45.8 W	Cables included	AC
		Rack mount kit	✓
		Manual	✓
		IR receiver included	✓



4710469341229

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date