

DELL P Series 27 USB-C Hub Monitor - P2723DE

Brand : DELL

Product family: P Series

```
Product code: DELL-P2723DE
```

Product name : Dell 27 USB-C Hub Monitor - P2723DE

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
- 5ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort
68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 16.7M, 5ms, 178°/178°, 1000:1

DELL P Series 27 USB-C Hub Monitor - P2723DE:


Experience pure productivity on a 27-inch QHD monitor featuring extensive connectivity and ComfortView Plus.

DELL P Series 27 USB-C Hub Monitor - P2723DE. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black




Display		Ergonomics	
Display diagonal * Display resolution * HD type *	resolution * 2560 x 1440 pixels	Swivel angle range Tilt adjustment Tilt angle range	-45 - 45° ✓ -5 - 21°
Native aspect ratio *16:9Display technology *LCD	LCD	On Screen Display (OSD) Plug and Play	✓
Panel type * Backlight type	IPS LED	Power	
Touchscreen * Display brightness (typical) Response time *	5 ms Image: Second se	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000	F Not available 26 kWh
Anti-glare screen Screen shape *		hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type	26 W 0.3 W 175 W 0.3 W 100 - 240 V 50 - 60 Hz 2 A Internal
Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours *			
Response time (fast) Pixel pitch Pixel density		Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	A to G 1057602
Horizontal scan range	29 - 113 kHz	Operational conditions	
Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric)	49 - 75 Hz 59.7 cm 33.6 cm 68.5 cm 68.47 cm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 20 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m

Display		Weight & dimensions	
High Dynamic Range (HDR)	×	Width (with stand)	611.6 mm
supported		Depth (with stand)	190.1 mm
Colour gamut standard Colour gamut	sRGB 99%	Height (with stand)	535.2 mm
	5570	Weight (with stand)	6.55 kg
Performance		Width (without stand)	611.6 mm
NVIDIA G-SYNC *	×	Depth (without stand)	52.2 mm 360.8 mm
AMD FreeSync *	×	Height (without stand) Weight (without stand)	5.07 kg
Low Blue Light technology	 Image: A set of the set of the	Bezel width (side)	7.43 mm
Multimedia		Bezel width (top)	7.37 mm
Built-in speaker(s) *	×	Bezel width (bottom)	1.78 cm
Built-in camera *	×	Packaging data	
		Package weight	9.78 kg
Design	Dusiness	Packaging content	-
Market positioning * Product colour *	Business Black	Stand included	1
Front bezel colour	Black	Stand Included	
Detachable stand	✓	Cables included	AC, DisplayPort, USB Type-C to USB Type-A
Feet colour	Silver	Quick start guide	✓
Ports & interfaces		Carbon footprint	
Built-in USB hub *	J	Total carbon footprint (kg of CO2e)	642
USB upstream port type	USB Type-C	Total carbon emissions, standard deviation (kg of CO2e)	151
Number of USB Type-C upstream ports quantity	1	Carbon emissions, manufacturing (kg of CO2e)	333
USB Type-A downstream ports quantity	5	Carbon emissions, logistics (kg of CO2e)	86
USB Power Delivery up to	90 W	Carbon emissions, energy usage (kg	
HDMI *	1	of CO2e)	217
HDMI ports quantity	1	Carbon emissions, end-of-life (kg of	5
HDMI version	1.4	CO2e) Total carbon emissions, w/o use	
DisplayPorts quantity	2 1.4	phase (kg of CO2e)	425
DisplayPort version Headphone out *		PAIA version	1.3.0
Charging port type	× USB Type-C	Other features	
	USB Type-C	Heavy metals free	Hg (mercury)
Network		Ethernet LAN (RJ-45) ports	1
Wi-Fi	×	Logistics data	
Ergonomics		Harmonized System (HS) code	85285210
VESA mounting *	1	- · · · ·	
Panel mounting interface	100 x 100 mm		
Cable lock slot *	1		
Height adjustment *	1		
Height adjustment	15 cm		
Pivot	1		
Pivot angle	90 - 90°		
Swivelling	1		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date