DELL

DELL P Series 27 4K USB-C Hub Monitor - P2723QE

Brand : DELL   **Product family:** P Series   **Product code:** DELL-P2723QE

Product name : Dell 27 4K
USB-C Hub Monitor - P2723QE

- 68.6cm (27") 4K Ultra HD 3840 x 2160 LED IPS
- 5ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort
68.6cm (27") 4K Ultra HD 3840 x 2160 LED IPS, 16:9, 350cd/m², 1.073B, 5ms, 178°/178°, 1000:1

**DELL P Series 27 4K USB-C Hub Monitor - P2723QE:**

Experience pure productivity on a 27-inch 4K monitor with extensive connectivity and ComfortView Plus.
DELL P Series 27 4K USB-C Hub Monitor - P2723QE. Display diagonal: 68.6 cm (27"), Display resolution:
3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 5 ms, Native aspect
ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub
version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display			**Ergonomics**	
Display diagonal *	68.6 cm (27")		On Screen Display (OSD)	✔
Display resolution *	3840 x 2160 pixels		Plug and Play	✔
HD type *	4K Ultra HD		LED indicators	✔
Native aspect ratio *	16:9		**Power**	
Display technology *	LCD		Energy efficiency class (SDR) *	F
Panel type *	IPS		Energy efficiency class (HDR) *	Not available
Backlight type	LED		Energy consumption (SDR) per 1000 hours *	26 kWh
Touchscreen *	✘		Power consumption (typical) *	26 W
Display brightness (typical)	350 cd/m²		Power consumption (standby) *	0.2 W
Response time *	5 ms		Power consumption (max)	169 W
Anti-glare screen	✔		Power consumption (off)	0.2 W
Screen shape *	Flat		AC input voltage	100 - 240 V
Supported video modes	480p, 576p, 720p, 2160p		AC input frequency	50 - 60 Hz
Contrast ratio (typical) *	1000:1		Input current	2.5 A
Maximum refresh rate *	60 Hz		Power supply type	Internal
Viewing angle, horizontal	178°		Energy efficiency scale	A to G
Viewing angle, vertical	178°		European Product Registry for Energy Labelling (EPREL) code	1054915
Display number of colours *	1.073 billion colours		**Operational conditions**	
Response time (fast)	8 ms		Operating temperature (T-T)	0 - 40 °C
Pixel pitch	0.1554 x 0.1554 mm		Storage temperature (T-T)	-20 - 60 °C
Pixel density	163 ppi		Operating relative humidity (H-H)	10 - 80%
Horizontal scan range	15 - 135 kHz		Storage relative humidity (H-H)	5 - 90%
Vertical scan range	24 - 86 Hz		Operating altitude	0 - 5000 m
Viewable size, horizontal	59.7 cm		Non-operating altitude	5000 - 12192 m
Viewable size, vertical	33.6 cm		**Weight & dimensions**	
Viewable size diagonal	68.5 cm		Width (with stand)	611.6 mm
Display diagonal (metric)	68.47 cm			
High Dynamic Range (HDR) supported	✘			

Display

Colour gamut standard	sRGB
Colour gamut	99%

Performance

NVIDIA G-SYNC *	✗
AMD FreeSync *	✗
Low Blue Light technology	✔

Multimedia

Built-in speaker(s) *	✗
Built-in camera *	✗

Design

Market positioning *	Business
Product colour *	Black
Front bezel colour	Black
Detachable stand	✔
Feet colour	Silver

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
HDMI *	✔
HDMI ports quantity	1
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone out *	✗
HDCP	✔

Network

Wi-Fi	✗

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Height adjustment *	✔
Height adjustment	15 cm
Pivot	✔
Pivot angle	90 - 90°
Swivelling	✔
Swivel angle range	-45 - 45°
Tilt adjustment	✔
Tilt angle range	-5 - 21°

Weight & dimensions

Depth (with stand)	185 mm
Height (with stand)	535.2 mm
Weight (with stand)	6.87 kg
Width (without stand)	611.6 mm
Depth (without stand)	52.1 mm
Height (without stand)	360.7 mm
Weight (without stand)	5.05 kg
Bezel width (side)	7.4 mm
Bezel width (top)	7.4 mm
Bezel width (bottom)	1.77 cm

Packaging data

Package weight	9.68 kg

Packaging content

Stand included	✔
Cables included	AC, DisplayPort, USB Type-A to USB Type-C, USB Type-C to USB Type-C
Quick start guide	✔
DisplayPort cable length	1.8 m

Sustainability

Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	PVC/BFR

Carbon footprint

Total carbon footprint (kg of CO2e)	727
Total carbon emissions, standard deviation (kg of CO2e)	172
Carbon emissions, manufacturing (kg of CO2e)	381
Carbon emissions, logistics (kg of CO2e)	87
Carbon emissions, energy usage (kg of CO2e)	254
Carbon emissions, end-of-life (kg of CO2e)	5
Total carbon emissions, w/o use phase (kg of CO2e)	473
PAIA version	1.3.0

Other features

Heavy metals free	Hg (mercury)
Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1

Logistics data

Harmonized System (HS) code	85285210

5397184656808

5704174839477

5704174839484

5704174839460