

## DELL P Series P3223DE LED display 80 cm (31.5") 2560 x 1440 pikseliä Quad HD LCD musta

Tuotemerkki : DELL

Tuoteperhe: P Series

Tuotekoodi: DELL-P3223DE

Tuotteen nimi : P3223DE

DELL P Series P3223DE. Näytön halkaisija: 80 cm (31.5"), Näytön erottelutarkkuus: 2560 x 1440 pikseliä, HD-tyyppi: Quad HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USBkeskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta






## Display

Display diagonal \* Display resolution \* HD type \* Native aspect ratio \* Display technology \* Panel type \* Backlight type Touchscreen \* Display brightness (typical) Response time \* Anti-glare screen Screen shape \* Supported video modes Contrast ratio (typical) \* Maximum refresh rate \* Viewing angle, horizontal Viewing angle, vertical Display number of colours \* Response time (fast) Pixel pitch Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric) High Dynamic Range (HDR) supported sRGB coverage (typical)

	Ergonomics	
80 cm (31.5") 2560 x 1440 pixels Quad HD 16:9 LCD IPS LED ★ 350 cd/m <sup>2</sup> 5 ms ✓ Flat 480p, 576p, 720p, 1080i, 1080p 1000:1 60 Hz 178° 178° 1.07 billion colours	On Screen Display (OSD) Plug and Play LED indicators	J J J
	Power	
	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	F Not available 30 kWh 29.9 W 0.3 W 183 W 0.3 W 100 - 240 V 50 - 60 Hz 2.3 A Internal A to G 1047046
0.2727 x 0.2727 mm	Operational conditions	
93.24 ppi 30 - 90 kHz 56 - 76 Hz 69.8 cm 39.3 cm 80 cm 80 cm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 20 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
	Weight & dimensions	
	Width (with stand) Depth (with stand) Height (with stand)	712.4 mm 230.1 mm 617.1 mm

Performance		Weight & dimensions	
NVIDIA G-SYNC *	×	Weight (with stand)	11.3 kg
AMD FreeSync *	×	Width (without stand)	712.4 mm
Low Blue Light technology	1	Depth (without stand)	54 mm
Multimedia		Height (without stand)	417.1 mm
		Weight (without stand)	7.06 kg
Built-in speaker(s) *	×	Bezel width (side) Bezel width (top)	7.55 mm 7.57 mm
Built-in camera *	×	Bezel width (bottom)	1.74 cm
Design			1.74 cm
Market positioning *	Business	Packaging data	
Product colour *	Black	Package weight	15.3 kg
Front bezel colour	Black	Packaging content	
Detachable stand	✓	Stand included	1
Feet colour	Silver	Cables included	AC, DisplayPort, USB Type-A to USB
Ports & interfaces			Type-C, USB Type-C to USB Type-C
Built-in USB hub *	1	Quick start guide	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	DisplayPort cable length	1.8 m
USB upstream port type	USB Type-C	Sustainability	
Number of USB Type-C upstream	1	Sustainability certificates	ENERGY STAR, TCO
ports quantity		Doesn't contain	PVC/BFR
USB Type-A downstream ports quantity	4	Carbon footprint	
USB Power Delivery up to	90 W	Total carbon footprint (kg of CO2e)	853
HDMI *	1	Total carbon emissions, standard	193
HDMI ports quantity	1	deviation (kg of CO2e)	155
HDMI version	1.4	Carbon emissions, manufacturing (kg of CO2e)	446
DisplayPorts quantity	2	Carbon emissions, logistics (kg of	142
DisplayPort version	1.4	CO2e)	143
Headphone out *	×	Carbon emissions, energy usage (kg	255
HDCP	✓	of CO2e) Carbon emissions, end-of-life (kg of	
Charging port type	USB Type-C	CO2e)	9
DC-in jack	✓	Total carbon emissions, w/o use	598
Network		phase (kg of CO2e)	
Wi-Fi	×	PAIA version	1.3.0
Ergonomics		Other features	
		Heavy metals free	Hg (mercury)
VESA mounting *	✓ 100 100 mm	Compliance certificates	RoHS
Panel mounting interface	100 x 100 mm	Ethernet LAN (RJ-45) ports	1
Cable lock slot *		Logistics data	
Height adjustment *		Harmonized System (HS) code	85285210
Height adjustment	15 cm		
Pivot	X		
Swivelling	✓		
Swivel angle range	-30 - 30°		
Tilt adjustment	<ul> <li>A 100</li> </ul>		
Tilt angle range	-5 - 21°		











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.