



TP-Link TL-SG1428PE verkkokytkin Hallittu L2 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : TP-Link

Tuotekoodi: TL-SG1428PE

Tuotteen nimi : TL-SG1428PE



TP-Link TL-SG1428PE. Kytkin tyyppi: Hallittu, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 26. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 56 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE.... Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Web-based management	✓	Form factor	1U
Ports & interfaces		Product colour	Black
Basic switching RJ-45 Ethernet ports quantity *	26	Number of fans	2 fan(s)
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity	26	Power source *	AC
SFP module slots quantity	2	Power supply included *	✓
Network		AC input voltage	100 - 240 V
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	AC input frequency	50 - 60 Hz
10G support *	✗	Power consumption (max)	1039.03 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE)	
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Power over Ethernet (PoE) *	✓
Port mirroring	✓	Power over Ethernet plus (PoE+) ports quantity	24
Flow control support	✓	Power over Ethernet (PoE) power per port	30 W
Link aggregation	✓	Total Power over Ethernet (PoE) budget	250 W
Broadcast storm control	✓	Operational conditions	
Rate limiting	✓	Operating temperature (T-T)	0 - 50 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-40 - 70 °C
Auto-negotiation	✓	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%
		Weight & dimensions	
		Width	440 mm

Network		Weight & dimensions	
VLAN support	✓	Depth	220 mm
Virtual LAN features	Port-based VLAN, Tagged VLAN	Height	44 mm
Number of VLANs	32	Packaging content	
Optical fiber		Cables included	AC
Fiber ethernet cabling technology	1000BASE-X	User guide	✓
Data transmission		Rack mount kit	✓
Switching capacity *	56 Gbit/s	Packaging data	
Forwarding rate	41.7 Mpps	Package width	336 mm
MAC address table *	8000 entries	Package depth	528 mm
Store-and-forward	✓	Package height	100 mm
Number of queues	4	Package weight	3.94 kg
Jumbo frames support	✓	Certificates	
Jumbo frames	10000	Certification	CE, FCC, RoHS
Packet buffer memory	4.1 MB	Logistics data	
Security		Harmonized System (HS) code	85176990
IGMP snooping	✓		
Security algorithms	SNMP, SNMPv2, SNMPv3		



6935364072216



6935364072209



0845973040482



845973040482

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.